DIN EN 12966:2019-02 (Englisch)

Road vertical signs - Variable message traffic signs (includes Amendment :2018)

Contents

Page

European foreword 7

Introduction 9

1 Scope 10

2 Normative references 10

3 Terms and definitions 11

4 Product characteristics 15
4.1 Dimensions and tolerances requirements 15
4.2 General design requirement 15
4.3 Visual performance requirements of continuous VMS 15
4.4 Visual performance requirements of discontinuous VMS 16
4.5 Physical performance requirements 25
4.6 Dangerous substances 28

5 Testing, assessment and sampling methods 29
5.1 Test sequence 29
5.2 Durability 29
5.3 Test modules 29
5.4 Physical performance test methods 31
5.5 Visual performance test methods 37

6 Assessment and verification of constancy of performance (AVCP) 46
6.1 General 46
6.2 Type testing 46
6.3 Factory production control (FPC) 52

7 Classification and designation 59
7.1 General 59
7.2 Continuous retro-reflective VMS 59
7.3 Continuous, externally illuminated retro-reflective VMS 59
7.4 Discontinuous VMS 60

8 Marking, labelling and packaging 61

9 Product information 61

Annex A (normative) Equivalent area 63

A.1 General 63
A.2 Calculation of the luminance 63
A.3 Calculation of non-matrix equivalent areas 66
A.3.1 Equivalent area for a line of elements 66
A.3.2 Equivalent area for a symbol fully populated with elements 67
A.3.3 Equivalent area for a symbol partially populated with elements 67

Annex B (normative) VMS performance declaration codes for marking 69

B.1 General 69

B.2 Code for continuous retro-reflective VMS ... 69
B.3 Code for externally illuminated continuous retro-reflective VMS ... 69
B.4 Code for discontinuous VMS ... 70

Annex L (informative) Terminology used in this European Standard ... 71

Annex M (informative) Guidance on graphics for discontinuous light emitting signs ... 73

M.1 General ... 73
M.2 Apparent luminance of lines and letter strokes ... 73

DIN EN 12966:2019-02 EN 12966:2014+A1:2018 (E) M.2.1 General ... 73
M.2.2 Further technical explanation of Apparent luminance ... 74
M.3 VMS with colour inversion ... 75
M.4 VMS without colour inversion ... 81

Annex N (informative) Guidance on dimensions , luminance, beam width, legibility and efficiency for discontinuous VMS ... 83

N.1 General ... 83
N.2 Dimensions ... 83
N.2.1 General ... 83
N.2.2 Text ... 84
N.2.3 Circles ... 84
N.2.4 Triangles ... 85
N.3 Luminance and beam width classes ... 85
N.4 Beam width and distances of legibility ... 90
N.4.1 Group of VMS, centred above the road ... 90
N.4.2 Group of VMS, not centred above the road ... 91
N.4.3 Curved road sections ... 92
N.4.4 Limits of legibility due to vertical beam ... 93
N.4.5 Calculation of recognition time ... 95
N.4.5.1General ... 95
N.4.5.2Distances ... in metres per second at various speeds 95
N.4.5.3Example ... of calculation of the recognition time 95
N.4.5.3.1 General ... 95
N.4.5.3.2 Using beam width class B2 ... 96
N.4.5.3.3 Using beam width class B4 ... 97
N.4.5.3.4 Using beam width class B6 ... 97
N.4.5.4Conclusions ... after calculation of recognition time 98
N.4.6 Luminance and luminance ratio ... 98
N.4.7 Beam width ... 99
N.5 Energy efficiency ... 99

Annex O (informative) Specific design issues ... 100

O.1 Finish ... 100
O.2 Front panels ... 100
O.3 Front screens ... 100
O.4 Appearance ... 100
O.5 Electrolytic compatibility ... 100
O.6 Protection against thermal overload ... 100
O.7 Physical security against unauthorized access ... 100
O.8 Interfaces between VMS, control, and higher order equipment ... 100
O.9 Diagnostic ... 101

Annex P (informative) Guidance for design of VMS messages ... 102

P.1 Design of VMS messages ... 102
P.2 Specifying text dimensions ... 103

Annex Q (informative) Technical documentation ... 106

Q.1 Sign enclosure 106
Q.2 Electrical equipment 106
Q.3 Mounting devices (if applicable) 106
Q.4 Retro-reflective and non retro-reflective components 106

Annex R (informative) Example of recommended summary of class combinations 108

DIN EN 12966:2019-02 EN 12966:2014+A1:2018 (E) Annex ZA (informative) !Relationship of this European Standard with Regulation (EU) No.305/2011 116

ZA.1 Scope and relevant characteristics 116

ZA.2 System of Assessment and Verification of Constancy of Performance (AVCP) 119

ZA.3 Assignment of AVCP tasks 119

ZA.4 The following clauses are not related to Regulation (EU) No 305/2011: 120

Bibliography 121

Figures Figure 1 -- Chromaticity areas for the colour classes C1 and C2 plotted in the CIE 1931 chromaticity diagram 18

Figure 2 -- Examples of passed and failed luminance distributions 23

Figure 3 -- Examples of variable message traffic sign test modules in front view - a) and c) - and side view b) 31

Figure 4 -- Side elevation of the set-up for the measurement of luminance and luminance ratio 38

Figure 5 -- Layout examples for a test module and the positioning of the measuring area (circle) of the luminance meter 43

Figure A.1 -- Merging of elements 63

Figure A.2 -- Character with a regular orthogonal matrix of (5 × 8) elements 64

Figure A.3 -- Open line 66

Figure A.4 -- Closed line 66

Figure A.5 -- Example of symbol with an area fully populated with elements 67

Figure A.6 -- Example of symbol with an area partially populated with elements 68

Figure B.1 -- Code of performance classes of continuous retro-reflective VMS 69

Figure B.2 -- Code of performance classes of externally illuminated continuous retro- reflective VMS 70

Figure B.3 -- Code of performance classes of discontinuous VMS 70

Figure L.1 -- Parts of a VMS 71

Figure L.2 -- Test configuration 72

Figure M.1 -- A legend seen at short (left), longer (centre), and very long distance (right) 74

Figure M.2 -- Example for calculation of dimensions of circular mandatory VMS 78

Figure M.3 -- Example for calculation of dimensions of circular mandatory VMS 79

Figure M.4 -- Example for calculation of dimensions of a triangular warning VMS 80

Figure M.5 -- Example of VMS using (64 × 64) elements with colour inversion 81

Figure M.6 -- Example of VMS using (48 × 48) elements with colour inversion 81

Figure M.7 -- Example of VMS using (32 × 32) elements with colour inversion 81

Figure M.8 -- Example of VMS using (64 × 64) elements, no colour inversion 82

Figure M.9 -- Example of VMS using (48 × 48) elements, no colour inversion 82

Figure M.10 -- Example of VMS using (32 × 32) elements, no colour inversion 82

Figure N.1 -- Relation between classes 86

Figure N.2 -- Example of coverage by beam width class B1 87

Figure N.3 -- Example of coverage by beam width class B3 88

Figure N.4 -- Example of coverage by beam width class B6 89

Figure N.5 -- Legibility of group of VMS, centred on gantry above the road 90

Figure N.6 -- Legibility of group of VMS, mounted on cantilever aside the road 91

Figure N.7-- Legibility of group of VMS, mounted on cantilever aside the road 93

Figure N.8-- Legibility of group of VMS, mounted on cantilever aside the road 94

Figure P.1 -- Example of the design of the letter E in a regular orthogonal matrix 102

Figure P.2 -- Equivalent text dimensions using uppercase characters 103

DIN EN 12966:2019-02 EN 12966:2014+A1:2018 (E) Figure P.3 -- Equivalent text dimensions using upper- and lower-case characters 104

Figure P.4 -- Equivalent text dimensions of full matrix display using proportional character spacing 105

Figure R.1-- Example of summary of the characteristics of products 109

Figure R.2 -- Example 1 for visual performance class combination 111

Figure R.3 -- Example 2 for visual performance class combination 112

Figure R.4 -- Example 3 for visual performance class combination 114

Figure R.5 -- Example 4 for visual performance class combination 115

Tables Table 1 -- Class designation of the visual performance parameters of VMS 16

Table 2 -- Corner points (CIE 1931 chromaticity co-ordinates x, y) of the chromaticity areas for the colours of class C1 17

Table 3 -- Corner points (CIE 1931 chromaticity co-ordinates x, y) of the chromaticity areas for the colours of class C2 17

Table 4 -- Le and La luminance limits for white on reference axis 19

Table 5 -- Le and La luminance limits for yellow on reference axis 20

Table 6 -- Le and La luminance limits for orange on reference axis 20

Table 7 -- Le and La luminance limits for green on reference axis 20

Table 8 -- Le and La luminance limits for red on reference axis 21

Table 9 -- Le and La luminance limits for blue on reference axis 21

Table 10 -- Minimum luminance ratio values (LR) for various colours and classes R1, R2 and R3, at test angles on the reference axis and off the reference axis 22

Table 11 -- Beam width classes 24

Table 12 -- Class designation 25

Table 13 -- Temperature range classes 25

Table 14 -- Ingress protection level classes 26

Table 15 -- Effect of voltage interruption 28

Table 16 -- Operating voltage range, power-up activation and temporary overvoltage tests 32

Table 17 -- Frequency and voltage tests 32

Table 18 -- Impact test 33

Table 19 -- Vibration test 33

Table 20 -- Corrosion test 34

Table 21 -- Water ingress test - Severity 34

Table 22 -- Dust ingress test - Severity 34

Table 23 -- Temperature test 35

Table 24 -- Test angles (in degrees, with respect to the reference axis), used for the measurement of luminance under external illumination and luminance ratio 39

Table 25 -- Test angles (in degrees, with respect to the reference axis), used for the measurement of luminance without external illumination 39

Table 26 -- Test angles (in degrees, with respect to the reference axis), used for the measurement of beam width, and for uniformity of luminous intensity and colour of monochromatic elements 40

Table 27 -- Test angles (in degrees, with respect to the reference axis), used for the measurement of uniformity of luminous intensity and colour of elements formed by mixing colours 41

Table 28 -- Characteristics of continuous VMS 47

Table 29 -- Characteristics of discontinuous VMS 49

Table 30 -- Identification label 52

Table 31 -- Minimum frequency of testing continuous VMS for product testing and evaluation as part of FPC 55

DIN EN 12966:2019-02 EN 12966:2014+A1:2018 (E) Table 32 -- Minimum frequency of testing discontinuous VMS for product testing and evaluation as part of FPC 56

Table M.1 -- Parameters for mandatory signs using a red circle 76

Table M.2 -- Parameters for mandatory signs using a red triangle 77

Table N.1 -- Minimum dimensions of text (mm) 84

Table N.2 -- Minimum dimensions of circles (mm) 85

Table N.3 -- Minimum dimensions of triangles (mm) 85

Table N.4 -- Examples for applications of beam width classes 86

Table N.5 -- Examples for recognition time depending on character height, speed and vertical beam width 94

Table N.6 -- Conversion from speed unit km/h to m/s 95

Table ZA.1 -- Relevant clauses for continuous VMS 116

Table ZA.2 -- Relevant clauses for discontinuous VMS 118

Table ZA.3 -- Assignment of AVCP tasks for VMS under system 1 120