ISO 17892-10:2018 (E)

Geotechnical investigation and testing — Laboratory testing of soil — Part 10: Direct shear tests

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Symbols

5 Apparatus

- 5.1 General
- 5.2 Shear devices
- 5.2.1 Shearbox test apparatus
- 5.2.2 Ring shear apparatus
- 5.3 Loading-devices
- 5.4 Measuring devices
- 5.4.1 Load measuring devices
- 5.4.2 Torque measuring devices
- 5.4.3 Displacement measuring devices
- 5.5 Ancillary apparatus

6 Test procedure

- 6.1 General requirements
- 6.2 Preparation of specimen
- 6.2.1 General requirements and selection of the preparation method
- 6.2.2 General requirements for preparation of specimens from undisturbed samples
- 6.2.3 Trimming from extruded or block samples
- 6.2.4 Extrusion from a tube of diameter larger than the mould and cutter
- 6.2.5 Preparation of laboratory fabricated specimens
- 6.3 Measurements before testing
- 6.4 Equipment preparation
- 6.5 Consolidation
- 6.6 Shearing

7 Test results

- 7.1 Water content
- 7.2 Initial dry density
- 7.3 Initial bulk density
- 7.4 Initial void ratio
- 7.5 Initial degree of saturation
- 7.6 Void ratio during testing
- 7.7 Stresses and displacements
- 7.7.1 Shearbox
- 7.7.2 Ring shear
- 7.8 Plotting

8 Test report

- 8.1 Mandatory reporting
- 8.2 Optional reporting

Annex A (normative) Calibration, maintenance and checks

A.1 General requirements
A.2 Environmental conditions
A.3 Equipment
A.3.1 Ovens
A.3.2 Thermometers
A.3.3 Balances
A.3.4 Deformation of apparatus
A.3.5 Loading devices
A.3.6 Dimensional measurement devices
A.3.7 Time measuring devices
A.3.8 Porous discs

Annex B (informative) Additional calculations for effective strength parameters

Page count: 23