ISO 3008-1:2019 (E)

Fire resistance tests — Door and shutter assemblies — Part 1: General requirements

Contents

Foreword

Introduction

1 Scope

2 Normative references

3 Terms and definitions

4 Test equipment

5 Test conditions

6 Test specimen

6.1 Size of specimen
6.2 Number of specimens
6.3 Design of specimen
6.4 Construction
6.5 Verification

7 Installation of test specimen

7.1 General
7.2 Supporting construction
7.3 Test construction
7.3.1 Associated and supporting construction
7.3.2 Associated construction
7.3.3 Supporting construction
7.3.4 Restraint on supporting construction
7.4 Gaps

8 Conditioning

8.1 Moisture content
8.2 Mechanical

9 Application of instrumentation

9.1 Temperature measurements
9.1.1 Furnace-temperature measuring instrument
9.1.2 Unexposed-face thermocouples
9.2 Maximum temperature
9.3 Temperature of door frame
9.4 Pressure measurements
9.5 Heat-flux measurement
9.5.1 General
9.5.2 Apparatus
9.5.3 Procedure
9.5.3.1 General positioning
9.5.3.2 Specific locations
9.5.4 Measurement
9.6 Deflection

10 Test procedure

11 Performance criteria

11.1 Integrity
11.2 Insulation

12 Test report

13 Field of direct application of test results

13.1 General
13.2 Timber constructions
13.3 Steel constructions
13.4 Glazed constructions
13.5 Fixings/hardware

Annex A (normative) Conditioning requirements for supporting constructions

A.1 General
A.2 Requirements

Annex B (informative) Estimation of radiant heat flux using measured surface temperatureand the Stefan-Boltzmann law

B.1 Introduction
B.2 Application
B.2.1 General
B.2.2 Specimen temperature measurement
B.2.3 Specimen emissivity
B.3 Example calculation

Page count: 52