

DIN EN 13384-1:2019-09 (E)

Chimneys - Thermal and fluid dynamic calculation methods - Part 1: Chimneys serving one heating combustion (includes Amendment A1:2019)

Contents		Page
European foreword		5
1	Scope	7
2	Normative references	7
3	Terms and definitions	7
4	Symbols and abbreviations	12
5	Calculation method for non-balanced flue chimneys	17
5.1	General principles	17
5.2	Pressure requirements	17
5.2.1	Negative pressure chimneys	17
5.2.2	Positive pressure chimneys	18
5.3	Temperature requirement	19
5.4	Calculation procedure	19
5.5	Flue gas data characterising the !combustion" appliance	20
5.5.1	General	20
5.5.2	!Flue gas mass flow and combustion air mass flow	20
5.5.3	Flue gas temperature	21
5.5.4	Minimum draught for the !combustion" appliance (PW) for negative pressure chimney	22
5.5.5	Maximum draught for the !combustion" appliance (PWmax) for negative pressure chimney	23
5.5.6	Maximum differential pressure of the !combustion" appliance (PWO) for positive pressure chimney	23
5.5.7	Minimum differential pressure of the !combustion" appliance (PWomin) for positive pressure chimney	23
5.6	Characteristic data for the calculation	23
5.6.1	General	23
5.6.2	Mean value for roughness (r)	23
5.6.3	Thermal resistance (1/)	23
5.7	Basic values for the calculation	24
5.7.1	Air temperatures	24
5.7.2	External air pressure (pL)	26
5.7.3	Gas constant	26
5.7.4	Density of the external air (L)	26
5.7.5	Specific heat capacity of the flue gas (cp)	27
5.7.6	Condensing temperature (Tsp)	27
5.7.7	Correction factor for temperature instability (SH)	27
5.7.8	Flow safety coefficient (SE)	27
5.8	Determination of the temperatures	27
5.8.1	General	27
5.8.2	Calculation of the coefficient of cooling (K)	28
5.8.3	Coefficient of heat transmission (kb)	28
5.9	Determination of the density of the flue gas and the velocity of the flue gas	31
5.9.1	Density of the flue gas (m)	31
5.9.2	Velocity of the flue gas (wm)	31
5.10	Determination of the pressures	31
5.10.1	Pressure at the flue gas inlet into the chimney	31
5.10.2	Theoretical draught available due to chimney effect (PH)	32

5.10.3	Pressure resistance of the chimney (PR)	33
5.10.4	Wind velocity pressure (PL)	34
5.11	Minimum draught required at the flue gas inlet into the chimney and maximum allowed draught (PZe and PZemax) and maximum and minimum differential pressure at the flue gas inlet into the chimney (PZOe and PZOemin)	35
5.11.1	General	35
5.11.2	Minimum and maximum draught for the "combustion" appliance (PW and PWmax) and maximum and minimum differential pressure of the "combustion" appliance (PWO and PWOmin)	36
5.11.3	Effective pressure resistance of the connecting flue pipe (PFV)	36
5.11.4	Pressure resistance of the air supply (PB)	37
5.12	Calculation of the inner wall temperature at the chimney outlet (Tiob)	38
6	Secondary air for negative pressure chimneys	40
6.1	General	40
6.2	Calculation method	40
6.3	Basic values for the calculation of secondary air	40
6.3.1	General	40
6.3.2	Mixing calculations	40
6.4	Pressures	41
6.4.1	Pressure resistance for the air supply with secondary air (PBNL)	41
6.4.2	Draught required for the secondary air devices (PNL)	43
6.4.3	Pressure resistance for that part of the connecting flue pipe before the secondary air device (PFV1)	44
6.4.4	Pressure requirement with secondary air	44
6.5	Temperature requirement with secondary air	44
7	Calculation method for balanced flue chimneys	45
7.1	General principles	45
7.2	Pressure requirements	46
7.3	Temperature requirements	46
7.4	Calculation procedure	46
7.5	Flue gas data characterizing the "combustion" appliance	47
7.6	Characteristic data for the calculation	47
7.7	Basic values for the calculation	47
7.7.1	Air temperatures	47
7.7.2	Other basic values	48
7.8	Determination of the temperatures	48
7.8.1	Non-concentric (separate) ducts	48
7.8.2	Concentric ducts - calculation based on a correction factor for heat radiation	49
7.8.3	Concentric ducts - calculation based on calculated heat radiation	64
7.8.4	Mean temperatures for pressure calculation	68
7.9	Determination of densities and velocities	69
7.9.1	Density and velocity of the flue gas	69
7.9.2	Density and velocity of the "combustion" air	69
7.10	Determination of pressures	70
7.10.1	Pressure at the flue gas inlet into the chimney	70
7.10.2	Theoretical draught due to chimney effect in the chimney segment (PH)	70
7.10.3	Pressure resistance in the chimney segment (PR)	70
7.10.4	Wind velocity pressure (PL)	70
7.11	Minimum draught required at the flue gas inlet into the chimney and maximum allowed draught (PZe and PZemax) and maximum and minimum differential pressure at the flue gas inlet into the chimney (PZOe and PZOemin)	71
7.11.1	General	71
7.11.2	Minimum and maximum draught for the "combustion" appliance (PW and PWmax) and maximum and minimum differential pressure of the "combustion" appliance (PWO and PWOmin)	71
7.11.3	Effective pressure resistance of the connection pipe (PFV)	71
7.11.4	Pressure resistance of the air supply	71
7.12	Calculation of the inner wall temperature at the chimney outlet (Tiob)	74
8	Consideration of the condensation heat of the flue gas water vapour	75

8.1	General	75
8.2	Onset of condensation	75
8.3	Calculation of the flue gas temperature at the outlet of a chimney segment with condensation (j NsegK)	78
9	Consideration of chimney fans	83
9.1	General	83
9.2	Inline fans	84
9.3	Exhaust fans	85
Annex A (informative) Calculation of thermal resistance		86
Annex B (informative) Tables		87
Annex C (informative) Chimney outlet with regard to adjacent buildings		104
Annex D (informative) Determination of the gas constant R considering the condensation		105