DIN EN 13384-1:2019-09 (E)

Chimneys - Thermal and fluid dynamic calculation methods - Part 1: Chimneys serving one heating combustion (includes Amendment A1:2019)

Contents

Page

European foreword 5

1 Scope 7

2 Normative references 7

3 Terms and definitions 7

4 Symbols and abbreviations 12

5 Calculation method for non-balanced flue chimneys 17
5.1 General principles 17
5.2 Pressure requirements 17
5.2.1 Negative pressure chimneys 17
5.2.2 Positive pressure chimneys 18
5.3 Temperature requirement 19
5.4 Calculation procedure 19
5.5 Flue gas data characterising the !combustion"appliance 20
5.5.1 General 20
5.5.2 !Flue gas mass flow and combustion air mass flow 20
5.5.3 Flue gas temperature 21
5.5.4 Minimum draught for the !combustion" appliance (PW) for negative pressure chimney 22
5.5.5 Maximum draught for the !combustion" appliance (PWmax) for negative pressure chimney 23
5.5.6 Maximum differential pressure of the !combustion" appliance (PWO) for positive pressure chimney 23
5.5.7 Minimum differential pressure of the !combustion" appliance (PWOmin) for positive pressure chimney 23
5.6 Characteristic data for the calculation 23
5.6.1 General 23
5.6.2 Mean value for roughness (r) 23
5.6.3 Thermal resistance (1/) 23
5.7 Basic values for the calculation 24
5.7.1 Air temperatures 24
5.7.2 External air pressure (pL) 26
5.7.3 Gas constant 26
5.7.4 Density of the external air (L) 26
5.7.5 Specific heat capacity of the flue gas (cp) 27
5.7.6 Condensing temperature (Tsp) 27
5.7.7 Correction factor for temperature instability (SH) 27
5.7.8 Flow safety coefficient (SE) 27
5.8 Determination of the temperatures 27
5.8.1 General 27
5.8.2 Calculation of the coefficient of cooling (K) 28
5.8.3 Coefficient of heat transmission (kb) 28
5.9 Determination of the density of the flue gas and the velocity of the flue gas 31
5.9.1 Density of the flue gas (m) 31
5.9.2 Velocity of the flue gas (wm) 31
5.10 Determination of the pressures 31
5.10.1 Pressure at the flue gas inlet into the chimney 31
5.10.2 Theoretical draught available due to chimney effect (PH) 32

5.10.3 Pressure resistance of the chimney (PR) ... 33
5.10.4 Wind velocity pressure (PL) ... 34
5.11 Minimum draught required at the flue gas inlet into the chimney and maximum allowed draught (PZe and PZemax) and maximum and minimum differential pressure at the flue gas inlet into the chimney (PZOe and PZOemin) ... 35
5.11.1 General ... 35
5.11.2 Minimum and maximum draught for the !combustion" appliance (PW and PWmax) and maximum and minimum differential pressure of the !combustion" appliance (PWO and PWOmin) ... 36
5.11.3 Effective pressure resistance of the connecting flue pipe (PFV) ... 36
5.11.4 Pressure resistance of the air supply (PB) ... 37
5.12 Calculation of the inner wall temperature at the chimney outlet (Tiob) ... 38

6 Secondary air for negative pressure chimneys ... 40
6.1 General ... 40
6.2 Calculation method ... 40
6.3 Basic values for the calculation of secondary air ... 40
6.3.1 General ... 40
6.3.2 Mixing calculations ... 40
6.4 Pressures ... 41
6.4.1 Pressure resistance for the air supply with secondary air (PBNL) ... 41
6.4.2 Draught required for the secondary air devices (PNL) ... 43
6.4.3 Pressure resistance for that part of the connecting flue pipe before the secondary air device (PFV1) ... 44
6.4.4 Pressure requirement with secondary air ... 44
6.5 Temperature requirement with secondary air ... 44

7 Calculation method for balanced flue chimneys ... 45
7.1 General principles ... 45
7.2 Pressure requirements ... 46
7.3 Temperature requirements ... 46
7.4 Calculation procedure ... 46
7.5 Flue gas data characterizing the !combustion" appliance ... 47
7.6 Characteristic data for the calculation ... 47
7.7 Basic values for the calculation ... 47
7.7.1 Air temperatures ... 47
7.7.2 Other basic values ... 48
7.8 Determination of the temperatures ... 48
7.8.1 Non-concentric (separate) ducts ... 48
7.8.2 Concentric ducts - calculation based on a correction factor for heat radiation ... 49
7.8.3 Concentric ducts - calculation based on calculated heat radiation ... 64
7.8.4 Mean temperatures for pressure calculation ... 68
7.9 Determination of densities and velocities ... 69
7.9.1 Density and velocity of the flue gas ... 69
7.9.2 Density and velocity of the !combustion" air ... 69
7.10 Determination of pressures ... 70
7.10.1 Pressure at the flue gas inlet into the chimney ... 70
7.10.2 Theoretical draught due to chimney effect in the chimney segment (PH) ... 70
7.10.3 Pressure resistance in the chimney segment (PR) ... 70
7.10.4 Wind velocity pressure (PL) ... 70
7.11 Minimum draught required at the flue gas inlet into the chimney and maximum allowed draught (PZe and PZemax) and maximum and minimum differential pressure at the flue gas inlet into the chimney (PZOe and PZOemin) ... 71
7.11.1 General ... 71
7.11.2 Minimum and maximum draught for the !combustion" appliance (PW and PWmax) and maximum and minimum differential pressure of the !combustion" appliance (PWO and PWOmin) ... 71
7.11.3 Effective pressure resistance of the connection pipe (PFV) ... 71
7.11.4 Pressure resistance of the air supply ... 71
7.12 Calculation of the inner wall temperature at the chimney outlet (Tiob) ... 74

8 Consideration of the condensation heat of the flue gas water vapour ... 75

8.1 General 75
8.2 Onset of condensation 75
8.3 Calculation of the flue gas temperature at the outlet of a chimney segment with condensation (j NsegK) 78

9 Consideration of chimney fans 83
9.1 General 83
9.2 Inline fans 84
9.3 Exhaust fans 85

Annex A (informative) Calculation of thermal resistance 86

Annex B (informative) Tables 87

Annex C (informative) Chimney outlet with regard to adjacent buildings 104

Annex D (informative) Determination of the gas constant R considering the condensation 105