

DIN EN 13384-2:2019-09 (E)

Chimneys - Thermal and fluid dynamic calculation methods - Part 2: Chimneys serving more than one combustion appliance (includes Amendment A1:2019)

Contents		Page
European foreword		5
Introduction		7
1	Scope	8
2	Normative references	8
3	Terms and definitions	9
4	General symbols and abbreviations	10
5	Calculation method	10
5.1	General principles	10
5.2	Pressure equilibrium condition	12
5.2.1	Negative pressure chimneys	12
5.2.2	Positive pressure chimneys	13
5.3	Mass flow requirement	14
5.4	Pressure requirements	14
5.4.1	Negative pressure chimneys	14
5.4.2	Positive pressure chimneys	15
5.5	Temperature requirement	16
5.6	Calculation procedure	17
6	Flue gas data characterising the "combustion" appliance	19
7	Data for chimney and connecting flue pipes	21
8	Basic data for the calculation	21
8.1	General	21
8.2	Air temperatures	21
8.2.1	External air temperature (TL)	21
8.2.2	Ambient air temperature (Tu)	21
8.3	External air pressure (pL)	21
8.4	Gas constant	21
8.4.1	Gas constant of the air (RL)	21
8.4.2	Gas constant of flue gas (R)	21
8.5	Density of air (L)	21
8.6	Specific heat capacity of the flue gas (cp)	21
8.7	Water vapour content ((H2O),j) and condensing temperature (Tsp)	22
8.8	Correction factor for temperature instability (SH)	22
8.9	Flow safety coefficient (SE)	22
8.10	External coefficient of heat transfer	22
9	Determination of temperatures	22
10	Mixing calculations	24
10.1	General	24
10.2	Flue gas mass flow (j,m)	24
10.3	Flue gas temperature at the inlet of the chimney segment (Te,j)	24
10.4	CO2-content of the flue gas in the chimney segment ((CO2),j)	24

10.5	H ₂ O-content of the flue gas ((H ₂ O) _j)	25
10.6	Gas constant of the flue gas (R _j)	25
10.7	Flue gas data	25
10.7.1	Specific heat capacity (cpV _j), (cp _j)	25
10.7.2	Thermal conductivity of the flue gas (AV _j), (A _j)	26
10.7.3	Dynamic viscosity (AV _j), (A _j)	26
10.7.4	Condensing temperature (TSP)	26
11	Density and velocity of the flue gas	27
12	Determination of the pressures	27
12.1	Pressures at each inlet of the chimney segments	27
12.1.1	Draught	27
12.1.2	Positive pressure	28
12.1.3	Draught due to chimney effect in the chimney segment (PH _j)	28
12.1.4	Pressure resistance in the chimney segment (PR _j)	28
12.2	Minimum draught required at the flue gas inlet into the chimney and maximum allowed draught (PZe and PZemax) and maximum and minimum differential pressure at the flue gas inlet into the chimney (PZOe and PZOemin)	31
12.2.1	Minimum required and maximum allowed draught	31
12.2.2	Maximum available and minimum allowed differential pressure	31
12.2.3	Calculated pressure resistance of the connecting flue pipe (PV _j)	31
12.2.4	Calculated pressure resistance of the air supply (PBC _j)	33
13	Inner wall temperature	34
14	Cascade installations	35
14.1	Principle of the calculation method	35
14.2	Pressure equilibrium condition	35
14.2.1	Negative pressure cascade installation	35
14.2.2	Positive pressure cascade installation	36
14.3	Mass flow requirement	37
14.4	Pressure requirements	37
14.4.1	Negative pressure chimneys	37
14.4.2	Positive pressure chimneys	38
14.5	Temperature requirement	39
14.6	Calculation procedure	39
14.7	Pressures at the outlet of the connecting flue pipe and pressures at the inlet of the collector segment	40
14.7.1	Pressure at the flue gas inlet into the collector segment (PZC _{j,l} or PZOC _{j,l})	40
14.7.2	Pressures required or available at the outlet of the connecting flue pipe (PZeC _{j,l} , PZOeC _{j,l})	43
14.8	Inner wall temperature (TiobC _{j,l})	45
15	Balanced flue chimney	45
15.1	Principle of the calculation method	45
15.2	Pressure equilibrium condition	46
15.3	Mass flow requirement	46
15.4	Pressure requirements	46
15.4.1	Negative pressure chimneys	46
15.4.2	Positive pressure chimneys	47
15.5	Temperature requirements	48
15.6	Calculation procedure for balanced flue chimneys	48
15.7	Mass flow of the "combustion" air	50
15.8	Determination of the temperatures in balanced flue chimneys	51
15.8.1	Separate ducts	51
15.8.2	Concentric ducts	51
15.8.3	Concentric connection pipes	59
15.9	Pressures of the air supply ducts	65
15.9.1	Draught due to chimney effect of the air supply duct of chimney segment j	65
15.9.2	Draught due to chimney effect of the air supply duct of connection pipes	65
15.9.3	Pressure resistance of the air supply duct of the chimney segment j (PRB _j)	66

15.9.4	Pressure resistance of the air supply duct of the connection pipe j (PRBV,j)	67
15.10	Density and velocity of the "combustion" air	69
15.10.1	Density and velocity of the "combustion" air in the air supply duct averaged over the length of the chimney segment	69
15.10.2	Density and velocity of the "combustion" air averaged over the length of the connection pipes	70
16	Consideration of chimney fans	70
16.1	General	70
16.2	Inline fans	71
16.3	Exhaust fans	72
Annex A (informative) Recommendations		74
A.1	General	74
A.2	Recommendations for the chimney and "combustion" appliances	74
A.3	Recommendations for connecting flue pipes	74
Annex B (informative) Characteristics for the "combustion" appliance		75