

# DIN 18008-2:2020-05 (E)

## Glass in Building - Design and construction rules - Part 2: Linearly supported glazings

---

Contents	Page
Foreword .....	3
1 Scope .....	4
2 Normative references .....	4
3 Terms and definitions.....	4
4 Construction products .....	4
5 Conditions for use .....	5
6 Actions and verifications .....	5
6.1 Verification of the ultimate limit state and serviceability limit state .....	5
6.2 Verification of residual load-bearing capacity .....	7
<b>Annex A</b> (informative) <b>Approximation methods for determination of climatic loads and distribution of actions</b> .....	<b>8</b>
A.1 General .....	8
A.2 Calculation of the individual panes' proportions $\delta_a$ and $\delta_i$ in the total bending stiffness .....	8
A.3 Calculation of the characteristic edge length $a^*$ .....	9
A.4 Calculation of factor $\varphi$ .....	9
A.5 Determination of the isochoric pressure $p_0$ .....	10
A.6 Distribution of actions .....	10
<b>Annex B</b> (normative) <b>Structures with verified residual load-bearing capacity</b> .....	<b>13</b>
B.1 Overhead glazing.....	13
B.1.1 General .....	13
B.1.2 Glazing made of laminated safety glass (LSG).....	13
B.1.3 Glazing made of wired glass.....	13
B.2 Vertical glazing.....	13
<b>Annex C</b> (informative) <b>Measures for ensuring the required reliability for the use of monolithic heat-soaked thermally toughened soda lime silicate safety glass in accordance with DIN EN 14179-1 and -2 above 4 m installation height</b> .....	<b>15</b>
Bibliography .....	16

## Figures

Figure A.1 — Examples: wind pressure (left), positive or negative pressure (centre or right) .....	10
--	----

## Tables

Table A.1 — Factor $B_V$ .....	9
Table A.2 — Distribution of actions .....	10
Table A.3 — Proportion of the stiffness of individual panes in the total stiffness.....	11