

# DIN EN 13381-10:2020-08 (E)

## Test methods for determining the contribution to the fire resistance of structural members - Part 10: Applied protection to solid steel bars in tension

---

<b>Contents</b>		<b>Page</b>
European foreword .....		4
Introduction .....		5
<b>1</b>	<b>Scope .....</b>	<b>6</b>
<b>2</b>	<b>Normative references .....</b>	<b>7</b>
<b>3</b>	<b>Terms and definitions, symbols and units .....</b>	<b>7</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>7</b>
<b>3.2</b>	<b>Symbols and units .....</b>	<b>8</b>
<b>4</b>	<b>Test equipment .....</b>	<b>9</b>
<b>4.1</b>	<b>General .....</b>	<b>9</b>
<b>4.2</b>	<b>Furnace .....</b>	<b>9</b>
<b>5</b>	<b>Test procedures .....</b>	<b>9</b>
<b>5.1</b>	<b>General .....</b>	<b>9</b>
<b>5.2</b>	<b>Support conditions .....</b>	<b>9</b>
<b>5.3</b>	<b>Number of test specimens .....</b>	<b>9</b>
<b>5.4</b>	<b>Size of test specimens .....</b>	<b>10</b>
<b>5.5</b>	<b>Construction of steel test specimens .....</b>	<b>10</b>
<b>5.5.1</b>	<b>Steel specification .....</b>	<b>10</b>
<b>5.5.2</b>	<b>Surface treatment and application of the fire protection material .....</b>	<b>10</b>
<b>5.6</b>	<b>Composition of fire protection materials .....</b>	<b>10</b>
<b>5.6.1</b>	<b>General .....</b>	<b>10</b>
<b>5.6.2</b>	<b>Thickness of applied reactive protection materials .....</b>	<b>10</b>
<b>5.7</b>	<b>Selection of test specimens .....</b>	<b>10</b>
<b>6</b>	<b>Installation of the test specimens .....</b>	<b>12</b>
<b>6.1</b>	<b>Test specimen installation patterns .....</b>	<b>12</b>
<b>6.2</b>	<b>Installation of the steel bars .....</b>	<b>13</b>
<b>6.3</b>	<b>Furnace Load .....</b>	<b>13</b>
<b>7</b>	<b>Conditioning of the test specimens .....</b>	<b>13</b>
<b>8</b>	<b>Application of instrumentation .....</b>	<b>13</b>
<b>8.1</b>	<b>General .....</b>	<b>13</b>
<b>8.2</b>	<b>Instrumentation for measurement and control of furnace temperature .....</b>	<b>13</b>
<b>8.2.1</b>	<b>General .....</b>	<b>13</b>
<b>8.2.2</b>	<b>Furnace temperature in the region of test specimens .....</b>	<b>13</b>
<b>8.3</b>	<b>Instrumentation for the measurement of steel temperatures .....</b>	<b>14</b>
<b>8.4</b>	<b>Instrumentation for the measurement of pressure .....</b>	<b>14</b>
<b>9</b>	<b>Test procedure .....</b>	<b>14</b>
<b>9.1</b>	<b>General .....</b>	<b>14</b>
<b>9.2</b>	<b>Furnace temperature and pressure .....</b>	<b>14</b>
<b>9.3</b>	<b>Temperature of steelwork .....</b>	<b>14</b>
<b>9.4</b>	<b>Observations .....</b>	<b>15</b>
<b>9.5</b>	<b>Termination of test .....</b>	<b>15</b>

<b>10</b>	<b>Test results .....</b>	<b>15</b>
<b>10.1</b>	<b>Acceptability of test results .....</b>	<b>15</b>
<b>10.2</b>	<b>Presentation of test results in the test report .....</b>	<b>15</b>
<b>11</b>	<b>Assessment .....</b>	<b>16</b>
<b>11.1</b>	<b>General .....</b>	<b>16</b>
<b>11.2</b>	<b>Assessment procedure for thermal performance .....</b>	<b>16</b>
<b>12</b>	<b>Report of the assessment .....</b>	<b>16</b>
<b>13</b>	<b>Limits of the applicability of the results of the assessment .....</b>	<b>17</b>
<b>13.1</b>	<b>General .....</b>	<b>17</b>
<b>13.2</b>	<b>Range in fire protection thickness .....</b>	<b>17</b>
<b>13.3</b>	<b>Range in dimensions .....</b>	<b>17</b>
<b>Annex A (normative) Linear interpolation analysis .....</b>		<b>20</b>
<b>Annex B (normative) Loaded test .....</b>		<b>26</b>
<b>B.1</b>	<b>General .....</b>	<b>26</b>
<b>B.2</b>	<b>Test equipment .....</b>	<b>26</b>
<b>B.3</b>	<b>Test specimens .....</b>	<b>26</b>
<b>B.4</b>	<b>Application of instrumentation .....</b>	<b>26</b>
<b>B.5</b>	<b>Installation of test specimens .....</b>	<b>26</b>
<b>B.6</b>	<b>Application of load .....</b>	<b>26</b>
<b>B.7</b>	<b>Correction of data .....</b>	<b>27</b>
<b>Annex C (normative) Maximum thickness selection and stickability correction for reactive coatings .....</b>		<b>28</b>
<b>Annex D (informative) A-deviations .....</b>		<b>30</b>
<b>Bibliography .....</b>		<b>31</b>