

# DIN EN 1745:2020-10 (E)

## Masonry and masonry products - Methods for determining thermal properties

---

<b>Contents</b>		<b>Page</b>
European foreword .....		4
Introduction .....		5
<b>1</b>	<b>Scope .....</b>	<b>8</b>
<b>2</b>	<b>Normative references .....</b>	<b>8</b>
<b>3</b>	<b>Terms, definitions and symbols .....</b>	<b>9</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>9</b>
<b>3.2</b>	<b>Symbols .....</b>	<b>10</b>
<b>4</b>	<b>Determination of 10,dry, unit -values for solid masonry units and 10,dry,mor -values for mortars .....</b>	<b>11</b>
<b>4.1</b>	<b>General .....</b>	<b>11</b>
<b>4.2</b>	<b>10,dry, mat -values for solid masonry units and mortars .....</b>	<b>12</b>
<b>4.2.1</b>	<b>Method S1. Determination of 10,dry,unit -values from tabulated 10,dry,mat /net dry density relationship .....</b>	<b>12</b>
<b>4.2.2</b>	<b>Method S2. Determination of 10,dry,unit -values based on 10,dry,mat /net dry density curve .....</b>	<b>12</b>
<b>4.2.3</b>	<b>Method S3. Determination of 10,dry,unit -values from determining the thermal transmittance (U<sub>mas</sub>) of masonry built from solid masonry units and mortar .....</b>	<b>14</b>
<b>4.3</b>	<b>Test methods and numbers of samples to be taken .....</b>	<b>16</b>
<b>5</b>	<b>Determination of equivalent 10,dry,unit -values for masonry units with formed voids and composite masonry units .....</b>	<b>16</b>
<b>5.1</b>	<b>General .....</b>	<b>16</b>
<b>5.2</b>	<b>Calculation methods .....</b>	<b>17</b>
<b>5.3</b>	<b>10,dry,unit -values of masonry units with formed voids and composite units .....</b>	<b>17</b>
<b>5.3.1</b>	<b>Determination of 10,dry,unit -values from tabulated unit /mat relationship .....</b>	<b>17</b>
<b>5.3.2</b>	<b>Determination of 10,dry,unit-values based on calculation .....</b>	<b>18</b>
<b>5.3.3</b>	<b>Method P5. Determination of 10,dry,unit -values from determining the thermal transmittance (U<sub>mas</sub>) of masonry built from masonry units with formed voids or composite masonry units and mortar .....</b>	<b>18</b>
<b>5.4</b>	<b>Test methods and numbers of samples to be taken .....</b>	<b>21</b>
<b>6</b>	<b>Moisture conversion .....</b>	<b>22</b>
<b>6.1</b>	<b>General .....</b>	<b>22</b>
<b>6.2</b>	<b>Procedure A (for materials, mortar, solid masonry units and masonry): .....</b>	<b>22</b>
<b>6.3</b>	<b>Procedure B (for masonry units with formed voids): .....</b>	<b>23</b>
<b>6.4</b>	<b>Procedure C (for composite masonry units): .....</b>	<b>23</b>
<b>7</b>	<b>Determination of design thermal values (R<sub>design,mas</sub> or design,mas) for masonry built from masonry units and mortar .....</b>	<b>23</b>
<b>7.1</b>	<b>General .....</b>	<b>23</b>
<b>7.2</b>	<b>R<sub>design,mas</sub> - or design,mas -values based on calculation .....</b>	<b>24</b>
<b>7.2.1</b>	<b>R<sub>design,mas</sub> - or design,mas -values based on design -values for the masonry units and the mortar .....</b>	<b>24</b>
<b>7.2.2</b>	<b>R<sub>design,mas</sub> -or design,mas -values using a numerical calculation method based on the design thermal conductivity of the materials used - .....</b>	<b>24</b>
<b>7.3</b>	<b>R<sub>design,mas</sub> - or design,mas -values of masonry built from masonry units with formed voids and mortar based on tabulated values .....</b>	<b>24</b>

7.3.1	Tabulated values .....	24
7.3.2	Application of Annex B .....	25
7.3.3	Alternative application of Annex B .....	25
7.4	Method S4/P6 R <sub>design,mas</sub> - or design,mas -values of masonry based on masonry testing .....	26
8	Determination of the thermal transmittance of masonry .....	26
9	Specific heat capacity .....	27
10	Rounding rules for $\mu$ -values for masonry units and masonry .....	27
Annex A (normative) Tabulated $\mu_{dry,mat}$ -values of materials used for masonry products .....		28
Annex B (informative) R <sub>dry,mas</sub> - or $\mu_{dry,mas}$ -values of masonry built from a range of masonry units containing formed voids .....		38
Annex C (informative) Example of how to use the tables in Annex B .....		78
Annex D (normative) Requirements for appropriate calculation procedures .....		80
D.1	Capabilities of the program .....	80
D.2	Input data and results .....	80
D.3	Testing of the program accuracy .....	81
D.4	Reference cases .....	81
D.4.1	Case 1: Calculation of thermal resistance R and thermal conductivity $\mu_{dry}$ ,unit of a masonry unit (vertically perforated unit) .....	81
D.4.2	Case 2: Calculation of thermal resistance R <sub>dry,mas</sub> of masonry consisting of vertically perforated masonry units, bed joints with mortar layers and internal/ external plaster layers .....	83
D.4.3	CASE 3: Calculation of thermal resistance R <sub>t</sub> of masonry consisting of masonry units, horizontal mortar layers, vertical mortar pockets and additional external insulation layer .....	85
Annex E (informative) Assessment and verification of constancy of performance .....		89
Annex F (informative) Alternative procedure for the moisture correction of units with formed voids .....		91
Annex G (informative) Simplified methodology for determining design moisture content of composite masonry units .....		92