

DIN EN 1745:2020-10 (E)

Masonry and masonry products - Methods for determining thermal properties

Contents		Page
European foreword		4
Introduction		5
1	Scope	8
2	Normative references	8
3	Terms, definitions and symbols	9
3.1	Terms and definitions	9
3.2	Symbols	10
4	Determination of 10,dry, unit -values for solid masonry units and 10,dry,mor -values for mortars	11
4.1	General	11
4.2	10,dry, mat -values for solid masonry units and mortars	12
4.2.1	Method S1. Determination of 10,dry,unit -values from tabulated 10,dry,mat /net dry density relationship	12
4.2.2	Method S2. Determination of 10,dry,unit -values based on 10,dry,mat /net dry density curve	12
4.2.3	Method S3. Determination of 10,dry,unit -values from determining the thermal transmittance (U_{mas}) of masonry built from solid masonry units and mortar	14
4.3	Test methods and numbers of samples to be taken	16
5	Determination of equivalent 10,dry,unit -values for masonry units with formed voids and composite masonry units	16
5.1	General	16
5.2	Calculation methods	17
5.3	10,dry,unit -values of masonry units with formed voids and composite units	17
5.3.1	Determination of 10,dry,unit -values from tabulated unit /mat relationship	17
5.3.2	Determination of 10,dry,unit-values based on calculation	18
5.3.3	Method P5. Determination of 10,dry,unit -values from determining the thermal transmittance (U_{mas}) of masonry built from masonry units with formed voids or composite masonry units and mortar	18
5.4	Test methods and numbers of samples to be taken	21
6	Moisture conversion	22
6.1	General	22
6.2	Procedure A (for materials, mortar, solid masonry units and masonry):	22
6.3	Procedure B (for masonry units with formed voids):	23
6.4	Procedure C (for composite masonry units):	23
7	Determination of design thermal values (R_{design,mas} or design,mas) for masonry built from masonry units and mortar	23
7.1	General	23
7.2	R_{design,mas} - or design,mas -values based on calculation	24
7.2.1	R_{design,mas} - or design,mas -values based on design -values for the masonry units and the mortar	24
7.2.2	R_{design,mas} -or design,mas -values using a numerical calculation method based on the design thermal conductivity of the materials used -	24
7.3	R_{design,mas} - or design,mas -values of masonry built from masonry units with formed voids and mortar based on tabulated values	24

7.3.1	Tabulated values	24
7.3.2	Application of Annex B	25
7.3.3	Alternative application of Annex B	25
7.4	Method S4/P6 R _{design,m_{as}} - or design,m _{as} -values of masonry based on masonry testing	26
8	Determination of the thermal transmittance of masonry	26
9	Specific heat capacity	27
10	Rounding rules for μ -values for masonry units and masonry	27
Annex A (normative) Tabulated $\mu_{10,dry,mat}$ -values of materials used for masonry products		28
Annex B (informative) R _{dry,m_{as}} - or $\mu_{10,dry,mas}$ -values of masonry built from a range of masonry units containing formed voids		38
Annex C (informative) Example of how to use the tables in Annex B		78
Annex D (normative) Requirements for appropriate calculation procedures		80
D.1	Capabilities of the program	80
D.2	Input data and results	80
D.3	Testing of the program accuracy	81
D.4	Reference cases	81
D.4.1	Case 1: Calculation of thermal resistance R and thermal conductivity $\mu_{10,dry}$,unit of a masonry unit (vertically perforated unit)	81
D.4.2	Case 2: Calculation of thermal resistance R _{dry,m_{as}} of masonry consisting of vertically perforated masonry units, bed joints with mortar layers and internal/ external plaster layers	83
D.4.3	CASE 3: Calculation of thermal resistance R _t of masonry consisting of masonry units, horizontal mortar layers, vertical mortar pockets and additional external insulation layer	85
Annex E (informative) Assessment and verification of constancy of performance		89
Annex F (informative) Alternative procedure for the moisture correction of units with formed voids		91
Annex G (informative) Simplified methodology for determining design moisture content of composite masonry units		92