

ISO/TR 23932-2:2020-03 (E)

Fire safety engineering - General principles - Part 2: Example of a dry-cleaning store

Contents		Page
Foreword		iv
Introduction		v
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Objective	1
5	Example of FSE process applied to a dry-cleaning store	1
5.1	Scope of the project concerning FSE process (ISO 23932-1:2018, Clause 5)	1
5.2	Identification of fire safety objectives (ISO 23932-1:2018, Clause 6)	7
5.2.1	Safety of life	7
5.2.2	Conservation of property	7
5.3	Identification of functional requirements (ISO 23932-1:2018, Clause 7)	8
5.3.1	Occupant protection	8
5.3.2	Protection of neighbours	8
5.3.3	Protection of fire fighters	8
5.3.4	Property protection	8
5.4	Selection of risk analysis approach (ISO 23932-1:2018, Clause 8)	8
5.5	Identification of performance criteria (ISO 23932-1:2018, Clause 9)	8
5.5.1	Protection of occupants of the shop	8
5.5.2	Protection of neighbours	9
5.5.3	Protection of fire fighters	9
5.5.4	Property protection	9
5.6	Fire safety design plan (ISO 23932-1:2018, Clause 10)	9
5.6.1	Development of the proposed solution	9
5.6.2	Description of the management of fire safety	11
5.6.3	Design proposal	11
5.7	Fire and behavioural scenarios (ISO 23932-1:2018, Clause 11)	14
5.7.1	Hazard identification	14
5.7.2	Fire scenarios	14
5.7.3	Behavioural scenarios	17
5.8	Selection of engineering methods (ISO 23932-1:2018, Clause 12)	18
5.9	Scenario-based evaluation of trial design (ISO 23932-1:2018, Clause 13)	18
5.9.1	Quantification of design fire scenarios	18
5.9.2	Comparison with performance criteria	40
5.10	Conditions of use of the built environment (ISO 23932-1:2018, 14.3)	41
5.10.1	Operating conditions	41
5.10.2	Levels and required control frequency	42
Bibliography		43