DIN EN 12150-1:2020-07 (E)

Glass in building - Thermally toughened soda lime silicate safety glass - Part 1: Definition and description

Contents

Page

European foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 7

4 Glass products 8

5 Fracture characteristics 9

6 Dimensions and tolerances 9
6.1 Nominal thickness and thickness tolerances 9
6.2 Width and length (sizes) 10
6.2.1 General 10
6.2.2 Maximum and minimum sizes 11
6.2.3 Tolerances and squareness 11
6.2.4 Edge deformation produced by the vertical process 12
6.3 Flatness 12
6.3.1 General 12
6.3.2 Measurement of overall bow 14
6.3.3 Measurement of !wave distortion and roller wave distortion" 15
6.3.4 Measurement of edge lift (for horizontally toughened glass only) 16
6.3.5 Measurement of perimeter deformation of glass produced by air cushion toughening process 17
6.3.6 Measurement of local distortion (for vertically toughened glass only) 18
6.3.7 Limitation on overall bow, roller waves and edge lift for horizontally toughened glass 18
6.3.8 Limitation on overall bow, wave and perimeter deformation for toughened glass manufactured by air cushion process 19
6.3.9 Limitation on overall bow and local distortion for vertically toughened glass 20
6.3.10 Other distortions 21

7 Edge and/or surface work, holes, notches and cut-outs 21
7.1 Warning 21
7.2 Edge working of glass for toughening 21
7.3 Profiled edges 22
7.4 Round holes 22
7.4.1 General 22
7.4.2 Diameter of holes 22
7.4.3 Limitations on position of holes 22
7.4.4 Tolerances on hole diameters 24
7.4.5 Tolerances on position of holes 24
7.5 Holes/others 25
7.6 Notches and cut-outs 25
7.7 Shaped panes 26

8 Fragmentation test 26
8.1 General 26

8.2 Dimensions and number of test specimens 26
8.3 Test procedure 26
8.4 Assessment of fragmentation 27
8.5 Minimum values from the particle count 28
8.6 Selection of the longest particle 28
8.7 Maximum length of longest particle 28

9 Other physical characteristics 29
9.1 Optical distortion 29
9.1.1 Thermally toughened soda lime silicate safety glass produced by vertical toughening 29
9.1.2 Thermally toughened soda lime silicate safety glass produced by horizontal toughening 29
9.2 Anisotropy (iridescence) 29
9.3 Thermal durability 29
9.4 Mechanical strength 29
9.5 Classification of performance under accidental human impact 30

10 Marking 30

Annex A (informative) Curved thermally toughened soda lime silicate safety glass 31

Annex B(informative) Alternative method for the measurement of roller wave distortion 32

B.1 Apparatus 32
B.2 Method 32
B.3 Limitations 33
B.4 Alternative use of apparatus 33

Annex C(informative) Examples of particle count 34

Annex D(informative) Risk of spontaneous breakage of toughened glass due to nickel sulfide inclusion 37

Bibliography 38