

DIN EN 12150-1:2020-07 (E)

Glass in building - Thermally toughened soda lime silicate safety glass - Part 1: Definition and description

| Contents | | Page |
|-------------------------|---|-------------|
| European foreword | | 4 |
| Introduction | | 5 |
| 1 | Scope | 6 |
| 2 | Normative references | 6 |
| 3 | Terms and definitions | 7 |
| 4 | Glass products | 8 |
| 5 | Fracture characteristics | 9 |
| 6 | Dimensions and tolerances | 9 |
| 6.1 | Nominal thickness and thickness tolerances | 9 |
| 6.2 | Width and length (sizes) | 10 |
| 6.2.1 | General | 10 |
| 6.2.2 | Maximum and minimum sizes | 11 |
| 6.2.3 | Tolerances and squareness | 11 |
| 6.2.4 | Edge deformation produced by the vertical process | 12 |
| 6.3 | Flatness | 12 |
| 6.3.1 | General | 12 |
| 6.3.2 | Measurement of overall bow | 14 |
| 6.3.3 | Measurement of "wave distortion and roller wave distortion" | 15 |
| 6.3.4 | Measurement of edge lift (for horizontally toughened glass only) | 16 |
| 6.3.5 | Measurement of perimeter deformation of glass produced by air cushion toughening process | 17 |
| 6.3.6 | Measurement of local distortion (for vertically toughened glass only) | 18 |
| 6.3.7 | Limitation on overall bow, roller waves and edge lift for horizontally toughened glass | 18 |
| 6.3.8 | Limitation on overall bow, wave and perimeter deformation for toughened glass manufactured by air cushion process | 19 |
| 6.3.9 | Limitation on overall bow and local distortion for vertically toughened glass | 20 |
| 6.3.10 | Other distortions | 21 |
| 7 | Edge and/or surface work, holes, notches and cut-outs | 21 |
| 7.1 | Warning | 21 |
| 7.2 | Edge working of glass for toughening | 21 |
| 7.3 | Profiled edges | 22 |
| 7.4 | Round holes | 22 |
| 7.4.1 | General | 22 |
| 7.4.2 | Diameter of holes | 22 |
| 7.4.3 | Limitations on position of holes | 22 |
| 7.4.4 | Tolerances on hole diameters | 24 |
| 7.4.5 | Tolerances on position of holes | 24 |
| 7.5 | Holes/others | 25 |
| 7.6 | Notches and cut-outs | 25 |
| 7.7 | Shaped panes | 26 |
| 8 | Fragmentation test | 26 |
| 8.1 | General | 26 |

| | | |
|--|--|----|
| 8.2 | Dimensions and number of test specimens | 26 |
| 8.3 | Test procedure | 26 |
| 8.4 | Assessment of fragmentation | 27 |
| 8.5 | Minimum values from the particle count | 28 |
| 8.6 | Selection of the longest particle | 28 |
| 8.7 | Maximum length of longest particle | 28 |
| 9 | Other physical characteristics | 29 |
| 9.1 | Optical distortion | 29 |
| 9.1.1 | Thermally toughened soda lime silicate safety glass produced by vertical toughening | 29 |
| 9.1.2 | Thermally toughened soda lime silicate safety glass produced by horizontal toughening | 29 |
| 9.2 | Anisotropy (iridescence) | 29 |
| 9.3 | Thermal durability | 29 |
| 9.4 | Mechanical strength | 29 |
| 9.5 | Classification of performance under accidental human impact | 30 |
| 10 | Marking | 30 |
| Annex A (informative) Curved thermally toughened soda lime silicate safety glass | | 31 |
| Annex B(informative) Alternative method for the measurement of roller wave distortion | | 32 |
| B.1 | Apparatus | 32 |
| B.2 | Method | 32 |
| B.3 | Limitations | 33 |
| B.4 | Alternative use of apparatus | 33 |
| Annex C(informative) Examples of particle count | | 34 |
| Annex D(informative) Risk of spontaneous breakage of toughened glass due to nickel sulfide inclusion | | 37 |
| Bibliography | | 38 |