

DIN EN 12150-1:2020-07 (E)

Glass in building - Thermally toughened soda lime silicate safety glass - Part 1: Definition and description

Contents		Page
European foreword		4
Introduction		5
1	Scope	6
2	Normative references	6
3	Terms and definitions	7
4	Glass products	8
5	Fracture characteristics	9
6	Dimensions and tolerances	9
6.1	Nominal thickness and thickness tolerances	9
6.2	Width and length (sizes)	10
6.2.1	General	10
6.2.2	Maximum and minimum sizes	11
6.2.3	Tolerances and squareness	11
6.2.4	Edge deformation produced by the vertical process	12
6.3	Flatness	12
6.3.1	General	12
6.3.2	Measurement of overall bow	14
6.3.3	Measurement of "wave distortion and roller wave distortion"	15
6.3.4	Measurement of edge lift (for horizontally toughened glass only)	16
6.3.5	Measurement of perimeter deformation of glass produced by air cushion toughening process	17
6.3.6	Measurement of local distortion (for vertically toughened glass only)	18
6.3.7	Limitation on overall bow, roller waves and edge lift for horizontally toughened glass	18
6.3.8	Limitation on overall bow, wave and perimeter deformation for toughened glass manufactured by air cushion process	19
6.3.9	Limitation on overall bow and local distortion for vertically toughened glass	20
6.3.10	Other distortions	21
7	Edge and/or surface work, holes, notches and cut-outs	21
7.1	Warning	21
7.2	Edge working of glass for toughening	21
7.3	Profiled edges	22
7.4	Round holes	22
7.4.1	General	22
7.4.2	Diameter of holes	22
7.4.3	Limitations on position of holes	22
7.4.4	Tolerances on hole diameters	24
7.4.5	Tolerances on position of holes	24
7.5	Holes/others	25
7.6	Notches and cut-outs	25
7.7	Shaped panes	26
8	Fragmentation test	26
8.1	General	26

8.2	Dimensions and number of test specimens	26
8.3	Test procedure	26
8.4	Assessment of fragmentation	27
8.5	Minimum values from the particle count	28
8.6	Selection of the longest particle	28
8.7	Maximum length of longest particle	28
9	Other physical characteristics	29
9.1	Optical distortion	29
9.1.1	Thermally toughened soda lime silicate safety glass produced by vertical toughening	29
9.1.2	Thermally toughened soda lime silicate safety glass produced by horizontal toughening	29
9.2	Anisotropy (iridescence)	29
9.3	Thermal durability	29
9.4	Mechanical strength	29
9.5	Classification of performance under accidental human impact	30
10	Marking	30
Annex A (informative) Curved thermally toughened soda lime silicate safety glass		31
Annex B(informative) Alternative method for the measurement of roller wave distortion		32
B.1	Apparatus	32
B.2	Method	32
B.3	Limitations	33
B.4	Alternative use of apparatus	33
Annex C(informative) Examples of particle count		34
Annex D(informative) Risk of spontaneous breakage of toughened glass due to nickel sulfide inclusion		37
Bibliography		38