

ISO/TS 5660-5:2020-03 (E)

Reaction-to-fire tests - Heat release, smoke production and mass loss rate - Part 5: Heat release rate (cone calorimeter method) and smoke production rate (dynamic measurement) under reduced oxygen atmospheres

Contents		Page
Foreword		iv
1	Scope	1
2	Normative references	1
3	Terms and definitions	1
4	Symbols	2
5	Principle	3
6	Apparatus	4
6.1	General	5
6.2	Heater and enclosure and chimney arrangement with cone calorimeter as per ISO 5660-1	5
6.2.1	Enclosure	5
6.3	Water-cooling for weighing device	6
6.4	Chimney	6
6.5	Air- and gas-supply system	7
6.6	Enclosure oxygen analyser	7
6.7	Data collection and analysis system	7
7	Suitability of product for testing	7
8	Specimen construction and preparation	7
9	Test environment	7
10	Calibration	8
10.1	Operating calibrations	8
10.1.1	Enclosure oxygen analyser	8
10.1.2	Enclosure flow rate measurement	8
10.1.3	Heater calibration	8
11	Test procedure	8
11.1	General precautions	8
11.2	Initial preparation	8
11.3	Procedure	8
11.4	Criteria to consider a test as successful	10
12	Calculations	11
12.1	General	11
12.2	Calibration constant for oxygen consumption analysis	11
12.3	Correct time delay	11
12.4	Heat release rate	11
13	Test report	13

Annex A (informative) Commentary and guidance notes for operators	17
Annex B (informative) Additional information for using the linked configuration	18
Annex C (informative) Additional information for using the enclosure as standalone device with ISO 13927 controls	19
Annex D (informative) Gas flow rates	20
Bibliography	23