

DIN EN 1993-1-8/NA:2020-11 (E)

National Annex - Nationally determined parameters - Eurocode 3: Design of steel structures - Part 1-8: Design of joints

| Contents | Page |
|--|-------------|
| Foreword | 4 |
| NA.1 Scope | 5 |
| NA.2.1 General | 5 |
| NA.2.2 National provisions | 6 |
| NCI re 1.2 Normative references | 6 |
| NDP re 1.2.6 (Reference standard group 6: Rivets) Note | 6 |
| NDP re 2.2(2) Note | 6 |
| NCI re 3.1.1 Galvanized bolts | 6 |
| NDP re 3.1.1(3) Note | 7 |
| NDP re 3.4.2(1) Note | 7 |
| NCI re 3.5 Bolted connections with components with internal threads and components with external threads | 7 |
| NCI re 3.13.1 Connections made with pins -- General | 8 |
| NCI re 4.5.2 Limit value for effective throat thicknesses | 8 |
| NCI re 4.5.3.2(6) | 8 |
| NDP re 5.2.1(2) Note | 8 |
| NCI re 6.2.7.1(13) and 6.2.7.1(14) Contact splices and compression force transfer | 8 |
| NDP re 6.2.7.2(9) Note | 9 |
| NCI Contact splices and compression force transfer | 9 |
| NCI Butt jointing of parts of cross section differing in thickness | 10 |
| NCI Welding of added flange plates at their ends | 11 |
| NCI Joints between flange plates | 11 |
| Annex NA.B(normative) Castings, forgings and components made of steels for quenching and tempering | 14 |
| NA.B.1 Materials | 14 |
| NA.B.2 Requirements | 14 |
| NA.B.3 Characteristic values | 15 |

| | |
|---|-----------|
| NA.B.4 Welds | 16 |
| NA.B.5 Bolted connections | 17 |
| Bibliography | 18 |
| Figures Figure NA.1 -- Possible designs of contact splices (a) partial contact, b) and c) full contact) | 9 |
| Figure NA.2 -- Permissible tolerances, $1/500$, e 2 mm | 9 |
| Figure NA.3 -- Examples of bevelling of edges when butt jointing parts of cross section differing in thickness | 11 |
| Figure NA.4 -- Pre-connecting of flange plates | 11 |
| Figure NA.5 -- Preparation of a butt joint between superposed flange plates (examples) | 12 |
| Tables Table NA.1 -- Characteristic strength values of threaded stud materials | 7 |
| Table NA.B.1 -- Requirements regarding the internal and external condition of components made from cast steel and spheroidal graphite cast iron, subjected to predominately static loading | 15 |
| Table NA.B.2 -- Characteristic values for cast steel and iron | 16 |
| Table NA.B.3 -- Correlation factor w for fillet welds | 17 |