DIN 4108-4:2020-11 (E)

Thermal insulation and energy economy in buildings - Part 4: Hygrothermal design values

Contents

Page

Foreword 4

Introduction 5

1 Scope 6

2 Normative references 6

3 Terms and definitions 11

4 Hygrothermal characteristic values 11
4.1 Building materials, building types and building components and elements 11
4.2 Moisture content in equilibrium 27
4.3 Conversion factors for the moisture content 28
4.4 Thermal resistance of air layers 29
4.5 Surface resistance 29
4.6 Specific heat capacity 29
4.7 Floors and ceilings 29

5 Glazing, windows, doors and curtain walling 31
5.1 Windows, window doors, external doors and roof windows 31
5.1.1 Design values for windows, window doors,external doors and roof windows as in DIN EN 14351-1 31
5.1.2 Air permeability as a function of design features of windows, window doors and external doors 32
5.2 Insulating glass units as in DIN EN 1279-5 33
5.2.1 Design values for the thermal transmittance 33
5.2.2 Design values for the total solar energy transmittance (solar factor) and light transmittance 33
5.3 Design values for curtain walling 35
5.3.1 Design values for thermal transmittance 35
5.3.2 Design value for total solar energy transmittance (solar factor) and light transmittance 36

6 Rooflights 36
6.1 Individual rooflights and continuous rooflights of plastic materials 36
6.2 Glass constructions in roof areas (e.g. glass roofs) 38

7 Design values for industrial, commercial and garage doors and gates 39

8 Calculation of insulation thicknesses for pipelines 39

Annex A (normative) **Determination of design values for masonry made from masonry units as in DIN EN 771** 43
A.1 General 43
A.2 Extrapolation of the dry values of thermal conductivity $\lambda_{10,dry,unit}$ of units at the upper limit of the declared density and determination of $\lambda_{10,dry,unit,100\%}$ 43
A.3 Influence of moisture content and determination of $\lambda_{design,unit,100\%}$ 45
A.4 Consideration of the influence of joints and determination of $\lambda_{design,mas,100\%}$ 45
A.4.1 Numerical calculations 45
A.4.2 Simplified method for composite components as in DIN EN ISO 6946 45
A.4.3 Tabular method 45

A.5 Classification of thermal conductivity $\lambda_{design,mas,100\%}$ and determination of the design value λ_B 46

Bibliography 47

Tables

Table 1 — Design values for thermal conductivity and guideline values for water vapour resistance factors 12
Table 2 — Line 5 of Table 1 for thermal insulating materials in accordance with harmonized European Standards 23
Table 3 — Moisture content in equilibrium of building materials 27
Table 4 — Conversion factors for wall building materials 28
Table 5 — Conversion factors for thermal insulation 29
Table 6 — Thermal resistances of floors and ceilings 29
Table 7 — Design value for the thermal transmittance of external doors $U_{D,BW}$ as a function of the design features 32
Table 8 — Air permeability as a function of design features of windows, window doors and external doors 32
Table 9 — Correction factors ΔU_g for calculating the design values $U_{g,BW}$ 33
Table 10 — Total solar energy transmittance and light transmittance as a function of the design features, the U_g value and the thermal transmittance 34
Table 11 — Correction factors c as a function of the emissivity ε_n 35
Table 12 — Guideline values for light transmittance $\tau_{D65,}$ U_t- and g-values 37
Table 13 — Design value $U_{D,BW}$ as a function of design features 39
Table 14 — Determination of insulation thicknesses while maintaining the minimum requirement of the German Energy Savings Ordinance (EnEV) − 100 % requirement 40
Table 15 — Determination of insulation thicknesses while maintaining the minimum requirement of the German Energy Savings Ordinance (EnEV) − 50 % requirement 42
Table A.1 — Gradients of the thermal conductivity- density curve 44
Table A.2 — Determination of $\lambda_{design,mas,100\%}$ for masonry with various joint materials 46