

# DIN 4108-4:2020-11 (E)

## Thermal insulation and energy economy in buildings - Part 4: Hygrothermal design values

---

| Contents  | Page |
|---|------|
| Foreword .....  | 4    |
| Introduction .....  | 5    |
| 1 Scope .....   | 6    |
| 2 Normative references .....  | 6    |
| 3 Terms and definitions.....  | 11   |
| 4 Hygrothermal characteristic values.....   | 11   |
| 4.1 Building materials, building types and building components and elements.....  | 11   |
| 4.2 Moisture content in equilibrium .....   | 27   |
| 4.3 Conversion factors for the moisture content .....   | 28   |
| 4.4 Thermal resistance of air layers.....   | 29   |
| 4.5 Surface resistance .....  | 29   |
| 4.6 Specific heat capacity .....  | 29   |
| 4.7 Floors and ceilings .....   | 29   |
| 5 Glazing, windows, doors and curtain walling.....  | 31   |
| 5.1 Windows, window doors, external doors and roof windows.....   | 31   |
| 5.1.1 Design values for windows, window doors,external doors and roof windows as in<br>DIN EN 14351-1.....  | 31   |
| 5.1.2 Air permeability as a function of design features of windows, window doors and external<br>doors.....   | 32   |
| 5.2 Insulating glass units as in DIN EN 1279-5.....   | 33   |
| 5.2.1 Design values for the thermal transmittance.....  | 33   |
| 5.2.2 Design values for the total solar energy transmittance (solar factor) and light<br>transmittance .....  | 33   |
| 5.3 Design values for curtain walling.....  | 35   |
| 5.3.1 Design values for thermal transmittance.....  | 35   |
| 5.3.2 Design value for total solar energy transmittance (solar factor) and light transmittance .....  | 36   |
| 6 Rooflights.....   | 36   |
| 6.1 Individual rooflights and continuous rooflights of plastic materials.....   | 36   |
| 6.2 Glass constructions in roof areas (e.g. glass roofs) .....  | 38   |
| 7 Design values for industrial, commercial and garage doors and gates .....   | 39   |
| 8 Calculation of insulation thicknesses for pipelines .....   | 39   |
| Annex A (normative) Determination of design values for masonry made from masonry units as in<br>DIN EN 771.....   | 43   |
| A.1 General .....   | 43   |
| A.2 Extrapolation of the dry values of thermal conductivity $\lambda_{10,dry,unit}$ of units at the upper limit<br>of the declared density and determination of $\lambda_{10,dry,unit,100\%}$ ..... | 43   |
| A.3 Influence of moisture content and determination of $\lambda_{design,unit,100\%}$ .....  | 45   |
| A.4 Consideration of the influence of joints and determination of $\lambda_{design,mas,100\%}$ .....  | 45   |
| A.4.1 Numerical calculations.....   | 45   |
| A.4.2 Simplified method for composite components as in DIN EN ISO 6946 .....  | 45   |
| A.4.3 Tabular method .....  | 45   |

|                  |   |           |
|------------------|---|-----------|
| <b>A.5</b>       | <b>Classification of thermal conductivity <math>\lambda_{\text{design,mas,100\%}}</math> and determination of the design value <math>\lambda_{\text{p}}</math> .....</b>        | <b>46</b> |
|                  | <b>Bibliography .....</b>   | <b>47</b> |
| <b>Tables</b>    |   |           |
| <b>Table 1</b>   | <b>— Design values for thermal conductivity and guideline values for water vapour resistance factors .....</b>  | <b>12</b> |
| <b>Table 2</b>   | <b>— Line 5 of Table 1 for thermal insulating materials in accordance with harmonized European Standards .....</b>  | <b>23</b> |
| <b>Table 3</b>   | <b>— Moisture content in equilibrium of building materials .....</b>  | <b>27</b> |
| <b>Table 4</b>   | <b>— Conversion factors for wall building materials .....</b>   | <b>28</b> |
| <b>Table 5</b>   | <b>— Conversion factors for thermal insulation .....</b>  | <b>29</b> |
| <b>Table 6</b>   | <b>— Thermal resistances of floors and ceilings .....</b>   | <b>29</b> |
| <b>Table 7</b>   | <b>— Design value for the thermal transmittance of external doors <math>U_{\text{D,BW}}</math> as a function of the design features .....</b>                                   | <b>32</b> |
| <b>Table 8</b>   | <b>— Air permeability as a function of design features of windows, window doors and external doors .....</b>  | <b>32</b> |
| <b>Table 9</b>   | <b>— Correction factors <math>\Delta U_{\text{g}}</math> for calculating the design values <math>U_{\text{g,BW}}</math> .....</b>   | <b>33</b> |
| <b>Table 10</b>  | <b>— Total solar energy transmittance and light transmittance as a function of the design features, the <math>U_{\text{g}}</math> value and the thermal transmittance .....</b> | <b>34</b> |
| <b>Table 11</b>  | <b>— Correction factors <math>c</math> as a function of the emissivity <math>\varepsilon_{\text{n}}</math> .....</b>  | <b>35</b> |
| <b>Table 12</b>  | <b>— Guideline values for light transmittance <math>\tau_{\text{D65}}</math>, <math>U_{\text{t}}</math>- and <math>g</math>-values .....</b>                                    | <b>37</b> |
| <b>Table 13</b>  | <b>— Design value <math>U_{\text{D,BW}}</math> as a function of design features .....</b>   | <b>39</b> |
| <b>Table 14</b>  | <b>— Determination of insulation thicknesses while maintaining the minimum requirement of the German Energy Savings Ordinance (EnEV) – 100 % requirement .....</b>              | <b>40</b> |
| <b>Table 15</b>  | <b>— Determination of insulation thicknesses while maintaining the minimum requirement of the German Energy Savings Ordinance (EnEV) – 50 % requirement .....</b>               | <b>42</b> |
| <b>Table A.1</b> | <b>— Gradients of the thermal conductivity- density curve .....</b>   | <b>44</b> |
| <b>Table A.2</b> | <b>— Determination of <math>\lambda_{\text{design,mas,100\%}}</math> for masonry with various joint materials .....</b>   | <b>46</b> |