

# DIN 4108-4:2020-11 (E)

## Thermal insulation and energy economy in buildings - Part 4: Hygrothermal design values

### Contents

	Page
<b>Foreword .....</b>	<b>4</b>
<b>Introduction .....</b>	<b>5</b>
<b>1 Scope .....</b>	<b>6</b>
<b>2 Normative references .....</b>	<b>6</b>
<b>3 Terms and definitions.....</b>	<b>11</b>
<b>4 Hygrothermal characteristic values.....</b>	<b>11</b>
<b>4.1 Building materials, building types and building components and elements.....</b>	<b>11</b>
<b>4.2 Moisture content in equilibrium .....</b>	<b>27</b>
<b>4.3 Conversion factors for the moisture content .....</b>	<b>28</b>
<b>4.4 Thermal resistance of air layers.....</b>	<b>29</b>
<b>4.5 Surface resistance .....</b>	<b>29</b>
<b>4.6 Specific heat capacity.....</b>	<b>29</b>
<b>4.7 Floors and ceilings .....</b>	<b>29</b>
<b>5 Glazing, windows, doors and curtain walling.....</b>	<b>31</b>
<b>5.1 Windows, window doors, external doors and roof windows.....</b>	<b>31</b>
<b>5.1.1 Design values for windows, window doors,external doors and roof windows as in DIN EN 14351-1.....</b>	<b>31</b>
<b>5.1.2 Air permeability as a function of design features of windows, window doors and external doors.....</b>	<b>32</b>
<b>5.2 Insulating glass units as in DIN EN 1279-5.....</b>	<b>33</b>
<b>5.2.1 Design values for the thermal transmittance.....</b>	<b>33</b>
<b>5.2.2 Design values for the total solar energy transmittance (solar factor) and light transmittance .....</b>	<b>33</b>
<b>5.3 Design values for curtain walling.....</b>	<b>35</b>
<b>5.3.1 Design values for thermal transmittance .....</b>	<b>35</b>
<b>5.3.2 Design value for total solar energy transmittance (solar factor) and light transmittance .....</b>	<b>36</b>
<b>6 Rooflights.....</b>	<b>36</b>
<b>6.1 Individual rooflights and continuous rooflights of plastic materials.....</b>	<b>36</b>
<b>6.2 Glass constructions in roof areas (e.g. glass roofs) .....</b>	<b>38</b>
<b>7 Design values for industrial, commercial and garage doors and gates .....</b>	<b>39</b>
<b>8 Calculation of insulation thicknesses for pipelines .....</b>	<b>39</b>
<b>Annex A (normative) Determination of design values for masonry made from masonry units as in DIN EN 771.....</b>	<b>43</b>
<b>A.1 General .....</b>	<b>43</b>
<b>A.2 Extrapolation of the dry values of thermal conductivity <math>\lambda_{10,dry,unit}</math> of units at the upper limit of the declared density and determination of <math>\lambda_{10,dry,unit,100\%}</math> .....</b>	<b>43</b>
<b>A.3 Influence of moisture content and determination of <math>\lambda_{design,unit,100\%}</math> .....</b>	<b>45</b>
<b>A.4 Consideration of the influence of joints and determination of <math>\lambda_{design,mas,100\%}</math> .....</b>	<b>45</b>
<b>A.4.1 Numerical calculations .....</b>	<b>45</b>
<b>A.4.2 Simplified method for composite components as in DIN EN ISO 6946 .....</b>	<b>45</b>
<b>A.4.3 Tabular method .....</b>	<b>45</b>

<b>A.5      Classification of thermal conductivity <math>\lambda_{\text{design,mas,100\%}}</math> and determination of the design value <math>\lambda_B</math> .....</b>	<b>46</b>
<b>Bibliography .....</b>	<b>47</b>
<b>Tables</b>	
<b>Table 1 — Design values for thermal conductivity and guideline values for water vapour resistance factors .....</b>	<b>12</b>
<b>Table 2 — Line 5 of Table 1 for thermal insulating materials in accordance with harmonized European Standards .....</b>	<b>23</b>
<b>Table 3 — Moisture content in equilibrium of building materials .....</b>	<b>27</b>
<b>Table 4 — Conversion factors for wall building materials .....</b>	<b>28</b>
<b>Table 5 — Conversion factors for thermal insulation .....</b>	<b>29</b>
<b>Table 6 — Thermal resistances of floors and ceilings .....</b>	<b>29</b>
<b>Table 7 — Design value for the thermal transmittance of external doors <math>U_{D,BW}</math> as a function of the design features .....</b>	<b>32</b>
<b>Table 8 — Air permeability as a function of design features of windows, window doors and external doors .....</b>	<b>32</b>
<b>Table 9 — Correction factors <math>\Delta U_g</math> for calculating the design values <math>U_{g,BW}</math> .....</b>	<b>33</b>
<b>Table 10 — Total solar energy transmittance and light transmittance as a function of the design features, the <math>U_g</math> value and the thermal transmittance .....</b>	<b>34</b>
<b>Table 11 — Correction factors <math>c</math> as a function of the emissivity <math>\varepsilon_n</math> .....</b>	<b>35</b>
<b>Table 12 — Guideline values for light transmittance <math>\tau_{D65}</math>, <math>U_t</math>- and <math>g</math>-values .....</b>	<b>37</b>
<b>Table 13 — Design value <math>U_{D,BW}</math> as a function of design features .....</b>	<b>39</b>
<b>Table 14 — Determination of insulation thicknesses while maintaining the minimum requirement of the German Energy Savings Ordinance (EnEV) – 100 % requirement .....</b>	<b>40</b>
<b>Table 15 — Determination of insulation thicknesses while maintaining the minimum requirement of the German Energy Savings Ordinance (EnEV) – 50 % requirement .....</b>	<b>42</b>
<b>Table A.1 — Gradients of the thermal conductivity- density curve .....</b>	<b>44</b>
<b>Table A.2 — Determination of <math>\lambda_{\text{design,mas,100\%}}</math> for masonry with various joint materials .....</b>	<b>46</b>