DIN 4102-16:2021-01 (E)

Fire behaviour of building materials and building components - Part 16: "Brandschacht" tests

Contents

Page

Foreword ... 4

1 Scope ... 6

2 Normative references ... 6

3 Terms and definitions ... 7

4 Brief description of method ... 7

5 Specimen preparation ... 7
5.1 General ... 7
5.2 Colour variations ... 7
5.3 Finishes (paints, coatings, wallcoverings, etc.) ... 8
5.4 Adjacent materials ... 8
5.5 Bonding agents ... 9

6 Number and size of specimens and test pieces ... 9
6.1 General ... 9
6.2 Reducing the scope of testing of *Brandschacht* tests ... 11
6.3 Number of tests for materials of various apparent densities and thicknesses ... 11

7 Conditioning and ageing of specimens ... 12
7.1 Conditioning of specimens ... 12
7.2 Conditioning to determine ageing behaviour ... 12
7.3 Ageing of plastic drainage pipes and fittings ... 13

8 Requirements for specific materials ... 14
8.1 Internal wall and ceiling linings applied using adhesives ... 14
8.2 Wood chipboard ... 14
8.3 Other types of covering ... 15
8.3.1 High-pressure laminates (HPL) or continuous pressure laminates (CPL) (laminated sheet) used to cover wood chipboard ... 15
8.3.2 Other coverings on substrates not covered by this standard ... 15
8.4 Back-ventilated cladding ... 16
8.5 Thermal insulation composite systems ... 16
8.6 Mineral fibre insulating materials, with or without metal facing ... 16
8.7 Rigid polystyrene foam boards ... 16
8.8 Rigid polystyrene foam composite panels ... 17
8.9 Adhesives for use with rigid polystyrene foam board ... 17
8.10 Sandwich panels ... 17
8.11 Loose or granular insulating materials ... 17
8.12 In-situ foam ... 18
8.13 Intumescent coatings and coatings for wood and wood-based panel products ... 18
8.13.1 Specimen materials ... 18
8.13.2 Surface treatment ... 19
8.14 Solid timber with fire retardants applied by the vacuum/pressure process ... 19
8.15 Textiles ... 19
8.16 Fire retardants for textiles ... 19
8.16.1 General ... 19

8.16.2 Test fabrics 20
8.16.3 Fire behaviour after washing 20
8.16.4 Fire behaviour after dry cleaning 20
8.16.5 Fire behaviour after exposure to natural weathering 20
8.16.6 Number of specimens 20
8.17 Pipes, pipe insulation, lagging, jacketing 21
8.17.1 Pipes 21
8.17.2 Pipe insulation (hinged or tubular, with or without jacketing applied at works) 22
8.17.3 Cladding for insulated pipes 22
8.18 Flexible ventilation ducting 23
8.19 Jointing products (at edges) 23
8.19.1 General 23
8.19.2 Sealants 23
8.19.3 Compressible soft foam strips 23
8.20 Raised access floor panels 23
8.21 Roof underlays 24
8.22 Decorative elements 24
8.23 Cables and cable coatings 24
8.24 Plastic sheeting (hollow core, framework or multiwall sheeting, e.g. polycarbonate) 24

9 Testing 24
9.1 General 24
9.2 Exposure to flame 24
9.3 Distance of specimens to burner 25
9.4 Testing aged specimens 25
9.5 Testing weathered specimens 25
9.6 Termination of the test 25

10 Evaluation of test results 25
10.1 Determining residual length 25
10.2 Materials with a thickness of > 80 mm 26
10.3 Flaming droplets for DIN 4102-B1 materials 26

11 Test certificate 26

Figures

Figure 1 — Pipe system for ageing tests 14

Tables

Table 1 — Number of specimens 10

Table 2 — Number of textile specimens 21