

DIN 4102-16:2021-01 (E)

Fire behaviour of building materials and building components - Part 16: "Brandschacht" tests

Contents	Page
Foreword	4
1 Scope	6
2 Normative references	6
3 Terms and definitions.....	7
4 Brief description of method.....	7
5 Specimen preparation	7
5.1 General	7
5.2 Colour variations.....	7
5.3 Finishes (paints, coatings, wallcoverings, etc.).....	8
5.4 Adjacent materials.....	8
5.5 Bonding agents.....	9
6 Number and size of specimens and test pieces.....	9
6.1 General	9
6.2 Reducing the scope of testing of <i>Brandschacht</i> tests	11
6.3 Number of tests for materials of various apparent densities and thicknesses	11
7 Conditioning and ageing of specimens	12
7.1 Conditioning of specimens	12
7.2 Conditioning to determine ageing behaviour	12
7.3 Ageing of plastic drainage pipes and fittings.....	13
8 Requirements for specific materials.....	14
8.1 Internal wall and ceiling linings applied using adhesives	14
8.2 Wood chipboard	14
8.3 Other types of covering	15
8.3.1 High-pressure laminates (HPL) or continuous pressure laminates (CPL) (laminated sheet) used to cover wood chipboard.....	15
8.3.2 Other coverings on substrates not covered by this standard	15
8.4 Back-ventilated cladding.....	16
8.5 Thermal insulation composite systems	16
8.6 Mineral fibre insulating materials, with or without metal facing	16
8.7 Rigid polystyrene foam boards.....	16
8.8 Rigid polystyrene foam composite panels	17
8.9 Adhesives for use with rigid polystyrene foam board	17
8.10 Sandwich panels	17
8.11 Loose or granular insulating materials.....	17
8.12 In-situ foam	18
8.13 Intumescent coatings and coatings for wood and wood-based panel products	18
8.13.1 Specimen materials	18
8.13.2 Surface treatment	19
8.14 Solid timber with fire retardants applied by the vacuum/pressure process	19
8.15 Textiles	19
8.16 Fire retardants for textiles.....	19
8.16.1 General	19

8.16.2	Test fabrics	20
8.16.3	Fire behaviour after washing	20
8.16.4	Fire behaviour after dry cleaning	20
8.16.5	Fire behaviour after exposure to natural weathering.....	20
8.16.6	Number of specimens.....	20
8.17	Pipes, pipe insulation, lagging, jacketing.....	21
8.17.1	Pipes	21
8.17.2	Pipe insulation (hinged or tubular, with or without jacketing applied at works)	22
8.17.3	Cladding for insulated pipes	22
8.18	Flexible ventilation ducting	23
8.19	Jointing products (at edges).....	23
8.19.1	General.....	23
8.19.2	Sealants.....	23
8.19.3	Compressible soft foam strips.....	23
8.20	Raised access floor panels	23
8.21	Roof underlays	24
8.22	Decorative elements.....	24
8.23	Cables and cable coatings	24
8.24	Plastic sheeting (hollow core, framework or multiwall sheeting, e.g. polycarbonate)	24
9	Testing	24
9.1	General.....	24
9.2	Exposure to flame.....	24
9.3	Distance of specimens to burner	25
9.4	Testing aged specimens	25
9.5	Testing weathered specimens.....	25
9.6	Termination of the test.....	25
10	Evaluation of test results	25
10.1	Determining residual length.....	25
10.2	Materials with a thickness of > 80 mm	26
10.3	Flaming droplets for DIN 4102-B1 materials	26
11	Test certificate.....	26

Figures

Figure 1	— Pipe system for ageing tests	14
----------	--------------------------------------	----

Tables

Table 1	— Number of specimens.....	10
Table 2	— Number of textile specimens	21