

ISO 15900:2020 (E)

Determination of particle size distribution — Differential electrical mobility analysis for aerosol particles

Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols
5	General principle
5.1	Particle size classification with the DEMC
5.2	Relationship between electrical mobility and particle size
5.3	Measurement and data inversion
5.4	Transfer function of the DEMC
5.5	Charge distribution function
5.5.1	General
5.5.2	Charge distribution function for radioactive bipolar charge conditioners
5.5.3	Charge distribution functions for other bipolar and unipolar charge conditioners
5.6	Particle losses in the DMAS
5.7	Effects due to non-spherical particles
5.8	Measurement of particle sizes below 10 nm
5.9	Traceability of measurement results
6	System and apparatus
6.1	General configuration
6.2	Components
6.2.1	Pre-conditioner
6.2.2	Charge conditioner
6.2.3	DEMC
6.2.4	Aerosol particle detector
6.2.5	System controller, data acquisition and analysis
7	Measurement procedures
7.1	Setup and preparation of the instrument
7.1.1	General
7.1.2	Aerosol pre-conditioning: Adapting the aerosol to be measured to the requirements of the DMAS
7.1.2.1	Particle concentration
7.1.2.2	Temperature and pressure
7.1.2.3	Humidity
7.1.3	Aerosol pre-conditioning: Separation of large particles
7.1.4	Charge conditioning
7.1.5	DEMC: Flows
7.1.6	DEMC: Voltage
7.1.7	DEMC: Temperature and pressure
7.1.8	Particle detection: CPC
7.1.9	Particle detection: FCAE
7.1.10	Data acquisition
7.2	Pre-measurement checks
7.2.1	General

7.2.2	Overall DMAS check
7.2.3	Data acquisition check
7.3	Measurement
7.4	Maintenance
8	Periodic tests and calibrations
8.1	Overview
8.2	Zero tests
8.2.1	General
8.2.2	Particle detector zero test
8.2.3	Overall DMAS zero test with inlet filter
8.2.4	Overall DMAS zero test with DEMC voltage set to 0 V
8.3	Flow rate tests
8.4	Voltage calibration
8.5	Charge conditioner test
8.6	Calibration for size measurement
8.6.1	General
8.6.2	Purpose of calibration
8.6.3	Particle size standards
8.6.4	Dynamic DMAS particle size calibration procedure
8.6.4.1	Procedure
8.6.4.2	Report for dynamic DMAS particle size calibration
8.6.5	Static DMAS particle size calibration procedure
8.6.5.1	Procedure
8.6.5.2	Calculations of the number-weighted mean electrical mobility,
8.6.5.3	Uncertainty of the result of the calibration
8.6.5.4	Report for static DMAS particle size calibration
8.6.5.5	Use of calibration data
8.7	Size resolution test
8.8	Number concentration calibration
9	Using a DEMC at a fixed voltage to generate particles of a chosen size
9.1	General
9.2	Multiply-charged particles
9.3	Size calibration with certified spheres
9.4	Sheath flow
9.5	Slip correction (if applicable)
9.6	Voltage (if applicable)
9.7	Calculation of overall uncertainty
10	Reporting of results
Annex A	(informative) Charge conditioners and charge distributions
A.1	General
A.2	Ionization sources
A.2.1	General
A.2.2	Sources with radioisotopes
A.2.2.1	Krypton 85 (85Kr)
A.2.2.2	Americium 241 (241Am)
A.2.2.3	Polonium 210 (210Po)
A.2.2.4	Nickel 63 (63Ni)
A.2.2.5	Licensing and precautions for radioisotope sources
A.2.3	Soft X-ray sources
A.2.3.1	Licensing and precautions for soft X-ray sources
A.2.4	Corona discharge
A.3	Charge conditioning
A.3.1	General
A.3.2	Bipolar charge conditioners
A.3.3	Unipolar charge conditioners
A.4	Implementation of bipolar steady-state charging
A.4.1	General
A.4.2	Charge distribution function of particles
A.4.2.1	Ion-aerosol attachment coefficient – Fuchs' theory
A.4.2.2	Properties of the ion

A.4.2.3	Approximation of the bipolar charge distribution for aerosol particles
A.5	Implementation of unipolar charge conditioning
Annex B	(informative) Particle detectors
B.1	General
B.2	Condensation particle counter
B.2.1	General
B.2.2	Calibration
B.3	Faraday cup aerosol electrometer
B.3.1	General
B.3.2	Structure and detection mechanism of FCAE
B.3.3	Calibration
Annex C	(informative) Slip correction factor
C.1	General
C.2	Historical investigation of the slip correction factor
C.3	Recommended coefficients for the slip correction factor
Annex D	(informative) Data inversion
D.1	General
D.2	Step-by-step DMAS calculation example
D.2.1	General
D.2.2	Measurement system
D.2.3	Data acquisition
D.2.4	Data inversion assuming only singly charged particles
D.2.5	Multiple charge correction
D.2.6	Diffusion loss correction
D.2.7	Final result
Annex E	(informative) Cylindrical DEMC
E.1	Geometry of cylindrical DEMC
E.2	Transfer function
E.3	Uncertainty calculation for Z^*
Annex F	(informative) Example certificate for a DMAS particle size calibration
Annex G	(informative) Good practice for measurements at particle sizes below 10 nm
G.1	General
G.2	Using optimized measurement equipment
G.3	Detector calibration considerations
Annex H	(informative) Examples for overall system tests
H.1	Example for an overall system test with PSL particles
H.1.1	General
H.1.2	Test setup
H.1.3	Test procedure
H.1.4	Test report
H.2	Example for an overall system test with polydisperse aerosol
H.2.1	General
H.2.2	Test setup
H.2.3	Test procedure
H.2.4	Test report
Annex I	(informative) Comparison of different approaches to calculate diffusion loss in laminar tube flow
I.1	General
I.2	Empirical calculation of the particle penetration for laminar tube flow
I.2.1	Gormley and Kennedy (1949)
I.2.2	Hinds (1999)
I.2.3	Willeke and Baron (1993)
I.3	Comparison of the different sets of empirical formulae
I.4	Equivalent tube length
I.5	Overall particle losses in the DMAS
I.6	Example calculation
Annex J	(informative) Corrections for effects due to non-spherical particles