ISO 3008-4:2021-02 (E)

Fire resistance tests - Door and shutter assemblies - Part 4: Linear joint fire seal materials used to seal the gap between a fire door frame and the supporting construction

Contents

Page

Foreword iv

Introduction v

1 Scope 1

2 Normative references 1

3 Terms and definitions 2

4 Test equipment 2
4.1 Reduced-scale furnace 2
4.2 Furnace internal dimensions 2
4.3 Vertical furnace dimensions 2

5 Test specimen 2
5.1 General 2
5.2 Specimen size 3
5.3 Specimen design 3
5.4 Timber door frame sections 3
5.5 Splices 3
5.6 Supporting construction 3
5.7 Packers and fixings 4
5.7.1 Packers 4
5.7.2 Fixings 4

6 Test conditions 5
6.1 Heating conditions 5
6.2 Pressure 5

7 Specimen preparation 5
7.1 Supporting construction 5
7.2 Joint seal 5
7.3 Splice location 6
7.4 Conditioning 6
7.5 Information and test specimen verification 6

8 Instrumentation 6
8.1 Temperature 6
8.1.1 Furnace thermocouples (Plate thermometers) 6
8.1.2 Unexposed-surface thermocouples 7
8.1.3 Roving thermocouples 7
8.2 Pressure 7
8.3 Deformation 7
8.4 Integrity 8

9 Test procedure 8
9.1 General test procedure 8
9.2 Termination of test 8

10 General performance criteria 8
10.1 Insulation 8
10.2 Integrity 9

11 Expression of test results 9

12 Test report 9

13 Field of application 9

Annex A (normative) Field of application 10

Bibliography 11