

DIN EN 1998-1/NA:2021-07 (E)

National Annex - Nationally determined parameters - Eurocode 8: Design of structures for earthquake resistance - Part 1: General rules, seismic actions and rules for buildings, with CD-ROM

Contents

Page

Foreword	7
NA.1 Scope	9
NA.2 National provisions	9
NA.2.1 General	9
NA.2.2 National provisions	12
NCI re 1.1.2(2) Scope of EN 1998-1.....	12
NDP re 1.1.2(7) Scope of EN 1998-1.....	12
NCI re 1.2 Normative references.....	13
NDP re 2.1(1)P Fundamental requirements	13
NCI re 2.1(4) Fundamental requirements	13
NDP re 3.1.1(4) General.....	13
NDP re 3.1.2(1) Identification of ground types	13
NDP re 3.2.1(1), (2) and (3) Seismic zones.....	15
NDP re 3.2.1(4) Seismic zones.....	16
NDP re 3.2.1(5)P Seismic zones.....	17
NDP re 3.2.2.1(4), 3.2.2.2(2)P Basic representation of the seismic action.....	17
NDP re 3.2.2.3(1)P Vertical elastic response spectrum.....	18
NCI re 3.2.2.4 Design ground displacement.....	19
NCI re 3.2.2.5(3)P Design spectrum for linear analysis.....	19
NDP re 3.2.2.5(4)P Design spectrum for linear analysis.....	19
NDP re 4.2.3.2(8) Criteria for regularity in plan.....	19
NDP re 4.2.4(2)P Combination coefficients for variable actions.....	19
NDP re 4.2.5(5)P Importance classes and importance factors.....	20
NCI re 4.2.5(5)P Importance classes and importance factors	20
NDP re 4.3.3.1(4) Methods of analysis	20
NDP re 4.3.3.1(8) Methods of analysis	21
NCI re 4.3.3.2.2(3) Base shear force.....	21
NCI re 4.3.3.2.4 Torsional effects	21
NCI re 4.3.3.4.2.1(1) Non-linear static (pushover) analysis.....	21
NCI re 4.3.3.4.2.1(2) and (3) Non-linear static (pushover) analysis.....	21
NCI re 4.3.3.4.2.3 Capacity curve.....	22
NCI re 4.3.3.4.2.3(2) Capacity curve.....	22
NCI re 4.3.3.4.2.6 Target displacement	22
NCI re 4.3.3.4.2.7 Procedure for the estimation of the torsional effects	22
NCI re 4.3.5.1 Non-structural elements.....	22
NCI re 4.4.2.1(1) Ultimate limit state.....	22
NDP re 4.4.2.5(2) Resistance of horizontal diaphragms	22
NDP re 4.4.3.2(2) Limitation of interstorey drift.....	23
NDP re 5.2.1(5) Energy dissipation capacity and ductility classes	23
NDP re 5.2.2.2(10) Behaviour factors for horizontal seismic actions.....	23
NDP re 5.2.4(1) and (3) Safety verifications	23
NCI re 5.3.2 Materials	23
NCI re 5.4.3.4.2(5) Detailing for local ductility.....	23
NCI re 5.4.3.4.2(6) Detailing for local ductility.....	23
NDP re 5.4.3.5.2(1) Shear resistance	23

NCI re 5.7(1) Design and detailing of secondary seismic elements	23
NDP re 5.8.2(3) Tie-beams and foundation beams	23
NDP re 5.8.2(4) Tie-beams and foundation beams	24
NDP re 5.8.2(5) Tie-beams and foundation beams	24
NDP re 5.11.1.3.2(3) Energy dissipation	24
NDP re 5.11.1.4 Behaviour factors.....	24
NDP re 5.11.1.5(2) Analysis of a transient situation	24
NDP re 5.11.3.4(7) Precast large-panel walls	24
NDP re 6.1.2(1)P Design concepts	24
NDP re 6.1.3(1) Safety verifications.....	24
NDP re 6.2(3) Materials	24
NDP re 6.2(7) Materials	25
NCI re 6.3.2 Behaviour factors	25
NDP re 6.5.5(7) Design rules for connections in dissipative zones	25
NDP re 6.7.4(2) Beams and columns.....	25
NDP re 7.1.2(1)P Design concepts	25
NDP re 7.1.3(1) and (3) Safety verifications.....	25
NDP re 7.1.3(4) Safety verifications.....	25
NDP re 7.7.2(4) Calculation	25
NCI re 8.2(4) Materials and properties of dissipative zones.....	25
NDP re 8.3(1) Ductility classes and behaviour factors	26
NCI re 8.4(1)P Structural analysis	26
NCI re 8.5.2 Detailing rules for connections.....	27
NCI re 8.6(4)P Safety verifications	27
NDP re 9.2.1(1) Types of masonry units.....	27
NDP re 9.2.2(1) Minimum strength of masonry units	27
NDP re 9.2.3(1) Mortar.....	27
NDP re 9.2.4(1) Masonry bond	27
NDP re 9.3(2) Types of construction and behaviour factors.....	27
NDP re 9.3(3) Types of construction and behaviour factors.....	27
NDP re 9.3(4) Types of construction and behaviour factors.....	27
NCI re 9.4(6) Structural analysis.....	28
NDP re 9.5.1(5) Design criteria and construction rules	29
NCI re 9.6(2)P Safety verifications	29
NDP re 9.6(3) Safety verifications	29
NDP re 9.7.2(1) Rules for “simple masonry buildings”.....	30
NCI re 9.7.2(1) Rules for “simple masonry buildings”	30
NCI re 9.7.2(2)b) Rules for “simple masonry buildings”	30
NCI re 9.7.2(2)c) Rules for “simple masonry buildings”	30
NCI re 9.7.2(3)b), c) Rules for “simple masonry buildings”	30
NCI re 9.7.2(3)d) Rules for “simple masonry buildings”	30
NCI re 9.7.2(3)e) Rules for “simple masonry buildings”	30
NDP re 9.7.2(5) Rules for “simple masonry buildings”.....	30
NDP re 10.3(2)P Fundamental requirements.....	30
Annex NA.D (normative) Simplified design rules for simple structures of ordinary construction.....	31
NA.D.1 General.....	31
NA.D.2 Base shear force.....	31
NA.D.3 Distribution of the horizontal seismic forces.....	32
NA.D.4 Torsional effects	33
NA.D.5 Combination of the effects of the components of the seismic action	34
NA.D.6 Analysis of deformations	34
NA.D.7 Non-structural elements.....	35
NA.D.8 Stability analysis.....	37
NA.D.9 Foundations	38
NA.D.10 Special rules for masonry structures.....	39

Annex NA.E (informative) Seismic hazard maps and parameter values for describing the elastic horizontal response spectrum for $T_{NCR} = 975$ years and $T_{NCR} = 2\,475$ years.....	40
NA.E.1 Hazard maps for $T_{NCR} = 975$ years and $T_{NCR} = 2\,475$ years.....	40
NA.E.2 Parameter values for describing the elastic horizontal response spectrum for $T_{NCR} = 975$ years and $T_{NCR} = 2\,475$ years	40
Annex NA.F (informative) Explanation of the procedure for determining the seismic action in the case of shear wave velocities below 150 m/s	43
NA.F.1 Determination of response spectra for ground level	43
NA.F.2 Procedure for determining soil dynamic characteristics	43
Annex NA.G (informative) Schematic representation of the deep geology classes	45
Annex NA.H (normative) NDP and NCI re 9.7.2(1) Rules for “simple masonry buildings”	47
NA.H.1 NDP re 9.7.2(1) Rules for “simple masonry buildings”	47
NA.H.2 NCI re 9.7.2(1) Rules for “simple masonry buildings”	47
Annex NA.I (normative) Digital representation of the spectral accelerations for the hazard map according to Figure NA.1.....	64
Annex NA.J (informative) Digital representation of further spectral accelerations.....	65
Bibliography.....	66

Figures

Figure NA.1 — Representation of the spatial distribution of the spectral response acceleration for the deep geology ratio A-R in the plateau region $S_{aP,R}$ for a return period $T_{NCR} = 475$ years	16
Figure NA.2 — Shape and description of the elastic acceleration response spectrum	18
Figure NA.3 — Wall height h and distance h_0	29
Figure NA.D.1 — Eccentricities to be assumed for a seismic force acting in the y-direction.....	34
Figure NA.E.1 — Schematic representation of the spatial distribution of the spectral response acceleration for the deep geology ratio A-R in the plateau region $S_{aP,R}$ for a return period $T_{NCR} = 975$ years in the Federal Republic of Germany	41
Figure NA.E.2 — Schematic representation of the spatial distribution of the spectral response acceleration for the deep geology ratio A-R in the plateau region $S_{aP,R}$ for a return period $T_{NCR} = 2\,475$ years in the Federal Republic of Germany	42
Figure NA.G.1 — Schematic representation of the deep geology classes in the region of the contour line of $S_{aP,R} = 0,6 \text{ m/s}^2$	46
Figure NA.H.1 — Reduction factor k_v as a function of the relative bearing depth a/t	48

Tables

Table NA.1 — Control periods for describing the horizontal elastic response spectrum ($T_{NCR} = 475$ years)	17
Table NA.2 — Soil factor S for describing the horizontal elastic response spectrum	18
Table NA.3 — Parameters for describing the vertical elastic response spectrum	19
Table NA.4 — Coefficients for φ for calculating ψ_{Ei}	20
Table NA.5 — Importance classes and importance factors	20
Table NA.6 — Design concept, structural types and upper limit values of the behaviour factors for the three ductility classes	26
Table NA.7 — Types of construction and upper limit of the behaviour factor	28
Table NA.8 — Minimum requirements for stiffening walls (shear walls)	29
Table NA.9 — Partial safety factors for masonry structures in the seismic design situation	30
Table NA.D.1 — Minimum wall thicknesses for non-load-bearing partitions	36
Table NA.D.2 — Maximum number of full storeys for buildings requiring a stability analysis by comparison with wind	38
Table NA.E.1 — Parameter values for describing the elastic horizontal response spectrum for the return periods $T_{NCR} = 975$ years and $T_{NCR} = 2\,475$ years	40
Table NA.H.1 — Minimum requirements for the cross-sectional area of shear walls relative to the floor plan area as a percentage, with significant floor restraint for spectral accelerations $\leq 1,25$ m/s ² and 1,70 m/s ²	50
Table NA.H.2 — Minimum requirements for the cross-sectional area of shear walls relative to the floor plan area as a percentage, with significant floor restraint for spectral accelerations of 2,10 m/s ² and 2,60 m/s ²	51
Table NA.H.3 — Minimum requirements for the cross-sectional area of shear walls relative to the floor plan area as a percentage, with significant floor restraint for spectral accelerations of 3,00 m/s ² and 3,60 m/s ²	52
Table NA.H.4 — Minimum masonry compressive strengths with significant floor restraint	53
Table NA.H.5 — Absorbable spectral acceleration for shear wall cross-sectional areas of $p_{A,vorh} = 12$ % or (20 %) for the cross-sectional area of shear walls relative to the floor plan area as a percentage, with significant floor restraint	54
Table NA.H.6 — Minimum requirements for the cross-sectional area of shear walls relative to the floor plan area as a percentage, with little floor restraint for spectral accelerations of $\leq 1,25$ m/s ² and 1,70 m/s ²	55

Table NA.H.7 — Minimum requirements for the cross-sectional area of shear walls relative to the floor plan area as a percentage, with little floor restraint for spectral accelerations of 2,10 m/s ² and 2,60 m/s ²	56
Table NA.H.8 — Minimum requirements for the cross-sectional area of shear walls relative to the floor plan area as a percentage, with little floor restraint for spectral accelerations of 3,00 m/s ² and 3,60 m/s ²	57
Table NA.H.9 — Absorbable spectral acceleration for shear wall cross-sectional areas of $p_{A,vorh} = 12\%$ or (20 %) for the cross-sectional area of shear walls relative to the floor plan area as a percentage with little floor restraint	58
Table NA.H.10 — Minimum requirements for the cross-sectional area of shear walls made of aerated concrete relative to the floor plan area, with significant floor restraint for spectral accelerations of $\leq 1,25\text{ m/s}^2$; $1,70\text{ m/s}^2$ and $2,10\text{ m/s}^2$	59
Table NA.H.11 — Minimum requirements for the cross-sectional area of shear walls made of aerated concrete masonry relative to the floor plan area, with significant floor restraint for spectral accelerations of $2,60\text{ m/s}^2$; $3,00\text{ m/s}^2$ and $3,60\text{ m/s}^2$	60
Table NA.H.12 — Absorbable spectral acceleration for shear wall cross-sectional areas of $p_{A,vorh} = 12\%$ or (20 %) for the cross-sectional area of shear walls made of aerated concrete masonry relative to the floor plan area as a percentage, with significant floor restraint.....	61
Table NA.H.13 — Minimum requirements for the cross-sectional area of shear walls made of aerated concrete masonry relative to the floor plan area, with little floor restraint for spectral accelerations of $\leq 1,25\text{ m/s}^2$; $1,70\text{ m/s}^2$ and $2,10\text{ m/s}^2$	62
Table NA.H.14 — Minimum requirements for the cross-sectional area of shear walls made of aerated concrete masonry relative to the floor plan area, with little floor restraint for spectral accelerations of $2,60\text{ m/s}^2$ and $3,00\text{ m/s}^2$ as well as absorbable spectral acceleration for shear wall cross-sectional areas of $p_{A,vorh} = 12\%$ or (20 %)	63