

### Contents

	Foreword
	Introduction
1	Scope
2	Normative references
3	Terms and definitions
4	Symbols
5	Materials
6	Disturbing actions
6.1	Coriolis force
6.2	Aerodynamic loads
6.2.1	Steady state
6.2.2	Buffeting
6.2.2.1	Buffeting force when two conveyances pass each other
6.2.2.2	Buffeting in the wake of a leading conveyance
6.2.2.3	Buffeting force when conveyance passes inflow or outflow of air
6.2.3	Air density
6.3	Rope torque
6.3.1	Head rope torque
6.3.2	Tail rope torque
6.3.3	Torque applied by multiple ropes
6.4	Eccentric conveyance loading
6.5	Winder emergency braking
6.6	Thermal actions on headframe
6.7	Wind load on conveyances
7	Restoring forces
7.1	Rope guide tension
7.2	Rope guide stiffness
7.2.1	Stiffness of rope guides
7.2.2	Stiffness of head and tail ropes
8	Conveyance trajectory
8.1	Simulation of conveyance behaviour
8.2	Combination of actions
9	Design procedure
9.1	Function of rope guides
9.2	Risk assessment
9.3	General design procedure
9.4	Simple design procedure
9.4.1	Limits on parameters
9.4.2	Design requirements
9.5	Comprehensive design procedure
10	Minimum clearances
10.1	Design clearances
10.2	Dynamic displacement envelope

- 10.3 Reduced dynamic clearances
- 10.4 Use of rubbing ropes
- 11 Construction and installation tolerances
  - 11.1 Shaft vertical cylinder diameter
  - 11.2 Tolerance of associated structures
  - 11.3 Tolerance on rope guide tension
  - 11.4 Commissioning
    - 11.4.1 Commissioning procedure
    - 11.4.2 Components of the commissioning procedure
- 12 Other design considerations
  - 12.1 General
  - 12.2 Loading and unloading of conveyances
  - 12.3 Accessing intermediate levels
  - 12.4 Number of rope guides
  - 12.5 Rope guide positions
  - 12.6 Rope guide construction
  - 12.7 Rope guide tension and factor of safety
  - 12.8 Rope guide attachments
  - 12.9 Shafts with more than one winder
  - 12.10 Design life
  - 12.11 Rope guide tensioning
    - 12.11.1 Gravity tensioning devices
    - 12.11.2 Hydraulic tensioning devices
- 13 Assessment of existing installations
  - 13.1 General
  - 13.2 Application of measurements
  - 13.3 Upgrades or modifications
- 14 Inspection and maintenance
  - 14.1 Deterioration mechanisms
    - 14.1.1 General
    - 14.1.2 Wear
    - 14.1.3 Corrosion
    - 14.1.4 Mechanical damage
    - 14.1.5 Broken wires
  - 14.2 Inspections
    - 14.2.1 General
    - 14.2.2 Inspection intervals
    - 14.2.3 Visual inspection
    - 14.2.4 Non-destructive inspection
  - 14.3 Maintenance actions
    - 14.3.1 Maintenance intervals
    - 14.3.2 Lubrication
    - 14.3.3 Rope turning and rope lifting
    - 14.3.4 Equalisation of hoist rope tensions
  - 14.4 Rope guide discard criteria
  - 14.5 Rope guide attachments
- Annex A (informative) Load combinations and displacement multipliers
  - A.1 General
  - A.2 Operating combinations
  - A.3 Displacement multipliers
- Annex B (informative) Introduction to Annexes B to F, and basic parameters
  - B.1 Calibration
  - B.2 Scope and use of Annexes B to F
  - B.3 Basic shaft parameters
    - B.3.1 Nominal shaft geometry
    - B.3.2 Airflow characteristics
    - B.3.3 Shaft wall misalignments
  - B.4 Basic rope parameters

- B.4.1 Head and tail rope parameters
- B.4.2 Rope guide and rubbing rope parameters
- B.4.3 Rope guide and fixed guide installation accuracy
- B.5 Basic winder and conveyance parameters
- B.5.1 General parameters
- B.5.2 Cage and counterweight parameters
- B.5.3 Skip parameters

**Annex C (informative) Preliminary aerodynamic coefficients**

- C.1 General
- C.2 Steady state lateral coefficient CLX and CLZ
- C.3 Buffeting
- C.3.1 General
- C.3.2 Buffeting force when two conveyances pass each other
- C.3.3 Conveyance passing inflow or outflow of air

**Annex D (informative) Rope torque factors**

- D.1 Rope torque

**Annex E (informative) Rope guide stiffness and tension**

- E.1 Determination of rope guide stiffness
- E.2 System natural frequencies
- E.3 Preliminary determination of rope guide tension
- E.4 Influence of temperature

**Annex F (informative) Approximate calculation of conveyance displacement**

- F.1 Approximate maximum conveyance displacements
- F.1.1 Displacement due to Coriolis force DC
- F.1.2 Displacement due to steady state aerodynamic force DA
- F.1.3 Yaw rotation and displacement from head and tail rope torsion
- F.1.4 Displacements due to buffeting forces DB
- F.2 Other disturbing actions
- F.2.1 Initial rope guide motion or external displacement
- F.2.2 Conveyance tilt due to eccentric loading

Page count: 53