

Contents

| | |
|---------|---|
| | Foreword |
| | Introduction |
| 1 | Scope |
| 2 | Normative references |
| 3 | Terms and definitions |
| 4 | Symbols |
| 5 | Materials |
| 6 | Disturbing actions |
| 6.1 | Coriolis force |
| 6.2 | Aerodynamic loads |
| 6.2.1 | Steady state |
| 6.2.2 | Buffeting |
| 6.2.2.1 | Buffeting force when two conveyances pass each other |
| 6.2.2.2 | Buffeting in the wake of a leading conveyance |
| 6.2.2.3 | Buffeting force when conveyance passes inflow or outflow of air |
| 6.2.3 | Air density |
| 6.3 | Rope torque |
| 6.3.1 | Head rope torque |
| 6.3.2 | Tail rope torque |
| 6.3.3 | Torque applied by multiple ropes |
| 6.4 | Eccentric conveyance loading |
| 6.5 | Winder emergency braking |
| 6.6 | Thermal actions on headframe |
| 6.7 | Wind load on conveyances |
| 7 | Restoring forces |
| 7.1 | Rope guide tension |
| 7.2 | Rope guide stiffness |
| 7.2.1 | Stiffness of rope guides |
| 7.2.2 | Stiffness of head and tail ropes |
| 8 | Conveyance trajectory |
| 8.1 | Simulation of conveyance behaviour |
| 8.2 | Combination of actions |
| 9 | Design procedure |
| 9.1 | Function of rope guides |
| 9.2 | Risk assessment |
| 9.3 | General design procedure |
| 9.4 | Simple design procedure |
| 9.4.1 | Limits on parameters |
| 9.4.2 | Design requirements |
| 9.5 | Comprehensive design procedure |
| 10 | Minimum clearances |
| 10.1 | Design clearances |
| 10.2 | Dynamic displacement envelope |

- 10.3 Reduced dynamic clearances
- 10.4 Use of rubbing ropes
- 11 Construction and installation tolerances
 - 11.1 Shaft vertical cylinder diameter
 - 11.2 Tolerance of associated structures
 - 11.3 Tolerance on rope guide tension
 - 11.4 Commissioning
 - 11.4.1 Commissioning procedure
 - 11.4.2 Components of the commissioning procedure
- 12 Other design considerations
 - 12.1 General
 - 12.2 Loading and unloading of conveyances
 - 12.3 Accessing intermediate levels
 - 12.4 Number of rope guides
 - 12.5 Rope guide positions
 - 12.6 Rope guide construction
 - 12.7 Rope guide tension and factor of safety
 - 12.8 Rope guide attachments
 - 12.9 Shafts with more than one winder
 - 12.10 Design life
 - 12.11 Rope guide tensioning
 - 12.11.1 Gravity tensioning devices
 - 12.11.2 Hydraulic tensioning devices
- 13 Assessment of existing installations
 - 13.1 General
 - 13.2 Application of measurements
 - 13.3 Upgrades or modifications
- 14 Inspection and maintenance
 - 14.1 Deterioration mechanisms
 - 14.1.1 General
 - 14.1.2 Wear
 - 14.1.3 Corrosion
 - 14.1.4 Mechanical damage
 - 14.1.5 Broken wires
 - 14.2 Inspections
 - 14.2.1 General
 - 14.2.2 Inspection intervals
 - 14.2.3 Visual inspection
 - 14.2.4 Non-destructive inspection
 - 14.3 Maintenance actions
 - 14.3.1 Maintenance intervals
 - 14.3.2 Lubrication
 - 14.3.3 Rope turning and rope lifting
 - 14.3.4 Equalisation of hoist rope tensions
 - 14.4 Rope guide discard criteria
 - 14.5 Rope guide attachments
- Annex A (informative) Load combinations and displacement multipliers
 - A.1 General
 - A.2 Operating combinations
 - A.3 Displacement multipliers
- Annex B (informative) Introduction to Annexes B to F, and basic parameters
 - B.1 Calibration
 - B.2 Scope and use of Annexes B to F
 - B.3 Basic shaft parameters
 - B.3.1 Nominal shaft geometry
 - B.3.2 Airflow characteristics
 - B.3.3 Shaft wall misalignments
 - B.4 Basic rope parameters

- B.4.1 Head and tail rope parameters
- B.4.2 Rope guide and rubbing rope parameters
- B.4.3 Rope guide and fixed guide installation accuracy
- B.5 Basic winder and conveyance parameters
- B.5.1 General parameters
- B.5.2 Cage and counterweight parameters
- B.5.3 Skip parameters

Annex C (informative) Preliminary aerodynamic coefficients

- C.1 General
- C.2 Steady state lateral coefficient CLX and CLZ
- C.3 Buffeting
- C.3.1 General
- C.3.2 Buffeting force when two conveyances pass each other
- C.3.3 Conveyance passing inflow or outflow of air

Annex D (informative) Rope torque factors

- D.1 Rope torque

Annex E (informative) Rope guide stiffness and tension

- E.1 Determination of rope guide stiffness
- E.2 System natural frequencies
- E.3 Preliminary determination of rope guide tension
- E.4 Influence of temperature

Annex F (informative) Approximate calculation of conveyance displacement

- F.1 Approximate maximum conveyance displacements
- F.1.1 Displacement due to Coriolis force DC
- F.1.2 Displacement due to steady state aerodynamic force DA
- F.1.3 Yaw rotation and displacement from head and tail rope torsion
- F.1.4 Displacements due to buffeting forces DB
- F.2 Other disturbing actions
- F.2.1 Initial rope guide motion or external displacement
- F.2.2 Conveyance tilt due to eccentric loading

Page count: 53