

DIN EN 13286-47:2022-01 (E)

Unbound and hydraulically bound mixtures - Part 47: Test method for the determination of California bearing ratio, immediate bearing index and linear swelling

| Contents | | Page |
|---|--|-------------|
| European foreword | | 3 |
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 5 |
| 4 | Principle | 6 |
| 5 | Apparatus | 6 |
| 5.1 | Apparatus for specimen manufacture | 6 |
| 5.2 | Additional apparatus for soaking procedure and measurement of swelling | 6 |
| 5.3 | Additional apparatus for determination of the California bearing ratio and immediate bearing index | 6 |
| 6 | Test sample for the California bearing ratio and immediate bearing index tests | 7 |
| 7 | Specimen manufacture for the California bearing ratio and immediate bearing index tests | 7 |
| 8 | Curing for California bearing ratio test | 7 |
| 8.1 | General | 7 |
| 8.2 | Curing by prevention of evaporation | 8 |
| 8.3 | Curing that permits full soaking | 8 |
| 8.4 | Curing consisting of 'prevention of evaporation' followed by soaking | 9 |
| 9 | Procedure for California bearing ratio and immediate bearing index determination | 9 |
| 10 | Calculation and expression of results | 10 |
| 11 | Test report | 11 |
| Annex A (normative) Different Types of Force-Penetration Curves | | 12 |
| A.1 | Convex Upward Force-Penetration Curve | 12 |
| A.2 | Force-Penetration Curve with Inflexion Point S at $X < 7,5$ mm | 13 |
| A.3 | Concave Upward Force-Penetration Curve with Inflexion Point S at $X > 7,5$ mm | 14 |