

# DIN EN 74-2:2022-09 (E)

## Couplers, spigot pins and baseplates for use in falsework and scaffolds - Part 2: Special couplers - Requirements and test procedures

---

<b>Contents</b>		<b>Page</b>
European foreword .....		4
Introduction .....		5
<b>1</b>	<b>Scope.....</b>	<b>6</b>
<b>2</b>	<b>Normative references.....</b>	<b>6</b>
<b>3</b>	<b>Terms, definitions and symbols .....</b>	<b>7</b>
<b>3.1</b>	<b>Terms and definitions .....</b>	<b>7</b>
<b>3.2</b>	<b>Symbols and abbreviations .....</b>	<b>9</b>
<b>4</b>	<b>Types and classes of special couplers.....</b>	<b>10</b>
<b>4.1</b>	<b>Types of couplers .....</b>	<b>10</b>
<b>4.2</b>	<b>Classes of Couplers .....</b>	<b>11</b>
<b>4.2.1</b>	<b>General.....</b>	<b>11</b>
<b>4.2.2</b>	<b>Transmissible internal forces, moments and related stiffnesses .....</b>	<b>11</b>
<b>5</b>	<b>Reference tubes and bar for coupler tests.....</b>	<b>15</b>
<b>6</b>	<b>General requirements.....</b>	<b>16</b>
<b>6.1</b>	<b>Materials .....</b>	<b>16</b>
<b>6.2</b>	<b>Design.....</b>	<b>16</b>
<b>6.3</b>	<b>Manufacturer's drawings .....</b>	<b>18</b>
<b>6.4</b>	<b>Production control .....</b>	<b>18</b>
<b>7</b>	<b>Tests methods and evaluation of results.....</b>	<b>19</b>
<b>7.1</b>	<b>General.....</b>	<b>19</b>
<b>7.2</b>	<b>Half couplers.....</b>	<b>21</b>
<b>7.2.1</b>	<b>General.....</b>	<b>21</b>
<b>7.2.2</b>	<b>Slipping force <math>F_s</math> of a half coupler .....</b>	<b>21</b>
<b>7.2.3</b>	<b>Failure force <math>F_f</math> of a half coupler .....</b>	<b>22</b>
<b>7.2.4</b>	<b>Pull apart force <math>F_p</math> of a half coupler.....</b>	<b>24</b>
<b>7.2.5</b>	<b>Shear force <math>F_q</math> of a half coupler .....</b>	<b>25</b>
<b>7.2.6</b>	<b>Stiffnesses and bending moments of a half coupler .....</b>	<b>26</b>
<b>7.2.7</b>	<b>Indentation of a half coupler .....</b>	<b>29</b>
<b>7.3</b>	<b>Sleeve couplers with shear studs (SS) .....</b>	<b>30</b>
<b>7.3.1</b>	<b>Failure force <math>F_f</math> of sleeve couplers .....</b>	<b>30</b>
<b>7.3.2</b>	<b>Bending moment <math>M_B</math> of sleeve couplers .....</b>	<b>31</b>
<b>7.4</b>	<b>Reduction couplers .....</b>	<b>33</b>
<b>7.4.1</b>	<b>General.....</b>	<b>33</b>
<b>7.4.2</b>	<b>Slipping and failure force of a reduction coupler (RR and RS).....</b>	<b>33</b>
<b>7.4.3</b>	<b>Pull apart force of a right angle reduction coupler (RR) .....</b>	<b>33</b>
<b>7.4.4</b>	<b>Indentation (RR and RS).....</b>	<b>33</b>
<b>8</b>	<b>Designation .....</b>	<b>33</b>
<b>9</b>	<b>Marking .....</b>	<b>34</b>
<b>10</b>	<b>Test report.....</b>	<b>34</b>
<b>11</b>	<b>Assessment.....</b>	<b>34</b>

<b>12</b>	<b>Product manual</b> .....	<b>35</b>
	<b>Annex A</b> (informative) <b>Ongoing production control</b> .....	<b>36</b>
	<b>Annex B</b> (informative) <b>Information about the design of temporary works structures</b> .....	<b>38</b>
<b>B.1</b>	<b>General</b> .....	<b>38</b>
<b>B.2</b>	<b>Structural design</b> .....	<b>38</b>
<b>B.2.1</b>	<b>Stiffnesses and structural systems</b> .....	<b>38</b>
<b>B.2.2</b>	<b>Structural systems for components with half couplers</b> .....	<b>39</b>
<b>B.2.3</b>	<b>Characteristic values of resistances for design purposes</b> .....	<b>41</b>
<b>B.2.4</b>	<b>Verification of ultimate limit state — Interaction</b> .....	<b>42</b>
	<b>Bibliography</b> .....	<b>43</b>