

DIN EN 1366-10:2022-12 (E)

Fire resistance tests for service installations - Part 10: Smoke control dampers

Contents		Page
European foreword		7
Introduction		8
1	Scope	9
2	Normative references	9
3	Terms and definitions	9
4	Test equipment	12
4.1	General	12
4.2	Test duct for surface mounted SCDs	12
4.3	Connecting duct for compartment boundary mounted SCDs	13
4.3.1	Compartmentation test	13
4.3.2	Maintenance of opening test	13
4.4	Cycling equipment	13
4.5	Condensing unit	13
4.6	Gas temperature measuring devices	13
4.7	Exhaust fan system	13
4.8	Perforated plate	14
4.9	Volume and flow measurement for duct mounted SCDs	14
4.10	Volume flow measurement for compartment boundary mounted SCDs	14
4.10.1	Compartmentation test	14
4.10.2	Maintenance of opening test	14
4.11	Ambient leakage measurement equipment	15
4.12	Pressure sensors for differential pressure control	15
4.12.1	Duct mounted smoke control dampers	15
4.12.2	Compartment boundary mounted smoke control dampers	15
4.13	Welded connecting tube	15
4.14	Extract fan connecting duct	15
4.15	Extraction fan	15
4.16	Thermocouples	15
4.17	Oxygen measuring equipment	15
4.18	Observation windows	16
5	Test specimens	16
5.1	Cross-section	16
5.2	Design	16
5.2.1	General	16
5.2.2	Supporting constructions	16
5.2.3	Inclusion of grilles	17
6	Test methods	17
6.1	General	17
6.2	Test sequence	17
6.3	Ambient leakage	19
6.3.1	Units of the largest size	19
6.3.2	Units of smallest size	19
6.4	Cycling requirements	19
6.4.1	General	19

6.4.2	Smoke control damper to be used in dedicated smoke control systems, operated only in the case of emergency	19
6.4.3	Smoke control damper to be used as part of a general HVAC system as well as a smoke control system, or as part of a smoke control systems that is cycled every day to check operation	19
6.4.4	Smoke control damper to be used as part of a general HVAC system as well as a smoke control system, that uses a modulating actuator	20
6.5	Selection of elevated temperature and fire resistance tests	20
6.6	Fire resistance tests and elevated temperature tests	21
6.6.1	Duct mounted smoke control dampers	21
6.6.2	Compartment boundary mounted smoke control dampers	22
6.6.3	Additional test information	25
6.7	Initiation regime	26
6.7.1	Smoke control dampers for systems with automatic activation (AA)	26
6.7.2	Smoke control damper for systems with manual activation (MA)	27
6.8	HOT400/30 extension test	29
6.9	Special constructions	29
7	Test procedure	29
7.1	Fire resistance or elevated temperature and maintenance of opening test for duct mounted smoke control dampers	29
7.1.1	General	29
7.1.2	Pre-test calibration	29
7.1.3	Ignition of furnace	31
7.1.4	Operate the damper	31
7.1.5	Furnace conditions	31
7.1.6	Thermocouples for insulation (I)	31
7.1.7	Oxygen measurements	32
7.1.8	General observations	32
7.1.9	Reduction of cross-section/maintenance of opening	32
7.1.10	Leakage calculations	32
7.1.11	Termination of test	32
7.2	Fire resistance tests for smoke control dampers mounted in a compartment boundary	33
7.2.1	General	33
7.2.2	Pre-test calibration	33
7.2.3	Ignition of furnace	33
7.2.4	Operate the damper	33
7.2.5	Furnace conditions	33
7.2.6	Thermocouples for insulation (I)	33
7.2.7	General observations	34
7.2.8	Leakage calculations	34
7.2.9	Termination of test	34
7.3	Maintenance of opening test for compartment boundary mounted smoke control dampers	34
7.3.1	General	34
7.3.2	Pre-test calibration	34
7.3.3	Ignition of furnace	35
7.3.4	Operate a damper	35
7.3.5	Furnace conditions	35
7.3.6	Thermocouples for insulation (I)	35
7.3.7	General observations	35
7.3.8	Reduction of cross-section/maintenance of opening	36
7.3.9	Termination of test	36
8	Performance criteria	36
8.1	Integrity	36
8.1.1	General	36
8.1.2	Integrity at perimeter	36
8.2	Insulation	40
8.2.1	General	40
8.2.2	Thermocouples at the compartment boundary outside of the furnace	40
8.3	Reduced leakage	40

8.4	Times and observations	41
8.5	Other	41
9	Test report	41
9.1	General	41
9.2	Duct mounted single and multi-compartment tests	42
9.3	Compartment boundary compartmentation test	43
9.4	Compartment boundary maintenance of opening test	43
10	Direct field of application of test results (DIAP)	44
10.1	Compartment boundary mounted smoke control dampers	44
10.2	Smoke control damper sizes	44
10.3	Duct mounted smoke control damper mounting positions	44
10.4	Distance between mounting positions in compartment boundary applications	44
10.5	Blade pivot axis	44
10.6	Pressure difference	45
10.7	Elevated temperatures	45
10.8	Cycling tests	45
10.8.1	Smoke control dampers meeting the cycling requirements for modulating applications ...	45
10.8.2	Smoke control dampers meeting the cycling requirements for use with combined smoke control and general HVAC applications and for smoke control systems that are cycle checked every day	45
10.8.3	Smoke control dampers meeting the cycling requirements for smoke control dampers that are operated only in the case of emergency	45
10.8.4	Load application	45
10.9	Initiation method	45
10.10	Duct mounted smoke control dampers - application to ducts other than that tested	46
10.10.1	Single compartment smoke control dampers	46
10.10.2	Multi compartment smoke control dampers	46
10.11	Compartment mounted smoke control dampers - application to shafts, walls and constructions other than that tested	47
10.11.1	Single compartment smoke control dampers	47
10.11.2	Multi compartment smoke control dampers	47
10.12	Standard damper open or closed position	47
Annex A (normative) Cycling test		74
A.1	General	74
A.2	Purpose of the test	74
A.3	Method of Application for loading	74
A.3.1	General	74
A.3.2	Smoke control damper with single blade	74
A.3.3	Smoke control damper with multi blades of smaller area	75
A.3.4	Circular smoke control dampers load calculation	75
A.3.5	Test arrangement for dampers with horizontal blade pivot axis	76
A.3.6	Test arrangement for dampers with vertical blade pivot axis	77
A.3.7	Report	80
A.4	Background for the torque value (informative)	80
A.4.1	Threshold rates of the working condition of the system	80
A.4.2	Previous experience	80
Annex B (informative) Leakage calculation from oxygen measurement		82
B.1	General	82
B.2	Supporting information on leakage flowrate calculations	83
B.2.1	Components in mixed fluids (mass and volume ratios)	83
B.2.2	Application to oxygen in air	84
B.2.3	Volume ratios and conservation of the mass during the smoke exhaust test	84
B.2.4	Assumptions and reworking	86
Annex C (normative) Maintenance of opening calculation		88

C.1	Calculation of the theoretical total mass M_{max} of hot gases during the fire test	88
C.1.1	Basis	88
C.1.2	Method	88
C.1.3	Summary	89
C.2	Calculation of the actual total mass M_{actual} of hot gases during the fire test	90
C.2.1	Basis	90
C.2.2	Method	91
C.2.3	Summary	92
C.2.4	Graphical representation of typical integral calculation from data	92
Annex D (normative) Optional High Operating Test HOT 400/30 classification		94
D.1	General	94
D.2	Tests	94
D.2.1	General	94
D.2.2	Equipment	94
D.2.3	Ambient leakage test	95
D.2.4	Cycling test	95
D.2.5	Ambient leakage test	95
D.2.6	Standby temperature test	95
D.2.7	HOT 400/30 Test	95
D.2.8	Performance criteria	96
Annex E (informative) Leakage and pressure classification clarification		99
Bibliography		100