DIN EN 1998-2/NA:2022-12 (E)

National Annex - Nationally determined parameters - Eurocode 8: Design of structures for earthquake resistance - Part 2: Bridges

Contents

Page

Foreword ... 4

NA.1 Scope ... 5

NA.2 National provisions for the application of DIN EN 1998-2:2011-12 ... 5
NA.2.1 General ... 5
NA.2.2 National provisions (Nationally determined parameters) ... 6
NDP re 1.1.1(8) Scope of DIN EN 1998-2 ... 6
NCI re 1.2.4 Normative references ... 6
NCI re 2.1(2)P Design seismic action ... 7
NDP re 2.1(3)P Design seismic action ... 7
NDP re 2.1(4)P Design seismic action and 2.1(6)P Design seismic action ... 7
NDP re 2.2.2 (5) Ultimate limit states (ULS) ... 8
NDP re 2.3.5.3(1) Local ductility at the plastic hinges ... 8
NDP re 2.3.6.3(5) Control of displacements — Detailing ... 8
NDP re 2.3.7(1) Simplified criteria ... 8
NDP re 2.3.7(1) Simplified criteria ... 8
NDP re 3.2.2.3(1)P Near source effects ... 8
NDP re 3.3(1)P Spatial variability of the seismic action ... 8
NDP re 3.3(6)P Spatial variability of the seismic action ... 9
NDP re 3.3(6)P Spatial variability of the seismic action ... 9
NDP re 4.1.2(4)P Masses ... 9
NDP re 4.1.8(2)P Regular and irregular seismic behaviour of ductile bridges ... 9
NDP re 5.3(4) Capacity design ... 9
NDP re 5.4(1) Second order effects ... 9
NDP re 5.6.2(2)P Structures of limited ductile behaviour ... 9
NDP re 6.2.1.4(1)P Required confining reinforcement ... 9
NDP re 6.5.1(1)P Verification of ductility of critical sections ... 10
NDP re 6.6.2.3(3) Elastomeric bearings ... 10
NDP re 6.6.3.2(1)P Holding-down devices ... 10
NDP re 6.7.3(7) Abutments rigidly connected to the deck ... 10
NDP re 7.4.1(1)P Design spectra ... 10
NDP re 7.6.2(1)P Isolating system ... 10
NDP re 7.6.2(5) Isolating system ... 10
NDP re 7.7.1(2) Lateral restoring capability ... 10
NDP re J.1(2) Factors causing variation of design properties ... 10
NDP re J.2(1) Evaluation of the variation ... 10

Annex NA.A (informative) Simplified design rules for simple bridges ... 11
NA.A.1 General ... 11
NA.A.2 Determination of the horizontal seismic forces ... 12
NA.A.2.1 General ... 12
NA.A.2.2 Excitation in the longitudinal direction — use of movable bearings at the abutment ... 12
NA.A.2.3 Excitation in the longitudinal direction — use of fixed bearings at the abutment ... 13
NA.A.2.4 Excitation in the transverse direction ... 13
NA.A.3 Combination of the action effects due to the components of the seismic action ... 15
NA.A.4 Torsional effects (rotation about the vertical axis) ... 15
NA.A.5 Displacements, joints, minimum bearing lengths ... 15
NA.A.5.1 (Relative) displacements ... 15

NA.A.5.2 Joints 16
NA.A.5.3 Minimum overlap length 16
NA.A.6 Stability analysis 17
NA.A.7 Abutments and retaining walls 18
NA.A.7.1 Abutments flexibly connected to the deck 18
NA.A.7.2 Abutments rigidly connected to the deck 19
NA.A.8 Bearings 19
NA.A.8.1 Fixed bearings 19
NA.A.8.2 Movable bearings 19
NA.A.8.3 Elastomeric bearings 19
NA.A.9 Avoidance of brittle fracture of specific non-ductile components 19
NA.A.10 Special rules for concrete members 20
NA.A.10.1 General 20
NA.A.10.2 Confining reinforcement in piers 20

Figures

Figure NA.A.1 — Model of the excitation in the longitudinal direction where the deck is supported by fixed bearings at the abutment (elevation) 13

Figure NA.A.2 — Model of a beam bridge with horizontal forces — F_{i} due to excitation in the transverse direction (view from above) 14

Figure NA.A.3 — Minimum overlap length at the abutment if movable bearings are used 17

Tables

Table NA.1 — Importance classes and importance factors 8

Table NA.2 — Distance of abutments beyond which ground motions are to be considered as uncorrelated 9

Table NA.A.1 — Limits of the length of continuous bridge decks — L_{lim} 11