# DIN EN 14488-3:2024-01 (E)

## Testing sprayed concrete - Part 3: Flexural strengths (first peak, ultimate and residual) of fibre reinforced beam specimens

## Contents

Page


European foreword ..... 3

Introduction ..... 4

1 Scope ..... 5

2 Normative references ..... 5

3 Terms and definitions ..... 5

4 Symbols and abbreviated terms ..... 6
4.1 Symbols ..... 6
4.2 Abbreviations ..... 7

5 Principle ..... 7

6 Method A: Four point bending test on beam ..... 7
6.1 Apparatus ..... 7
6.1.1 Testing machine ..... 7
6.1.2 Force application ..... 8
6.1.3 Deflection measurement and control ..... 9
6.2 Test specimen ..... 9
6.2.1 General ..... 9
6.2.2 Adjustment of test specimens ..... 10
6.3 Procedures ..... 10
6.3.1 Preparation and positioning of specimens ..... 10
6.3.2 Loading ..... 11
6.4 Expression of results ..... 11
6.4.1 First peak and ultimate flexural strengths ..... 11
6.4.2 Residual flexural strengths ..... 12
6.5 Test report ..... 13
6.6 Accuracy ..... 13

7 Method B: Three point bending test on square panel with notch ..... 14
7.1 Apparatus ..... 14
7.1.1 Testing machine ..... 14
7.2 Test specimens ..... 15
7.2.1 Shape and size of test specimens ..... 15
7.2.2 Manufacture and curing of test specimens ..... 15
7.2.3 Notching of test specimens ..... 15
7.3 Testing procedure ..... 16
7.3.1 Preparation and positioning of test specimens ..... 16
7.3.2 Bending test ..... 19
7.4 Expression of results ..... 19
7.4.1 Equivalence between CMOD and deflection ..... 19
7.4.2 Limit of proportionality ..... 20
7.4.3 Residual flexural tensile strength ..... 20
7.5 Test report ..... 22
7.6 Precision ..... 22