

DIN EN 1999-1-5:2024-11 (E)

Eurocode 9 - Design of aluminium structures - Part 1-5: Shell structures

Contents		Page
	European foreword	5
0	Introduction	6
1	Scope	8
1.2	Assumptions	9
2	Normative references	10
3	Terms, definitions and symbols	10
3.1	Terms and definitions	10
3.1.1	Structural forms and geometry	10
3.1.2	Special definitions for buckling calculations	11
3.2	Symbols	12
3.3	Sign conventions	16
3.4	Coordinate systems	16
4	Basis of design	18
4.1	General	18
4.2	Consequence class and execution class	18
5	Materials and geometry	19
5.1	Material properties	19
5.2	Design values of geometrical data	19
5.3	Geometrical tolerances and geometrical imperfections	19
6	Durability	19
7	Structural analysis	19
7.1	Geometry	19
7.2	Boundary conditions	20
7.3	Actions and environmental influences	21
7.4	Stress resultants and stresses	22
7.5	Types of analysis	22
8	Ultimate limit state	23
8.1	Resistance of cross section	23
8.1.1	Design values of stresses	23
8.1.2	Design values of resistance	24
8.1.3	Stress limitation	25
8.1.4	Design by numerical analysis	25
8.2	Buckling resistance	25
8.2.1	General	25
8.2.2	Buckling-relevant geometrical tolerances	26
8.2.3	Shell in compression and shear	27
8.2.4	Effect of welding	30
8.2.5	Design by numerical analysis	33
9	Serviceability limit states	33
9.1	General	33
9.2	Deflections	33

Annex A (normative) Formulae for shell buckling analysis	34
A.1 Use of this annex	34
A.2 Scope and field of application	34
A.3 Unstiffened cylindrical shells of constant wall thickness	34
A.3.1 Notations and boundary conditions	34
A.3.2 Meridional (axial) compression	35
A.3.3 Circumferential (hoop) compression	37
A.3.4 Shear	40
A.3.5 Meridional (axial) compression with coexistent internal pressure	41
A.3.6 Combinations of meridional (axial) compression, circumferential (hoop) compression and shear	42
A.4 Unstiffened cylindrical shells of stepwise wall thickness	44
A.4.1 General	44
A.4.2 Meridional (axial) compression	45
A.4.3 Circumferential (hoop) compression	45
A.4.4 Shear	49
A.5 Unstiffened lap jointed cylindrical shells	50
A.5.1 Geometry and stress resultants	50
A.5.2 Meridional (axial) compression	50
A.5.3 Circumferential (hoop) compression	50
A.5.4 Shear	51
A.6 Unstiffened conical shells	51
A.6.1 General	51
A.6.2 Design buckling stresses	52
A.6.3 Buckling strength verification	52
A.7 Stiffened cylindrical shells of constant wall thickness	53
A.7.1 General	53
A.7.2 Isotropic walls with meridional stiffeners	53
A.7.3 Isotropic walls with circumferential stiffeners	55
A.7.4 Circumferentially corrugated walls with meridional stiffeners	55
A.7.5 Axially corrugated walls with ring stiffeners	59
A.7.6 Stiffened wall treated as an orthotropic shell	60
A.7.7 Equivalent orthotropic properties of corrugated sheeting	63
A.8 Unstiffened spherical shells under uniform circumferential compression	64
A.8.1 Notations and boundary conditions	64
A.8.2 Critical buckling stresses	65
A.8.3 Circumferential buckling parameter	65
Annex B (informative) Formulae for buckling analysis of tori-conical and tori-spherical shells	67
B.1 Use of this Annex	67
B.2 Scope and field of application	67
B.3 Notations and boundary conditions	67
B.4 External pressure	68
B.4.1 Critical external pressure	68
B.4.2 Uniform squash limit external pressure	69
B.4.3 External pressure buckling parameter	71
B.5 Internal pressure	71
B.5.1 Critical internal pressure	71
B.5.2 Uniform squash limit internal pressure	72
B.5.3 Internal pressure buckling parameter	73
Bibliography	75