

ISO 18096:2022-08 (E)

Thermal insulating products for building equipment and industrial installations - Determination of maximum service temperature for preformed pipe insulation

| Contents | | Page |
|---------------------|--|-------------|
| Foreword | | iv |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Principle | 1 |
| 5 | Apparatus | 2 |
| 6 | Test specimens | 4 |
| 6.1 | Dimensions of test specimens | 4 |
| 6.2 | Number of test specimens | 4 |
| 6.3 | Conditioning of test specimens | 5 |
| 7 | Procedure | 5 |
| 7.1 | Test conditions | 5 |
| 7.2 | Test procedure | 5 |
| 8 | Calculation and expression of results | 6 |
| 8.1 | Thickness deformation versus time | 6 |
| 8.2 | Additional tests and/or observations | 8 |
| 8.3 | Internal self-heating | 8 |
| 9 | Accuracy of measurement | 8 |
| 10 | Test report | 9 |
| Annex A (normative) | Modifications of and additions to the general test method for mineral wool products | 10 |
| Annex B (normative) | Modifications of and additions to the general test method for polyethylene foam (PEF) and flexible elastomeric foam (FEF) products | 12 |
| Annex C (normative) | Modifications of and additions to the general test method for phenolic foam products | 15 |
| Bibliography | | 17 |