

DIN EN 1998-5/NA:2023-11 (E)

National Annex - National determined parameters - Eurocode 8: Design of structures for earthquake resistance - Part 5: Foundations, retaining structures and geotechnical aspects

Contents

Page

| | |
|--|----------|
| Foreword | 3 |
| NA.1 Scope | 4 |
| NA.2 National provisions | 4 |
| NA.2.1 General | 4 |
| NA.2.2 National provisions | 4 |
| NDP re 1.1(4) Scope | 4 |
| NCI re 1.1 Scope | 4 |
| NCI re 1.2.1 General reference standards | 5 |
| NDP re 3.1(3) Strength parameters | 5 |
| NDP re 4.1.4(11)P Potentially liquefiable soils..... | 5 |
| NCI re 4.2.2(1)P Determination of the ground type for the definition of the seismic action | 5 |
| NDP re 5.2(2)P c) Rules for conceptual design..... | 5 |
| NCI re 5.4.1.2(2) Foundation horizontal connections..... | 5 |
| Annex NA.G (normative) Simplified design rules for foundations of simple structures and simple retaining structures | 6 |
| NA.G.1 General | 6 |
| NA.G.2 Soil investigations | 6 |
| NA.G.3 Structural strength verification..... | 6 |
| Annex NA.H (normative) Simplified verification against soil liquefaction | 7 |
| Annex NA.I (normative) Verification of the seismic bearing capacity of shallow foundations | 9 |

Figures

| | |
|---|----------|
| Figure NA.H.1 — Minimum values of the peak pressure of the pressure probe as a function of acceleration according to DIN EN 1998-1/NA:2023-11, Equation (NA.1): (a) FC = 0 %, (b) FC = 15 %, (c) FC = 35 % | 8 |
|---|----------|