

DIN EN 15026:2023-12 (E)

Hygrothermal performance of building components and building elements - Assessment of moisture transfer by numerical simulation

| Contents | | Page |
|-------------------------|--|-------------|
| European foreword | | 5 |
| Introduction | | 6 |
| 1 | Scope | 8 |
| 2 | Normative references | 8 |
| 3 | Terms, definitions, symbols and units | 8 |
| 4 | Hygrothermal formulae and material properties | 10 |
| 4.1 | Assumptions | 10 |
| 4.2 | Balance formulae | 11 |
| 4.2.1 | General | 11 |
| 4.2.2 | Internal energy density | 11 |
| 4.2.3 | Additional source terms | 12 |
| 4.3 | Relations between driving potentials and conserved quantities | 12 |
| 4.4 | Transport of heat and moisture | 12 |
| 4.4.1 | General | 12 |
| 4.4.2 | Heat and enthalpy transport inside materials | 12 |
| 4.4.3 | Moisture transport | 13 |
| 4.4.4 | Moisture transport across material interfaces/vapour retarders/foils | 14 |
| 4.4.5 | Internal air layers | 15 |
| 4.5 | Material properties | 15 |
| 5 | Boundary and initial conditions | 15 |
| 5.1 | Inside conditions | 15 |
| 5.1.1 | Usage conditions | 15 |
| 5.1.2 | Parameters | 16 |
| 5.1.3 | Sources of data | 16 |
| 5.2 | Outside conditions | 16 |
| 5.2.1 | Sources of data | 16 |
| 5.2.2 | Climate parameters | 17 |
| 5.3 | Interpolation of tabulated climatic data | 17 |
| 5.4 | Boundary heat and moisture flows | 18 |
| 5.4.1 | Heat transfer | 18 |
| 5.4.2 | Vapour diffusion | 21 |
| 5.4.3 | Convective latent heat flow | 21 |
| 5.4.4 | Wind driven rain | 21 |
| 5.5 | Initial conditions | 22 |
| 6 | Numerical simulation | 22 |
| 6.1 | Background | 22 |
| 6.2 | Geometrical modelling | 23 |
| 6.3 | Grid and time step sensitivity studies | 23 |
| 7 | Documentation of input data and results | 24 |
| 7.1 | General | 24 |
| 7.2 | Problem description | 24 |
| 7.2.1 | General | 24 |
| 7.2.2 | Scope and subject of simulation | 24 |

| | | |
|---|---|-----------|
| 7.3 | Model geometry and input parameters | 24 |
| 7.3.1 | Simulated geometry | 24 |
| 7.3.2 | Initial conditions | 24 |
| 7.3.3 | Boundary conditions | 24 |
| 7.3.4 | Material parameters | 25 |
| 7.3.5 | Auxiliary models | 25 |
| 7.3.6 | Output specifications | 25 |
| 7.4 | Simulation method and numerical properties | 25 |
| 7.4.1 | General | 25 |
| 7.4.2 | Simulation tool | 25 |
| 7.4.3 | Numerical simulation properties | 25 |
| 7.4.4 | Numerical accuracy control | 26 |
| 7.5 | Calculation report | 26 |
| 7.5.1 | General | 26 |
| 7.5.2 | Display of results | 26 |
| 7.5.3 | Interpretation of the results | 26 |
| Annex A (informative) Material parameters | | 28 |
| A.1 | General | 28 |
| A.2 | Heat storage | 28 |
| A.3 | Heat transport | 28 |
| A.4 | Moisture storage | 30 |
| A.5 | Moisture transport properties | 31 |
| A.5.1 | General | 31 |
| A.5.2 | Water vapour diffusion resistance | 31 |
| A.5.3 | Liquid transport properties | 33 |
| A.6 | Material-related model limitations | 34 |
| A.6.1 | General | 34 |
| A.6.2 | Influence of material boundaries on liquid moisture transport | 34 |
| A.6.3 | Hysteresis phenomena | 34 |
| A.6.4 | Swelling | 35 |
| A.6.5 | Weathering and ageing | 35 |
| Annex B (normative) Benchmark tests | | 36 |
| B.1 | General | 36 |
| B.1.1 | General background | 36 |
| B.1.2 | Reference implementation | 36 |
| B.2 | Problem description | 36 |
| B.3 | Results | 38 |
| B.4 | Other benchmark cases and validation suites | 40 |
| Annex C (informative) Moisture design years | | 41 |
| Annex D (normative) Inside boundary conditions for residential and office buildings | | 42 |
| Annex E (normative) Auxiliary models for the simplified inclusion of special effects | | 43 |
| E.1 | General | 43 |
| E.2 | Rear ventilation and venting of building components | 43 |
| E.3 | Condensation caused by air flow through building components | 44 |
| E.4 | Wind driven rain penetration | 45 |
| Bibliography | | 47 |