

DIN EN 16637-3:2024-01 (E)

Construction products - Assessment of release of dangerous substances - Part 3: Horizontal up-flow percolation test

Contents		Page
European foreword		4
Introduction		6
1	Scope	7
2	Normative references	7
3	Terms and definitions	8
4	Symbols and abbreviations	11
4.1	Symbols	11
4.2	Abbreviations	11
5	Principle	12
5.1	General principles	12
5.2	Number of eluates	12
6	Reagents	13
7	Equipment	14
8	Sample preparation	16
8.1	General	16
8.2	Preparation of the test sample	16
8.2.1	Principles	16
8.2.2	Rules of application	16
8.3	Test portion	17
8.4	Drying	17
8.5	Subsampling	17
8.6	Sieving of samples into fractions	18
8.7	Size reduction of particles	18
9	Test procedure	18
9.1	Temperature	18
9.2	Determination of dry residue	18
9.3	Pre-treatment of the column	18
9.4	Packing of the column	19
9.4.1	General	19
9.4.2	Equilibration	19
9.4.3	Calculation of the flow rate	19
9.5	Collection of eluates	19
9.6	Further preparation of the eluates for analysis	22
9.7	Blank test	22
10	Evaluation of measurement results	22
10.1	Expression of results in concentrations	22
10.2	Expression of results in terms of mass related release	22
11	Documentation and test report	23

12	Test performance	25
13	Indirect methods	25
13.1	Definition	25
13.2	Provisions	25
13.3	Examples of indirect methods	25
Annex A (informative) Examples of sample preparation procedures		26
Annex B (informative) Illustration of the column and accompanying equipment		29
Annex C (informative) Procedures for packing and saturation of the column		30
Annex D (informative) Assessment of release mechanism(s)		33
Annex E (informative) Summary of cumulative results for L/S = 2 and L/S = 10		53
Bibliography		69