

DIN EN 1993-3-1/NA:2024-09 (E)

National Annex - Nationally determined parameters - Eurocode 3: Design of steel structures - Part 3-1: Towers, masts and chimneys - Towers and masts

| Contents | Page |
|---------------------------------------|-------------|
| Foreword | 5 |
| NA.1 Scope | 6 |
| NA.2.1 General | 6 |
| NA.2.2 National provisions | 7 |
| NCI re 1.2 Normative references | 7 |
| NDP re 2.1.1(3)P | 8 |
| NDP re 2.3.1(1) | 8 |
| NDP re 2.3.2(1) | 8 |
| NDP re 2.3.6(2) | 8 |
| NDP re 2.3.7(1) | 9 |
| NDP re 2.3.7(4) | 9 |
| NDP re 2.5(1) | 9 |
| NDP re 2.6(1) | 9 |
| NDP re 4.1(1) | 9 |
| NDP re 4.2(1) | 9 |
| NDP re 5.1(6) | 9 |
| NDP re 5.2.4(1) | 9 |
| NDP re 6.1(1) | 9 |
| NDP re 6.3.1(1) | 10 |
| NDP re 6.4.1(1) | 10 |
| NDP re 6.4.2(2) | 10 |
| NDP re 6.5.1(1) | 10 |
| NDP re 7.1(1) | 10 |
| NCI re 9.1 | 10 |
| NDP re 9.5(1) | 10 |
| NDP re A.1(1) | 11 |

| | |
|---|-----------|
| NDP re A.2(1)P (2 places) | 11 |
| NCI re Annex B | 11 |
| NCI re Annex C | 11 |
| NDP re D.1.1(2) | 11 |
| NDP re D.1.2(2) | 11 |
| NDP re D.3(6) (2 places) | 11 |
| NDP re D.4.1(1) | 12 |
| NDP re D.4.2(3) | 12 |
| NDP re D.4.3(1) | 12 |
| NDP re D.4.4(1) | 12 |
| NCI re Annex F | 12 |
| Annex NA.B (normative) Assumptions for wind actions | 13 |
| NA.B.1 NCI General | 13 |
| NA.B.1.1 NCI Scope | 13 |
| NA.B.1.2 NCI Symbols and indices | 13 |
| NA.B.2 NCI Wind force coefficient | 14 |
| NA.B.2.1 NCI General | 14 |
| NA.B.2.2 NCI Reference area | 15 |
| NA.B.2.3 NCI Determination of the wind force coefficient | 15 |
| NA.B.3 NCI Gust response of lattice towers | 24 |
| NA.B.3.1 NCI Criteria for static methods | 24 |
| NA.B.3.2 NCI Equivalent static method | 25 |
| NA.B.3.3 NCI Crosswind vortex vibrations | 26 |
| NA.B.4 NCI Response of guyed masts | 27 |
| NA.B.4.1 NCI General | 27 |
| NA.B.4.2 NCI Criteria for static methods | 27 |
| NA.B.4.3 NCI Equivalent static methods | 28 |
| NA.B.4.4 NCI Spectral analysis method | 32 |
| NA.B.4.5 NCI Vortex-excited vibrations | 32 |
| NA.B.4.6 NCI Guy vibrations | 33 |
| NA.B.4.7 NCI Natural frequency of free-standing towers | 34 |

| | |
|--|-----------|
| NA.B.4.8 NCI Natural frequency for cantilevered guyed masts | 34 |
| Annex NA.C (normative) Ice loading and combinations of ice with wind | 36 |
| NA.C.1 NCI General | 36 |
| NA.C.2 NCI Ice loading | 36 |
| NA.C.3 NCI Ice weight | 37 |
| NA.C.4 NCI Wind and ice | 37 |
| Annex NA.F (normative) Execution and monitoring of conditions | 38 |
| NA.F.1 NCI Execution | 38 |
| NA.F.2 NCI Monitoring of conditions | 39 |
| NA.F.3 NCI Main inspection | 39 |
| Annex NA.I (normative) Additional technical regulations | 40 |
| NA.I.1 NCI Persons falling in safety harnesses | 40 |
| NA.I.2 NCI Information on the calculation of bracing | 40 |
| NA.I.3 NCI Bolted connections | 40 |
| NA.I.4 NCI Minimum thickness | 40 |
| NA.I.5 NCI Cross-section bracing | 40 |
| NA.I.6 NCI Wire rope grips | 41 |
| NA.I.7 NCI Bolts | 41 |
| NA.I.8 NCI Insulators and protective fittings | 41 |
| NA.I.8.1 NCI General | 41 |
| NA.I.8.2 NCI Ceramic insulators | 41 |
| NA.I.8.3 NCI Safety and routine testing of ceramic insulators subjected to pressure | 42 |
| NA.I.8.4 NCI Other insulators | 42 |
| NA.I.9 NCI Foundations | 42 |
| NA.I.9.1 NCI Concrete foundations | 42 |
| NA.I.9.2 NCI Anchoring | 42 |
| NA.I.9.3 NCI Auxiliary anchors | 43 |
| NA.I.10 NCI Corrosion protection | 43 |
| NA.I.10.1 NCI General | 43 |
| NA.I.10.2 NCI Coatings | 43 |
| NA.I.11 NCI Lightning protection and earthing systems | 44 |

| | |
|---|----|
| NA.I.12 NCI Installation aids | 45 |
| NA.I.13 NCI Equipment for accessing and inspecting the structure, fall protection | 45 |
| NA.I.13.1 NCI General | 45 |
| NA.I.13.2 NCI Ladders | 45 |
| NA.I.13.3 NCI Safety equipment on working platforms and walkways | 45 |
| NA.I.13.4 NCI Access to guys | 46 |
| NA.I.13.5 NCI Openings in hollow masts | 46 |
| Bibliography | 47 |
| Figures Figure NA.B.1 -- Definition of the face | 16 |
| Figure NA.B.2 -- Wind incidence factor K | 19 |
| Figure NA.B.3 -- Force coefficients $c_{f,S,0}$ for lattice structures with square or triangular cross-section | 21 |
| Figure NA.B.4 -- Load cases for lattice towers | 25 |
| Figure NA.B.5 -- Application of patch loads | 30 |
| Figure NA.B.6 -- Typical wind directions to be considered | 31 |
| Figure NA.B.7 -- Example of the effective length L_j for guyed masts | 32 |
| Figure NA.B.8 -- Basic value $c_{lat,0}$ for the aerodynamic excitation force coefficient as a function of the strake length l_w (applies for $Sc \geq 8$) | 33 |
| Figure NA.B.9 -- Coefficients for determining the natural frequency according to Equation (NA.B.29) | 35 |
| Figure NA.F.1 -- Erection tolerances | 39 |
| Figure NA.I.1 -- Example of the earthing of a guyed mast | 45 |
| Tables Table NA.1 -- Characteristic values for the Hertz pressure of steel bearings | 10 |
| Table NA.A.2 -- Partial factors G and Q for actions | 11 |
| Table NA.B.1 -- Typical force coefficients, $c_{f,A,0}$ and $c_{f,G,0}$, for individual members | 22 |
| Table NA.I.1 -- Ceramic insulators | 42 |