DIN EN 1366-9:2025-04 (E)

Fire resistance tests for service installations - Part 9: Single compartment smoke extraction ducts

Contents

Page

European foreword 5

Introduction 7

1 Scope 8

2 Normative references 8

3 Terms and definitions 9

4 Test equipment 10
4.1 General 10
4.2 Furnace 10
4.3 Perforated plate 10
4.4 Air velocity measuring station 11
4.5 Ambient temperature leakage measuring device 11
4.6 Pressure sensors for differential pressure control 11
4.7 Welded connecting tube 11
4.8 Extract fan connecting duct 11
4.9 Extraction fan 12
4.10 Thermocouples 12
4.11 Oxygen measuring equipment 12
4.12 Oxygen measurement probes 12
4.13 Restraint equipment 12
4.14 Deflection measurements 12

5 Test conditions 12
5.1 Differential pressure conditions 12
5.2 Heating and pressure conditions 12

6 Test specimen 13
6.1 Size 13
6.1.1 Length 13
6.1.2 Cross-section 13
6.2 Number 13
6.3 Design 13

7 Installation of test specimen 14
7.1 General 14
7.2 Supporting construction 14
7.3 Duct arrangement 14
7.4 Restraint of ducts 14
7.4.1 Inside the furnace 14
7.4.2 Outside the furnace 14
7.5 Perforated plate 15

8 Conditioning 15
8.1 General 15
8.2 Water based sealing materials 15

9 Application of instrumentation 15

9.1 Thermocouples ... 15
9.1.1 Furnace thermocouples (plate thermometers) ... 15
9.1.2 Gas temperature within flow nozzles ... 15
9.2 Pressure ... 15
9.2.1 Furnace pressure ... 15
9.2.2 Differential under-pressure in duct ... 15
9.3 Oxygen measurements ... 16
9.4 Deflection measurement for determination of reduction of internal cross-sectional area ... 16

10 Test procedure ... 17
10.1 Pre-test adjustment ... 17
10.1.1 Oxygen-measuring instrument ... 17
10.1.2 Perforated plate ... 17
10.2 Leakage measurement at ambient temperature ... 17
10.3 Pre-fire test procedures ... 18
10.4 Fire test ... 18
10.5 Termination of test ... 19

11 Performance criteria ... 20
11.1 General requirements ... 20
11.2 Criteria at ambient temperature ... 20
11.2.1 Ambient leakage ... 20
11.2.2 Maintenance of cross-section under ambient conditions outside the furnace ... 20
11.3 Criteria under fire conditions ... 20
11.3.1 General ... 20
11.3.2 Integrity ... 20
11.3.3 Smoke leakage ... 21

12 Test report ... 21

13 Direct field of application of test results ... 21
13.1 General ... 21
13.2 Duct sizes ... 22
13.3 Suspension device ... 22
13.4 Pressure difference ... 22
13.5 Vertical part of duct ... 22
13.6 Steel ducts ... 22

Annex A (informative) Measurement of volume/mass flow ... 36

A.1 Hints on measuring volume flow or mass flow with differential pressure devices ... 36
A.2 Density ... 36
A.3 Absolute pressure (barometric pressure) ... 36
A.4 Viscosity ... 37
A.5 Characteristic data of the inlet nozzles according to Figure 10 ... 37

Annex B (informative) Measurement of oxygen content ... 40

B.1 Details on measuring oxygen content with parametric cell analysers ... 40
B.2 Choice of O2 measuring devices ... 40
B.3 Effect of O2 measuring device errors ... 41
B.4 Zero and end point drift ... 41
B.5 Details on the creation of an oxygen content from 12,5 to 13,5 vol % within the furnace
43 Annex C (informative) The usage of correction factors for the consideration of different parameters ... 44

C.1 Details for the development of the correction factors and their error limits ... 44
C.2 The complete formula for the leakage mass flow and the parameters ... 44
C.3 Application of correction factors in the simple mass flow formulae and achievable accuracy ... 47

Bibliography ... 49