

ISO 16316:2024-10 (E)

Windows, doors and curtain walling - Impacted by windborne debris in windstorms - Test method and classification

Contents

Page

Foreword.....	v
1 Scope	1
2 Normative references	1
3 Terms and definitions	1
4 Symbols and abbreviated terms	4
5 Principle and significance	4
5.1 General.....	4
5.2 Significance and use.....	5
5.3 Options.....	5
6 Test apparatus	5
7 Test specimens	7
7.1 General.....	7
7.2 Test specimen size.....	7
7.3 Test specimen.....	7
7.4 Order of testing.....	8
8 Test procedure	8
8.1 General.....	8
8.2 Preparation.....	8
8.2.1 General.....	8
8.2.2 Installation.....	8
8.2.3 Conditioning.....	8
8.2.4 Missile impact.....	8
8.3 Missile impact test.....	9
8.3.1 Projectile descriptions.....	9
8.3.2 Impact-speed tolerance.....	9
8.3.3 Impact angle.....	9
8.3.4 Impact location.....	10
8.4 Air pressure cycling test.....	16
8.4.1 General.....	16
8.4.2 Leakage.....	16
8.4.3 Air-pressure differential.....	17
8.4.4 Cyclic test loading.....	17
9 Pass and fail assessment criteria	18
9.1 General.....	18
9.2 Glass infill(s).....	18
9.3 Panel(s).....	18
9.4 External emergency exit doorset (panic exit doorset).....	18
9.5 Edge releases.....	18
9.6 Windstorm protective systems.....	18
10 Product qualification	18
10.1 Requirements.....	18
10.2 Applicable missile for impact test.....	19
10.3 Levels of protection.....	19
10.4 Reference wind-speed zones.....	19

Annex A (normative) Required information and test report	21
Annex B (informative) Recommended missile-propulsion devices	24
Annex C (informative) Reference wind speed	26
Annex D (normative) Flow chart of test procedure	27
Annex E (informative) Guidance on substitution criteria for fenestration assemblies qualified under this document	29
Annex F (informative) Test program examples	43
Annex G (informative) Flow chart of engineering analysis for wind-borne debris resistant building envelope design	62
Bibliography	64