

# DIN EN 12046-2:2025-07 (E)

## Operating forces - Test method - Part 2: Doors

---

<b>Contents</b>		<b>Page</b>
European foreword .....		3
<b>1</b>	<b>Scope .....</b>	<b>4</b>
<b>2</b>	<b>Normative references .....</b>	<b>4</b>
<b>3</b>	<b>Terms and definitions .....</b>	<b>4</b>
<b>4</b>	<b>Principle of test .....</b>	<b>5</b>
<b>5</b>	<b>Test apparatus .....</b>	<b>5</b>
<b>5.1</b>	<b>Test rig .....</b>	<b>5</b>
<b>5.2</b>	<b>Equipment for application of forces and torques .....</b>	<b>5</b>
<b>5.3</b>	<b>Alternative equipment for application of forces and torques with weights .....</b>	<b>5</b>
<b>6</b>	<b>Test specimen .....</b>	<b>6</b>
<b>7</b>	<b>Test procedures .....</b>	<b>6</b>
<b>7.1</b>	<b>General .....</b>	<b>6</b>
<b>7.2</b>	<b>Load point .....</b>	<b>6</b>
<b>7.3</b>	<b>Procedure for determining the closing force .....</b>	<b>7</b>
<b>7.3.1</b>	<b>Applying the force by means of weight and pulley .....</b>	<b>7</b>
<b>7.3.2</b>	<b>Applying the force by other means .....</b>	<b>7</b>
<b>7.4</b>	<b>Procedure for determining the force and torque for operating the building hardware .....</b>	<b>7</b>
<b>7.5</b>	<b>Procedure for determining the minimum force to commence and maintain the motion .....</b>	<b>8</b>
<b>8</b>	<b>Test sequences .....</b>	<b>8</b>
<b>8.1</b>	<b>General .....</b>	<b>8</b>
<b>8.2</b>	<b>Specimens without self-closing devices .....</b>	<b>9</b>
<b>8.3</b>	<b>Specimens with self-closing devices .....</b>	<b>9</b>
<b>9</b>	<b>Expression of results .....</b>	<b>9</b>
<b>10</b>	<b>Test report .....</b>	<b>9</b>
<b>Annex A (informative) Typical test set-up for hinged or pivoted doorset .....</b>		<b>11</b>
<b>Annex B (informative) Typical test set-up for sliding doorset .....</b>		<b>12</b>
<b>Annex C (informative) Measuring points for handles, emergency exit devices and panic devices .....</b>		<b>13</b>
<b>Annex D (informative) Typical test set-up for determining the minimum force to open the door leaf .....</b>		<b>16</b>
<b>Bibliography .....</b>		<b>17</b>