

DIN 4150-2:2025-08 (E)

Vibrations in buildings - Part 2: Effects on persons in buildings

Contents		Page
Foreword		6
1	Scope	7
2	Normative references	7
3	Terms and definitions	8
4	Principle for evaluating the discomfort of humans in buildings caused by vibration immissions	11
4.1	General	11
4.2	Determination of the parameters to be evaluated	12
4.2.1	General	12
4.2.2	Weighted vibration severity KBF(t)	12
4.2.3	Maximum cycle KBF value KBFTi	13
4.2.4	Maximum weighted vibration severity KBFmax	13
4.2.5	Root-mean-square value of KBFTi KBFTm	13
4.2.6	Evaluation vibration severity KBFTr	14
5	Vibration measurement	14
5.1	Measuring instruments	14
5.2	Measurement directions and points of measurement	14
5.3	Measurement period	14
5.4	Monitoring	14
5.5	Uncertainty of measurement	15
6	Evaluation of vibration immissions	15
6.1	Parameters to be evaluated	15
6.2	Guideline values	15
6.3	Procedure	16
6.4	Determining KBFTr	18
6.4.1	Evaluation period Tr	18
6.4.2	Effects outside of rest periods	18
6.4.3	Effects during rest periods	19
6.4.4	Vibration immissions in commercial establishments	19
6.5	Source-specific requirements	19
6.5.1	Infrequent, short-term vibration	19
6.5.2	Vibration generated by road traffic	20
6.5.3	Vibration generated by rail traffic	21
6.5.4	Vibration generated by construction work	27
7	Approximating evaluation parameters from direct vibration recordings	28
8	Test report	30
Annex A (informative)	Flow chart showing the procedure for evaluating vibration generated by construction work	32
Annex B (informative)	Examples explaining the evaluation procedure	33
B.1	EXAMPLE 1 -- Sinusoidal long-term vibration; evaluation according to Table 1, line 2	33
B.1.1	Type of vibration immissions to be evaluated	33

B.1.2	Assumptions	33
B.1.3	Evaluation procedure	33
B.1.4	Conclusion	33
B.2	EXAMPLE 2 -- Sinusoidal long-term vibration; evaluation according to Table 1, line 4	33
B.2.1	Type of vibration immissions to be evaluated	33
B.2.2	Assumptions	34
B.2.3	Evaluation procedure	34
B.2.4	Conclusion	35
B.3	EXAMPLE 3 -- Steady-state long-term vibration	35
B.3.1	Type of vibration immissions to be evaluated	35
B.3.2	Assumptions	36
B.3.3	Evaluation procedure	36
B.3.4	Conclusion	37
B.4	EXAMPLE 4 -- Shocks outside of the rest period	37
B.4.1	Type of vibration immissions to be evaluated	37
B.4.2	Assumptions	38
B.4.3	Evaluation procedure	38
B.4.4	Conclusion	40
B.5	EXAMPLE 5 -- Shocks during the rest period	40
B.5.1	Type of vibration immissions to be evaluated	40
B.5.2	Assumptions	40
B.5.3	Evaluation procedure	40
B.5.4	Conclusion	40
B.6	EXAMPLE 6 -- Shocks; exposure period of 16 h daily	40
B.6.1	Type of vibration immissions to be evaluated	40
B.6.2	Assumptions	40
B.6.3	Evaluation procedure	40
B.6.4	Conclusion	41
B.7	EXAMPLE 7 -- Vibration effects generated by blasting	41
B.7.1	Type of vibration immissions to be evaluated	41
B.7.2	Assumptions	41
B.7.3	Evaluation procedure	41
B.7.4	Conclusion	41
B.8	EXAMPLE 8 -- Vibration effects generated by tram and subway traffic	42
B.8.1	Type of vibration immissions to be evaluated	42
B.8.2	Assumptions	43
B.8.3	Evaluation procedure	43
B.8.4	Conclusions	45
B.9	EXAMPLE 9 -- Vibration effects generated by rail traffic	46
B.9.1	Type of vibration immissions to be evaluated	46
B.9.2	Assumptions	48
B.9.3	Evaluation procedure	48
B.9.4	Conclusion	50
Annex C (informative) Explanatory notes		51
C.1	Explanatory notes re 3.4	51
C.2	Explanatory notes re 4.2.3	51
C.3	Explanatory notes re 5.2	51
C.4	Explanatory notes re 6.4.3	51
C.5	Explanatory notes re 6.5.1.2	51
C.6	Explanatory notes re 6.5.2	52
C.7	Explanatory notes re 6.5.3.1	52
C.8	Explanatory notes re 6.5.3.2	53
C.9	Explanatory notes re 6.5.3.3	53
C.10	Explanatory notes re 6.5.3.6	53
C.11	Explanatory notes re 6.5.4	54
Annex D (informative) Prognosis and spectral calculation of KB values		55
Bibliography		56

Figures

Figure 1 — Time history of the weighted vibration severity $KB_F(t)$ with representation of the maximum cycle KB_F values KB_{FTi}	13
Figure 2 — Flow chart for the evaluation procedure	17
Figure A.1 — Flow chart for evaluation according to 6.5.4	32
Figure B.1 — Time history of the weighted vibration severity $KB_F(t)$ for vibration immissions according to Example 1 (Clause B.1) and Example 2 (Clause B.2)	35
Figure B.2 — Time history of the weighted vibration severity $KB_F(t)$ for vibration immissions according to Example 3 (Clause B.3)	36
Figure B.3 — Time history of the weighted vibration severity $KB_F(t)$ for vibration immissions according to Examples 4 (Clause B.4) to Example 6 (Clause B.6)	38
Figure B.4 — Time histories for vibration immissions as in Example 7 (Clause B.7)	42
Figure B.5 — Measured time history of the vibration velocity at the centre of a floor of the residential building being investigated	43
Figure B.6 — Sketch showing the existing track, the planned track and the residential building to be investigated	46
Figure B.7 — Measured time history of the vibration velocity and the weighted vibration severity at the centre of a floor of the building being investigated.....	47
Figure C.1 — Relationship between evaluation vibration severity KB_{FTi} , the root-mean-square value of KB_{FTi} for trains $KB_{FTm,Zug}$ and train frequency.....	52

Tables

Table 1 — Guideline values A for evaluating vibration immissions occurring in rooms requiring protection.....	16
Table 2 — Evaluation factors α_{Zug} for taking account of the different characteristics of train passages and track location	23
Table 3 — A_0 values at night for new railways to be constructed	25
Table 4 — Guideline values A for effects of vibration generated by construction work (other than blasting).....	27
Table 5 — Empirical values for constant c_F for different types of vibration effects	30
Table B.1 — $KB_{FTi,Zug}$ values determined.....	44
Table B.2 — Maximum root-mean-square values for KB_{FTi} for train categories.....	48
Table B.3 — Operating programme for the zero scenario and plan scenario	49