

DIN 4150-2:2025-08 (E)

Vibrations in buildings - Part 2: Effects on persons in buildings

| Contents | | Page |
|-----------------------|---|-------------|
| Foreword | | 6 |
| 1 | Scope | 7 |
| 2 | Normative references | 7 |
| 3 | Terms and definitions | 8 |
| 4 | Principle for evaluating the discomfort of humans in buildings caused by vibration immissions | 11 |
| 4.1 | General | 11 |
| 4.2 | Determination of the parameters to be evaluated | 12 |
| 4.2.1 | General | 12 |
| 4.2.2 | Weighted vibration severity KBF(t) | 12 |
| 4.2.3 | Maximum cycle KBF value KBFTi | 13 |
| 4.2.4 | Maximum weighted vibration severity KBFmax | 13 |
| 4.2.5 | Root-mean-square value of KBFTi KBFTm | 13 |
| 4.2.6 | Evaluation vibration severity KBFTr | 14 |
| 5 | Vibration measurement | 14 |
| 5.1 | Measuring instruments | 14 |
| 5.2 | Measurement directions and points of measurement | 14 |
| 5.3 | Measurement period | 14 |
| 5.4 | Monitoring | 14 |
| 5.5 | Uncertainty of measurement | 15 |
| 6 | Evaluation of vibration immissions | 15 |
| 6.1 | Parameters to be evaluated | 15 |
| 6.2 | Guideline values | 15 |
| 6.3 | Procedure | 16 |
| 6.4 | Determining KBFTr | 18 |
| 6.4.1 | Evaluation period Tr | 18 |
| 6.4.2 | Effects outside of rest periods | 18 |
| 6.4.3 | Effects during rest periods | 19 |
| 6.4.4 | Vibration immissions in commercial establishments | 19 |
| 6.5 | Source-specific requirements | 19 |
| 6.5.1 | Infrequent, short-term vibration | 19 |
| 6.5.2 | Vibration generated by road traffic | 20 |
| 6.5.3 | Vibration generated by rail traffic | 21 |
| 6.5.4 | Vibration generated by construction work | 27 |
| 7 | Approximating evaluation parameters from direct vibration recordings | 28 |
| 8 | Test report | 30 |
| Annex A (informative) | Flow chart showing the procedure for evaluating vibration generated by construction work | 32 |
| Annex B (informative) | Examples explaining the evaluation procedure | 33 |
| B.1 | EXAMPLE 1 -- Sinusoidal long-term vibration; evaluation according to Table 1, line 2 | 33 |
| B.1.1 | Type of vibration immissions to be evaluated | 33 |

| | | |
|--|---|-----------|
| B.1.2 | Assumptions | 33 |
| B.1.3 | Evaluation procedure | 33 |
| B.1.4 | Conclusion | 33 |
| B.2 | EXAMPLE 2 -- Sinusoidal long-term vibration; evaluation according to Table 1, line 4 | 33 |
| B.2.1 | Type of vibration immissions to be evaluated | 33 |
| B.2.2 | Assumptions | 34 |
| B.2.3 | Evaluation procedure | 34 |
| B.2.4 | Conclusion | 35 |
| B.3 | EXAMPLE 3 -- Steady-state long-term vibration | 35 |
| B.3.1 | Type of vibration immissions to be evaluated | 35 |
| B.3.2 | Assumptions | 36 |
| B.3.3 | Evaluation procedure | 36 |
| B.3.4 | Conclusion | 37 |
| B.4 | EXAMPLE 4 -- Shocks outside of the rest period | 37 |
| B.4.1 | Type of vibration immissions to be evaluated | 37 |
| B.4.2 | Assumptions | 38 |
| B.4.3 | Evaluation procedure | 38 |
| B.4.4 | Conclusion | 40 |
| B.5 | EXAMPLE 5 -- Shocks during the rest period | 40 |
| B.5.1 | Type of vibration immissions to be evaluated | 40 |
| B.5.2 | Assumptions | 40 |
| B.5.3 | Evaluation procedure | 40 |
| B.5.4 | Conclusion | 40 |
| B.6 | EXAMPLE 6 -- Shocks; exposure period of 16 h daily | 40 |
| B.6.1 | Type of vibration immissions to be evaluated | 40 |
| B.6.2 | Assumptions | 40 |
| B.6.3 | Evaluation procedure | 40 |
| B.6.4 | Conclusion | 41 |
| B.7 | EXAMPLE 7 -- Vibration effects generated by blasting | 41 |
| B.7.1 | Type of vibration immissions to be evaluated | 41 |
| B.7.2 | Assumptions | 41 |
| B.7.3 | Evaluation procedure | 41 |
| B.7.4 | Conclusion | 41 |
| B.8 | EXAMPLE 8 -- Vibration effects generated by tram and subway traffic | 42 |
| B.8.1 | Type of vibration immissions to be evaluated | 42 |
| B.8.2 | Assumptions | 43 |
| B.8.3 | Evaluation procedure | 43 |
| B.8.4 | Conclusions | 45 |
| B.9 | EXAMPLE 9 -- Vibration effects generated by rail traffic | 46 |
| B.9.1 | Type of vibration immissions to be evaluated | 46 |
| B.9.2 | Assumptions | 48 |
| B.9.3 | Evaluation procedure | 48 |
| B.9.4 | Conclusion | 50 |
| Annex C (informative) Explanatory notes | | 51 |
| C.1 | Explanatory notes re 3.4 | 51 |
| C.2 | Explanatory notes re 4.2.3 | 51 |
| C.3 | Explanatory notes re 5.2 | 51 |
| C.4 | Explanatory notes re 6.4.3 | 51 |
| C.5 | Explanatory notes re 6.5.1.2 | 51 |
| C.6 | Explanatory notes re 6.5.2 | 52 |
| C.7 | Explanatory notes re 6.5.3.1 | 52 |
| C.8 | Explanatory notes re 6.5.3.2 | 53 |
| C.9 | Explanatory notes re 6.5.3.3 | 53 |
| C.10 | Explanatory notes re 6.5.3.6 | 53 |
| C.11 | Explanatory notes re 6.5.4 | 54 |
| Annex D (informative) Prognosis and spectral calculation of KB values | | 55 |
| Bibliography | | 56 |

Figures

| | |
|--|----|
| Figure 1 — Time history of the weighted vibration severity $KB_F(t)$ with representation of the maximum cycle KB_{FTi} values KB_{FTi} | 13 |
| Figure 2 — Flow chart for the evaluation procedure | 17 |
| Figure A.1 — Flow chart for evaluation according to 6.5.4 | 32 |
| Figure B.1 — Time history of the weighted vibration severity $KB_F(t)$ for vibration immissions according to Example 1 (Clause B.1) and Example 2 (Clause B.2) | 35 |
| Figure B.2 — Time history of the weighted vibration severity $KB_F(t)$ for vibration immissions according to Example 3 (Clause B.3) | 36 |
| Figure B.3 — Time history of the weighted vibration severity $KB_F(t)$ for vibration immissions according to Examples 4 (Clause B.4) to Example 6 (Clause B.6) | 38 |
| Figure B.4 — Time histories for vibration immissions as in Example 7 (Clause B.7) | 42 |
| Figure B.5 — Measured time history of the vibration velocity at the centre of a floor of the residential building being investigated | 43 |
| Figure B.6 — Sketch showing the existing track, the planned track and the residential building to be investigated | 46 |
| Figure B.7 — Measured time history of the vibration velocity and the weighted vibration severity at the centre of a floor of the building being investigated..... | 47 |
| Figure C.1 — Relationship between evaluation vibration severity KB_{FTi} , the root-mean-square value of KB_{FTi} for trains $KB_{FTm,Zug}$ and train frequency..... | 52 |

Tables

| | |
|--|----|
| Table 1 — Guideline values A for evaluating vibration immissions occurring in rooms requiring protection..... | 16 |
| Table 2 — Evaluation factors α_{Zug} for taking account of the different characteristics of train passages and track location | 23 |
| Table 3 — A_0 values at night for new railways to be constructed | 25 |
| Table 4 — Guideline values A for effects of vibration generated by construction work (other than blasting)..... | 27 |
| Table 5 — Empirical values for constant c_F for different types of vibration effects | 30 |
| Table B.1 — $KB_{FTi,Zug}$ values determined..... | 44 |
| Table B.2 — Maximum root-mean-square values for KB_{FTi} for train categories..... | 48 |
| Table B.3 — Operating programme for the zero scenario and plan scenario | 49 |