

DIN EN 16613:2025-08 (E)

Glass in building - Laminated glass and laminated safety glass - Determination of interlayer viscoelastic properties

| Contents | Page |
|---|-------------|
| European foreword | 3 |
| Introduction | 4 |
| 1 Scope..... | 5 |
| 2 Normative references..... | 5 |
| 3 Terms and definitions | 5 |
| 4 Symbols and abbreviations | 7 |
| 5 Test procedure..... | 9 |
| 5.1 General..... | 9 |
| 5.2 Test specimens | 11 |
| 5.3 Test method | 11 |
| 5.3.1 Glass transition temperature T_g (Step 1) | 11 |
| 5.3.2 Determination of the temperature and time dependent shear modulus $G_{int}(T,t)$ | 11 |
| 6 Evaluation of the shear transfer characteristics | 15 |
| 6.1 Determination of the temperature and time dependent shear modulus $G_{int}(T,t)$ | 15 |
| 6.2 Load durations and temperature ranges | 15 |
| 7 Test report..... | 16 |
| Annex A (normative) Bending creep method for the determination of the interlayer properties | 17 |
| Annex B (normative) Preparation of test specimens..... | 26 |
| Annex C (informative) Time-temperature-superposition principle and Prony series | 27 |
| Annex D (informative) Interlayer mechanical properties at different frequencies for a chosen temperature..... | 30 |
| Annex E (informative) Determination of the displacement of the point of contact between the support rollers and the plate | 31 |
| Bibliography | 33 |