

DIN EN 1793-5:2026-07 (E)

Road traffic noise reducing devices - Test method for determining the acoustic performance - Part 5: Intrinsic characteristics - Sound absorption under direct sound field conditions

Contents	Page
European foreword	4
Introduction	6
1 Scope	8
2 Normative references	8
3 Terms and definitions	8
4 Symbols and abbreviations	14
5 Sound reflection index measurements	16
5.1 General principle	16
5.2 Measured quantity	17
5.3 Test arrangement	20
5.3.1 General	20
5.3.2 Tests on purposely built full-size test specimens	20
5.3.3 Installed road traffic noise reducing devices	21
5.3.4 Inclined or curved road traffic noise reducing devices	23
5.4 Measuring equipment	26
5.4.1 Components of the measuring system	26
5.4.2 Sound source	27
5.4.3 Test signal	27
5.5 Data processing	28
5.5.1 Calibration	28
5.5.2 Sample rate and filtering	29
5.5.3 Background noise	30
5.5.4 Signal subtraction technique	31
5.5.5 Accurate alignment procedure	32
5.5.6 Adrienne temporal window	34
5.5.7 Placement of the Adrienne temporal window	36
5.5.8 Maximum sampled area	38
5.6 Positioning of the measuring equipment	39
5.6.1 General	39
5.6.2 Selection of the measurement positions	39
5.6.3 Consideration of relevant and parasitic reflections	47
5.6.4 Low-frequency limit	50
5.6.5 Reflecting objects	51
5.6.6 Safety considerations	51
5.7 Test specimen surface and meteorological conditions	51
5.7.1 Condition of the test specimen surface	51
5.7.2 Wind	51
5.7.3 Air temperature	51
5.8 Single-number rating of sound absorption under a direct sound field DLRI	51
6 Measurement uncertainty	52
7 Measuring procedure	52

8	Test report	53
	Annex A (informative) Low-frequency limit and window width	55
	Annex B (normative) Measurement uncertainty	60
	Annex C (normative) Template of test report on sound reflection index of road traffic noise reducing devices	62
	Annex D (normative) Indoor measurements for product qualification	71
	Bibliography	72