

DIN EN 1793-4:2026-07 (E)

Road traffic noise reducing devices - Test method for determining the acoustic performance - Part 4: Intrinsic characteristics - Intrinsic sound diffraction

Contents

Page

European foreword	4
Introduction	6
1 Scope	7
2 Normative references	7
3 Terms and definitions	8
4 Symbols and abbreviations	10
5 Sound diffraction index measurements	12
5.1 General principle	12
5.2 Dimensions and specifications	13
5.2.1 Added devices	13
5.2.2 Reference walls	13
5.2.3 In situ tests	14
5.3 Positions of the sound source	14
5.4 Position of the microphone(s)	14
5.5 Free-field measurements	15
5.6 Measured quantity	23
5.7 Measuring equipment	24
5.7.1 Components of the measuring system	24
5.7.2 Sound source	25
5.7.3 Test signal	26
5.8 Data processing	26
5.8.1 Calibration	26
5.8.2 Sample rate	26
5.8.3 Background noise	27
5.8.4 Measurement points	27
5.8.5 Adrienne temporal window	27
5.8.6 Placement of the Adrienne temporal window	28
5.8.7 Low frequency limit and sample size	30
5.9 Positioning of the measuring equipment	30
5.9.1 Selection of the measurement positions	30
5.9.2 Reflecting objects	31
5.9.3 Safety considerations	31
5.10 Sample surface and meteorological conditions	31
5.10.1 Condition of the sample surface	31
5.10.2 Wind	31
5.10.3 Air temperature	31
5.11 Sound diffraction index difference	31
5.12 Single-number rating of sound diffraction index difference	32
6 Measurement uncertainty	33
7 Measuring procedure	33
8 Test report	34

Annex A (informative) Low-frequency limit and window width	36
Annex B (informative) Measurement uncertainty	41
Annex C (normative) Template of test report on sound diffraction index difference of added devices	44
Annex D (normative) Indoor measurements for product qualification	47
Bibliography	49