DIN EN 1793-4:2026-07 (E)

Road traffic noise reducing devices - Test method for determining the acoustic performance - Part 4: Intrinsic characteristics - Intrinsic sound diffraction

Contents

Page

European foreword 4

Introduction 6

1 Scope 7

2 Normative references 7

3 Terms and definitions 8

4 Symbols and abbreviations 10

5 Sound diffraction index measurements 12
5.1 General principle 12
5.2 Dimensions and specifications 13
5.2.1 Added devices 13
5.2.2 Reference walls 13
5.2.3 In situ tests 14
5.3 Positions of the sound source 14
5.4 Position of the microphone(s) 14
5.5 Free-field measurements 15
5.6 Measured quantity 23
5.7 Measuring equipment 24
5.7.1 Components of the measuring system 24
5.7.2 Sound source 25
5.7.3 Test signal 26
5.8 Data processing 26
5.8.1 Calibration 26
5.8.2 Sample rate 26
5.8.3 Background noise 27
5.8.4 Measurement points 27
5.8.5 Adrienne temporal window 27
5.8.6 Placement of the Adrienne temporal window 28
5.8.7 Low frequency limit and sample size 30
5.9 Positioning of the measuring equipment 30
5.9.1 Selection of the measurement positions 30
5.9.2 Reflecting objects 31
5.9.3 Safety considerations 31
5.10 Sample surface and meteorological conditions 31
5.10.1 Condition of the sample surface 31
5.10.2 Wind 31
5.10.3 Air temperature 31
5.11 Sound diffraction index difference 31
5.12 Single-number rating of sound diffraction index difference 32

6 Measurement uncertainty 33

7 Measuring procedure 33

8 Test report 34

Annex A (informative) Low-frequency limit and window width 36

Annex B (informative) Measurement uncertainty 41

Annex C (normative) Template of test report on sound diffraction index difference of added devices 44

Annex D (normative) Indoor measurements for product qualification 47

Bibliography 49