

ISO 11925-2:2026-01 (E)

Reaction to fire tests - Ignitability of products subjected to direct impingement of flame - Part 2: Single-flame source test

| Contents | | Page |
|-----------------------|---|-------------|
| Foreword | | iv |
| Introduction | | v |
| 1 | Scope | 1 |
| 2 | Normative references | 1 |
| 3 | Terms and definitions | 1 |
| 4 | Test apparatus | 2 |
| 5 | Test specimen | 4 |
| 5.1 | Preparation | 4 |
| 5.2 | Dimensions | 4 |
| 5.3 | Products which are not essentially flat | 4 |
| 5.4 | Number of specimens | 4 |
| 5.5 | Substrates | 5 |
| 6 | Conditioning | 5 |
| 7 | Test procedure | 5 |
| 7.1 | General | 5 |
| 7.2 | Preliminary operations | 5 |
| 7.3 | Testing operations | 5 |
| 7.4 | Duration of test | 7 |
| 8 | Expression of results | 7 |
| 9 | Test report | 8 |
| Annex A (informative) | Precision of test method | 22 |
| Annex B (normative) | Testing not essentially flat end-use products | 25 |
| Annex C (normative) | Testing perforated end-use products | 26 |
| Bibliography | | 27 |