

DIN EN 492:2006-04 (E)

Fibre-cement slates and fittings - Product specification and test methods

| Contents | | Page |
|-----------------|---|-------------|
| 1 | Scope | 5 |
| 2 | Normative references | 5 |
| 3 | Terms and definitions | 5 |
| 4 | Symbols and abbreviations | 6 |
| 5 | Product requirements | 7 |
| 5.1 | General | 7 |
| 5.1.1 | Composition | 7 |
| 5.1.2 | Appearance and finish | 7 |
| 5.2 | Dimensions and tolerance | 8 |
| 5.2.1 | General | 8 |
| 5.2.2 | Thicknesses | 8 |
| 5.2.3 | Tolerances on nominal dimensions | 8 |
| 5.3 | Physical requirements and characteristics for fibre-cement slates | 8 |
| 5.3.1 | General | 8 |
| 5.3.2 | Apparent density | 8 |
| 5.3.3 | Mechanical characteristics | 9 |
| 5.3.4 | Water impermeability | 9 |
| 5.4 | Durability requirements | 9 |
| 5.4.1 | General | 9 |
| 5.4.2 | Freeze-thaw | 9 |
| 5.4.3 | Heat-rain | 10 |
| 5.4.4 | Warm water | 10 |
| 5.4.5 | Soak-dry | 10 |
| 5.5 | Fire and safety | 10 |
| 5.5.1 | External fire performance | 10 |
| 5.5.2 | Reaction to fire | 10 |
| 5.5.3 | Release of dangerous substances | 10 |
| 5.6 | Product information | 10 |
| 6 | Evaluation of conformity | 11 |
| 6.1 | General | 11 |
| 6.2 | Type testing | 11 |
| 6.2.1 | General | 11 |
| 6.2.2 | Initial type testing | 11 |
| 6.2.3 | Further type testing | 11 |
| 6.3 | Factory Production Control (FPC) | 12 |
| 6.3.1 | General | 12 |
| 6.3.2 | Acceptance tests | 12 |
| 6.3.3 | Equipment | 13 |
| 6.3.4 | Raw materials and components | 13 |
| 6.3.5 | Product testing and evaluation | 13 |
| 6.3.6 | Non-conforming products | 14 |
| 6.4 | Inspection of a consignment of finished products | 14 |
| 7 | Test methods | 14 |
| 7.1 | General | 14 |
| 7.2 | Dimensional tests | 14 |
| 7.2.1 | Preparation of specimen | 14 |

| | | |
|--|--|----|
| 7.2.2 | Apparatus | 14 |
| 7.2.3 | Procedure | 14 |
| 7.2.4 | Expression and interpretation of results | 14 |
| 7.3 | Tests for physical performance and characteristics | 15 |
| 7.3.1 | Apparent density | 15 |
| 7.3.2 | Mechanical characteristics: Breaking load test | 15 |
| 7.3.3 | Water impermeability | 18 |
| 7.3.4 | Warm water | 18 |
| 7.3.5 | Soak-dry | 19 |
| 7.4 | Tests for climatic performance | 20 |
| 7.4.1 | Freeze-thaw | 20 |
| 7.4.2 | Heat-rain | 22 |
| 7.5 | Test for fire performance | 23 |
| 7.5.1 | Test for external fire performance | 23 |
| 7.5.2 | Test for reaction to fire | 23 |
| 8 | Marking, labelling and packaging | 24 |
| Annex A (normative) Consignment inspection sampling | | 25 |
| Annex B (normative) Statistical method for determining the corresponding wet values or revised dry specifications for the bending moment when carrying out the dry method of test for quality control purposes | | 26 |
| B.1 | Procedure | 26 |
| B.2 | Determination of the correlation between the results of testing wet and dry specimens ... | 26 |
| B.3 | Determination of the regression line | 27 |
| B.4 | Determination of a value for wet testing from an obtained value for dry testing | 27 |
| B.5 | Determination of the minimum value specified for dry testing x_{std} corresponding to the minimum value specified for wet testing in this standard y_{std} | 28 |
| Annex C (informative) Examples | | 30 |
| C.1 | Examples of dimension h | 30 |
| C.2 | Examples of fibre-cement slates installed showing lines of fixing | 31 |
| Annex D (normative) Requirements of Decision 2001/671/EC as regards the external fire performance of roof coverings | | 33 |
| Annex ZA (informative) Clauses of this European Standard addressing the provisions of the EU Construction Products Directive | | 34 |
| ZA.1 | Scope and relevant characteristics | 34 |
| ZA.2 | Procedure for the attestation of conformity of fibre cement slates and fittings | 36 |
| ZA.2.1 | Systems of attestation of conformity | 36 |
| ZA.2.2 | EC Declaration of conformity | 38 |
| ZA.3 | CE marking | 39 |
| Bibliography | | 41 |