

DIN EN 13022-1:2006-08 (E)

Glass in building - Structural sealant glazing - Part 1: Glass products for structural sealant glazing systems for supported and unsupported monolithic and multiple glazing

| Contents | | Page |
|-----------------|--|-------------|
| Foreword | | 4 |
| 1 | Scope | 5 |
| 2 | Normative references | 8 |
| 3 | Symbols, terminology, terms and definitions | 9 |
| 3.1 | Symbols | 9 |
| 3.2 | Terminology | 10 |
| 3.3 | Terms and definitions | 11 |
| 4 | Characteristics of glass products - requirements | 12 |
| 4.1 | Appropriate glass products | 12 |
| 4.2 | Dimensional tolerances | 13 |
| 4.3 | Glass shapes | 13 |
| 4.3.1 | Curved glass | 13 |
| 4.4 | Corners, notches and holes | 13 |
| 5 | Verification of the suitability of glass products for use in SSG systems when exposed to UV radiation | 14 |
| 5.1 | General | 14 |
| 5.2 | Insulating glass unit (IGU) | 14 |
| 5.2.1 | Situation 1 (see Figure 2 of the scope) | 14 |
| 5.2.2 | Situation 2 (see Figure 2 of the scope) | 15 |
| 5.2.3 | Coated glass | 15 |
| 5.2.4 | Possibility to substitute the outer IGU seal | 16 |
| 5.2.5 | Further requirements for the outer IGU seal when in an unsupported case | 16 |
| 5.3 | Monolithic glass or laminated glass, Situation 3 (see Figure 2) | 16 |
| 5.4 | Assessment of the adhesion between the sealant and the glass | 16 |
| 5.4.1 | Clear float | 16 |
| 5.4.2 | Coated glass | 16 |
| 5.4.3 | Enamelled glass | 17 |
| 5.4.4 | Patterned glass | 17 |
| 6 | Design | 17 |
| 6.1 | Calculation of the thickness of the glass | 17 |
| 6.2 | Calculation of the height of the outer sealant of the insulating glass unit for supported and unsupported glazing | 17 |
| 6.2.1 | Supported insulating glass unit | 17 |
| 6.3 | Calculation of the height of the outer sealant of the insulating glass unit for unsupported glazing | 21 |
| 6.3.1 | Calculation of the height regarding the relevant combined load of the wind, snow and self weight and relevant combined load for wind, snow and self weight | 21 |
| 6.3.2 | Calculation of the height of the outer seal to bear the permanent shear loading | 21 |
| 7 | Minimum glass thickness | 22 |
| 7.1 | General case | 22 |
| 7.2 | Case of glass with worked edges | 23 |

| | |
|---|-----------|
| Annex A (informative) Assembly requirement | 24 |
| A.1 Setting blocks for glass panes or Insulating Glass Units | 24 |
| A.1.1 General case | 24 |
| A.1.2 Supporting the self-weight of a monolithic glass | 26 |
| A.2 Water drainage from the system | 26 |
| Bibliography | 27 |