

DIN EN 1998-2 :2006-06 (E)

Eurocode_8: Design of structures for earthquake resistance_ - Part_2

TABLE OF CONTENTS

| | |
|---|-----------|
| FOREWORD | 7 |
| 1 INTRODUCTION | 11 |
| 1.1 SCOPE | 11 |
| 1.1.1 <i>Scope of EN 1998-2</i> | 11 |
| 1.1.2 <i>Further parts of EN 1998</i> | 12 |
| 1.2 NORMATIVE REFERENCES | 12 |
| 1.2.1 <i>Use</i> | 12 |
| 1.2.2 <i>General reference standards</i> | 12 |
| 1.2.3 <i>Reference Codes and Standards</i> | 12 |
| 1.2.4 <i>Additional general and other reference standards for bridges</i> | 12 |
| 1.3 ASSUMPTIONS | 13 |
| 1.4 DISTINCTION BETWEEN PRINCIPLES AND APPLICATION RULES | 13 |
| 1.5 DEFINITIONS | 13 |
| 1.5.1 <i>General</i> | 13 |
| 1.5.2 <i>Terms common to all Eurocodes</i> | 13 |
| 1.5.3 <i>Further terms used in EN 1998-2</i> | 13 |
| 1.6 SYMBOLS | 15 |
| 1.6.1 <i>General</i> | 15 |
| 1.6.2 <i>Further symbols used in Sections 2 and 3 of EN 1998-2</i> | 15 |
| 1.6.3 <i>Further symbols used in Section 4 of EN 1998-2</i> | 16 |
| 1.6.4 <i>Further symbols used in Section 5 of EN 1998-2</i> | 17 |
| 1.6.5 <i>Further symbols used in Section 6 of EN 1998-2</i> | 18 |
| 1.6.6 <i>Further symbols used in Section 7 and Annexes J, JJ and K of EN 1998-2</i> | 220 |
| 2 BASIC REQUIREMENTS AND COMPLIANCE CRITERIA..... | 23 |
| 2.1 DESIGN SEISMIC ACTION | 23 |
| 2.2 BASIC REQUIREMENTS | 24 |
| 2.2.1 <i>General</i> | 24 |
| 2.2.2 <i>No-collapse (ultimate limit state)</i> | 24 |
| 2.2.3 <i>Minimisation of damage (serviceability limit state)</i> | 25 |
| 2.3 COMPLIANCE CRITERIA | 25 |
| 2.3.1 <i>General</i> | 25 |
| 2.3.2 <i>Intended seismic behaviour</i> | 25 |
| 2.3.3 <i>Resistance verifications</i> | 28 |
| 2.3.4 <i>Capacity design</i> | 28 |
| 2.3.5 <i>Provisions for ductility</i> | 28 |
| 2.3.6 <i>Connections - Control of displacements - Detailing</i> | 31 |
| 2.3.7 <i>Simplified criteria</i> | 35 |
| 2.4 CONCEPTUAL DESIGN | 35 |
| 3 SEISMIC ACTION | 38 |
| 3.1 DEFINITION OF THE SEISMIC ACTION | 38 |
| 3.1.1 <i>General</i> | 38 |
| 3.1.2 <i>Application of the components of the motion</i> | 38 |
| 3.2 QUANTIFICATION OF THE COMPONENTS | 38 |
| 3.2.1 <i>General</i> | 38 |

| | | |
|----------|---|-----------|
| 3.2.2 | <i>Site dependent elastic response spectrum</i> | 39 |
| 3.2.3 | <i>Time-history representation</i> | 39 |
| 3.2.4 | <i>Site dependent design spectrum for linear analysis</i> | 40 |
| 3.3 | SPATIAL VARIABILITY OF THE SEISMIC ACTION | 40 |
| 4 | ANALYSIS | 44 |
| 4.1 | MODELLING | 44 |
| 4.1.1 | <i>Dynamic degrees of freedom</i> | 44 |
| 4.1.2 | <i>Masses</i> | 44 |
| 4.1.3 | <i>Damping of the structure and stiffness of members</i> | 45 |
| 4.1.4 | <i>Modelling of the soil</i> | 45 |
| 4.1.5 | <i>Torsional effects</i> | 46 |
| 4.1.6 | <i>Behaviour factors for linear analysis</i> | 47 |
| 4.1.7 | <i>Vertical component of the seismic action</i> | 50 |
| 4.1.8 | <i>Regular and irregular seismic behaviour of ductile bridges</i> | 50 |
| 4.1.9 | <i>Non-linear analysis of irregular bridges</i> | 51 |
| 4.2 | METHODS OF ANALYSIS | 51 |
| 4.2.1 | <i>Linear dynamic analysis - Response spectrum method</i> | 51 |
| 4.2.2 | <i>Fundamental mode method</i> | 53 |
| 4.2.3 | <i>Alternative linear methods</i> | 57 |
| 4.2.4 | <i>Non-linear dynamic time-history analysis</i> | 57 |
| 4.2.5 | <i>Static non-linear analysis (pushover analysis)</i> | 59 |
| 5 | STRENGTH VERIFICATION | 61 |
| 5.1 | GENERAL | 61 |
| 5.2 | MATERIALS AND DESIGN STRENGTH | 61 |
| 5.2.1 | <i>Materials</i> | 61 |
| 5.2.2 | <i>Design strength</i> | 61 |
| 5.3 | CAPACITY DESIGN | 61 |
| 5.4 | SECOND ORDER EFFECTS | 63 |
| 5.5 | COMBINATION OF THE SEISMIC ACTION WITH OTHER ACTIONS | 64 |
| 5.6 | RESISTANCE VERIFICATION OF CONCRETE SECTIONS | 65 |
| 5.6.1 | <i>Design resistance</i> | 65 |
| 5.6.2 | <i>Structures of limited ductile behaviour</i> | 65 |
| 5.6.3 | <i>Structures of ductile behaviour</i> | 65 |
| 5.7 | RESISTANCE VERIFICATION FOR STEEL AND COMPOSITE MEMBERS | 73 |
| 5.7.1 | <i>Steel piers</i> | 73 |
| 5.7.2 | <i>Steel or composite deck</i> | 74 |
| 5.8 | FOUNDATIONS | 74 |
| 5.8.1 | <i>General</i> | 74 |
| 5.8.2 | <i>Design action effects</i> | 75 |
| 5.8.3 | <i>Resistance verification</i> | 75 |
| 6 | DETAILING | 76 |
| 6.1 | GENERAL | 76 |
| 6.2 | CONCRETE PIERS | 76 |
| 6.2.1 | <i>Confinement</i> | 76 |
| 6.2.2 | <i>Buckling of longitudinal compression reinforcement</i> | 80 |
| 6.2.3 | <i>Other rules</i> | 81 |
| 6.2.4 | <i>Hollow piers</i> | 82 |
| 6.3 | STEEL PIERS | 82 |

| | | |
|---|--|------------|
| 6.4 | FOUNDATIONS | 82 |
| 6.4.1 | <i>Spread foundation</i> | 82 |
| 6.4.2 | <i>Pile foundations</i> | 82 |
| 6.5 | STRUCTURES OF LIMITED DUCTILE BEHAVIOUR | 83 |
| 6.5.1 | <i>Verification of ductility of critical sections</i> | 83 |
| 6.5.2 | <i>Avoidance of brittle failure of specific non-ductile components</i> | 83 |
| 6.6 | BEARINGS AND SEISMIC LINKS | 84 |
| 6.6.1 | <i>General requirements</i> | 84 |
| 6.6.2 | <i>Bearings</i> | 85 |
| 6.6.3 | <i>Seismic links, holding-down devices, shock transmission units</i> | 86 |
| 6.6.4 | <i>Minimum overlap lengths</i> | 88 |
| 6.7 | CONCRETE ABUTMENTS AND RETAINING WALLS | 90 |
| 6.7.1 | <i>General requirements</i> | 90 |
| 6.7.2 | <i>Abutments flexibly connected to the deck</i> | 90 |
| 6.7.3 | <i>Abutments rigidly connected to the deck</i> | 90 |
| 6.7.4 | <i>Culverts with large overburden</i> | 92 |
| 6.7.5 | <i>Retaining walls</i> | 93 |
| 7 | BRIDGES WITH SEISMIC ISOLATION | 94 |
| 7.1 | GENERAL | 94 |
| 7.2 | DEFINITIONS..... | 94 |
| 7.3 | BASIC REQUIREMENTS AND COMPLIANCE CRITERIA | 95 |
| 7.4 | SEISMIC ACTION | 96 |
| 7.4.1 | <i>Design spectra</i> | 96 |
| 7.4.2 | <i>Time-history representation</i> | 96 |
| 7.5 | ANALYSIS PROCEDURES AND MODELLING..... | 96 |
| 7.5.1 | <i>General</i> | 96 |
| 7.5.2 | <i>Design properties of the isolating system</i> | 97 |
| 7.5.3 | <i>Conditions for application of analysis methods</i> | 103 |
| 7.5.4 | <i>Fundamental mode spectrum analysis</i> | 103 |
| 7.5.5 | <i>Multi-mode Spectrum Analysis</i> | 107 |
| 7.5.6 | <i>Time history analysis</i> | 108 |
| 7.5.7 | <i>Vertical component of seismic action</i> | 108 |
| 7.6 | VERIFICATIONS | 108 |
| 7.6.1 | <i>Seismic design situation</i> | 108 |
| 7.6.2 | <i>Isolating system</i> | 108 |
| 7.6.3 | <i>Substructures and superstructure</i> | 110 |
| 7.7 | SPECIAL REQUIREMENTS FOR THE ISOLATING SYSTEM | 111 |
| 7.7.1 | <i>Lateral restoring capability</i> | 111 |
| 7.7.2 | <i>Lateral restraint at the isolation interface</i> | 113 |
| 7.7.3 | <i>Inspection and Maintenance</i> | 113 |
| ANNEX A (INFORMATIVE) PROBABILITIES RELATED TO THE REFERENCE SEISMIC ACTION. GUIDANCE FOR THE SELECTION OF DESIGN SEISMIC ACTION DURING THE CONSTRUCTION PHASE | | 114 |
| ANNEX B (INFORMATIVE) RELATIONSHIP BETWEEN DISPLACEMENT DUCTILITY AND CURVATURE DUCTILITY FACTORS OF PLASTIC HINGES IN CONCRETE PIERS..... | | 115 |
| ANNEX C (INFORMATIVE) ESTIMATION OF THE EFFECTIVE STIFFNESS OF REINFORCED CONCRETE DUCTILE MEMBERS..... | | 116 |

| | |
|--|------------|
| ANNEX D (INFORMATIVE) SPATIAL VARIABILITY OF EARTHQUAKE GROUND MOTION: MODEL AND METHODS OF ANALYSIS..... | 118 |
| ANNEX E (INFORMATIVE) PROBABLE MATERIAL PROPERTIES AND PLASTIC HINGE DEFORMATION CAPACITIES FOR NON-LINEAR ANALYSES | 125 |
| ANNEX F (INFORMATIVE) ADDED MASS OF ENTRAINED WATER FOR IMMersed PIERS..... | 131 |
| ANNEX G (NORMATIVE) CALCULATION OF CAPACITY DESIGN EFFECTS | 133 |
| ANNEX H (INFORMATIVE) STATIC NON-LINEAR ANALYSIS (PUSHOVER) | 135 |
| ANNEX J (NORMATIVE) VARIATION OF DESIGN PROPERTIES OF SEISMIC ISOLATOR UNITS..... | 138 |
| ANNEX JJ (INFORMATIVE) λ-FACTORS FOR COMMON ISOLATOR TYPES | 140 |
| ANNEX K (INFORMATIVE) TESTS FOR VALIDATION OF DESIGN PROPERTIES OF SEISMIC ISOLATOR UNITS..... | 143 |